

ISO/IEC 23290:2004-10 (E)

Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network (PISN) - Mapping functions for the tunnelling of QSIG through H.323 networks

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Terms and definitions	2
4.1	External definitions	2
4.2	Other definitions	2
4.2.1	Call	2
4.2.2	Channel	3
4.2.3	Inter-PINX Connection (IPC)	3
4.2.4	Inter-PINX Link (IPL)	3
4.2.5	PINX roles	3
5	List of acronyms	3
6	Introduction	4
6.1	Reference configuration	4
6.2	Specific scenarios	4
6.3	Relationship with H.323 gateways	5
7	Capabilities at the Q reference point	6
8	Capabilities at the C reference point	6
9	Mapping functions	7
9.1	General requirements	7
9.2	Mapping of the DQ-channel	7
9.3	Mapping of the UQ-channel(s)	7
9.3.1	On-demand scenario	7
9.3.2	Semi-permanent scenario	7
10	IPC control procedures	8
10.1	Protocol identification	8
10.2	Registration with gatekeeper	8
10.3	Systems without gatekeeper	8
10.4	H.323 call establishment	8
10.4.1	Call admission	8
10.4.2	Outgoing call establishment	9
10.4.3	Incoming call establishment	9
10.5	Transfer of inter-PINX signalling information	10
10.6	H.323 call clearing	10
11	Scenario specific procedures	10

11.1	On-demand scenario	10
11.2	Semi-permanent scenario	11
Annex A (normative) Implementation Conformance Statement (ICS) Proforma		13
Annex B (informative) Examples of message sequences		20