DIN V 66401:2005-06 (E)

UIM - The unique identification mark - Application requirements for very small items using matrix symbols

Inhalt

Seite

1 Scope 4
2 Normative references 4
3 Terms and definitions 5
4 Unique Identification Mark (UIM) 6
4.1 Symbologies for Unique Identification Marks 7
4.1.1 Module sizes – X-dimensions 7
4.1.2 Quiet zone 7
4.1.3 Print quality 7
4.2 The unique data element 7
4.2.1 Construction of a unique data element 7
4.2.2 Data Identifiers (DI) 8
4.2.3 System Identifier (SI) 8
4.2.4 Issuing Agency Codes (IAC) and Company Identification Codes (CIN) 8
5 Human readable information attached to UIM 8
Annex A (informative) Minimum sizes of a Unique Identification Mark 9
A.1 Size of a UIM with DI “25S” and a serial number 9
A.2 Size of a UIM with DI “25T” and a lot or batch number 9
A.3 Size of a UIM with System Identifier “+” and a product code combined with serial number or lot number 10
Annex B (informative) Data Matrix symbols 11
B.1 Data Matrix formats 11
B.2 Black or white print 11
B.3 Symbol sizes 11
B.3.1 Square format 11
B.3.2 Rectangular format 12
Annex C (informative) QR Code 13
C.1 Symbol sizes 13
C.2 QR symbol sizes 13
Annex D (informative) Capacity and symbol sizes of UIMs 15
D.1 Capacity and symbol sizes of UIMs with a serial number 15
D.2 Capacity and symbol sizes of UIMs with a lot number 15
D.3 Capacity and symbol sizes of UIMs with SI “+”, combined product and serial or lot number 15
D.4 Relation of symbol sizes and module sizes 16
Annex E (informative) Unique Identification Mark using Application Identifiers (AI) 18
Annex F (informative) System considerations 19
Bibliography 20