

DIN V 66401:2005-06 (E)

UIM - The unique identification mark - Application requirements for very small items using matrix symbols

Inhalt	Seite
1 Scope.....	4
2 Normative references.....	4
3 Terms and definitions.....	5
4 Unique Identification Mark (UIM).....	6
4.1 Symbologies for Unique Identification Marks.....	7
4.1.1 Module sizes – X-dimensions.....	7
4.1.2 Quiet zone.....	7
4.1.3 Print quality.....	7
4.2 The unique data element.....	7
4.2.1 Construction of a unique data element.....	7
4.2.2 Data Identifiers (DI).....	8
4.2.3 System Identifier (SI).....	8
4.2.4 Issuing Agency Codes (IAC) and Company Identification Codes (CIN).....	8
5 Human readable information attached to UIM.....	8
Annex A (informative) Minimum sizes of a Unique Identification Mark.....	9
A.1 Size of a UIM with DI “25S” and a serial number.....	9
A.2 Size of a UIM with DI “25T” and a lot or batch number.....	9
A.3 Size of a UIM with System Identifier “+” and a product code combined with serial number or lot number.....	10
Annex B (informative) Data Matrix symbols.....	11
B.1 Data Matrix formats.....	11
B.2 Black or white print.....	11
B.3 Symbol sizes.....	11
B.3.1 Square format.....	11
B.3.2 Rectangular format.....	12
Annex C (informative) QR Code.....	13
C.1 Symbol sizes.....	13
C.2 QR symbol sizes.....	13
Annex D (informative) Capacity and symbol sizes of UIMs.....	15
D.1 Capacity and symbol sizes of UIMs with a serial number.....	15
D.2 Capacity and symbol sizes of UIMs with a lot number.....	15
D.3 Capacity and symbol sizes of UIMs with SI “+”, combined product and serial or lot number.....	15
D.4 Relation of symbol sizes and module sizes.....	16
Annex E (informative) Unique Identification Mark using Application Identifiers (AI).....	18
Annex F (informative) System considerations.....	19
Bibliography.....	20