ISO/IEC 8802-2:1998-06 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan ar ea networks - Specific requirements - Part 2: Logical link control

Contents

Page

1. Overview 1
1.1 Scope and purpose 1
1.2 Standards compatibility 3
1.3 Normative references 3
1.4 Acronyms and definitions 5
1.5 Conformance 11

2. LLC sublayer Service specifications 12
2.1 General 12
2.2 Network layer/LLC sublayer interface Service specification 14
2.3 LLC sublayer/MAC sublayer interface Service specification 35
2.4 LLC sublayer/LLC sublayer management function interface service specification 38

3. LLC PDU structure 39
3.1 General 39
3.2 LLC PDU format 39
3.3 Elements of the LLC PDU 39

4. LLC types and classes of procedures 42
4.1 General 42
4.2 Classes of LLC (conformance clause) 43
4.3 Support of route determination entity (RDE) (conformance clause) 45

5. LLC Clements of procedure 46
5.1 General 46
5.2 Control field formats 46
5.3 Control field parameters 47
5.4 Commands and responses 50

6. LLC description of the Type 1 procedures 62
6.1 Mode of Operation 62
6.2 Procedure for addressing 62
6.3 Procedure for the use of the P/F bit 62
6.4 Procedures for logical data link setup and disconnection 62
6.5 Procedures for information transfer 62
6.6 Uses of the XID command PDU and response PDU 63
6.7 Uses of the TEST command PDU and response PDU 63
6.8 List of logical data link parameters 64
6.9 Precise description of the Type 1 procedures 64

7. LLC description of the Type 2 procedures 73
7.1 Modes 73
7.2 Procedure for addressing 74
7.3 Procedures for the use of the P/F bit 74
7.4 Procedures for data link setup and disconnection 74
7.5 Procedures for information transfer 76
7.6 Procedures for resetting 80
7.7 FRMR exception conditions 81
7.8 List of data link connection parameters 82
7.9 Precise description the Type 2 procedures 83

8. LLC description of the Type 3 proccdures 115
8.1 Modes of operation 115
8.2 Procedure for addressing 115
8.3 Procedure for the use of the P/F bit1 115
8.4 Procedures for link setup and disconnection 115
8.5 Procedures for information transfer 116
8.6 List of logical link parameters 119
8.7 Precise description of Type 3 procedures 121

9. LLC RDE procedures 130
9.1 Overview of RDE 130
9.2 Support of the LLC service 130
9.3 Principles of operation 135
9.4 Encoding of RDE PDUs 139
9.5 Encoding of the routing Information field (RIF) 140
9.6 RDE route control process 140
9.7 The route determination component (RDC) 147

10. LLC sublayer managed objects 154
10.1 LLCStation managed object 155
10.2 ILCSAP managed object 162
10.3 LLCConnectionless managed object 163
10.4 LLCConnection2 managed object 167
10.5 LLCConnection2IVMO managed object 180
10.6 LLCConnectionlessAck managed object 181
10.7 LLCConnectionlessAckIVMO managed object 188
10.8 RDE Setup managed object 189
10.9 1 RDE pair managed object 191
10.10 Resource Type ID managed object 193
10.11 Conformance 194
10.12 ASN.I LLCDefinitions 194

ANNEX

Annex A (normative) Protocol Implementation Conformance Statement (PICS) proforma 199

Annex B (informative) Relationship between LLC Type 3 and PROWAY (IEC 60955 : 1989) 223

Annex C (informative) LLC flow control techniques for bridged LANs 228

Annex D (informative) Subnetwork access protocol support 230

Annex E (normative) Allocation of object identifier values 231