

ISO/IEC 8802-2:1998-06 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 2: Logical link control

Contents	Page
1. Overview.....	1
1.1 Scope and purpose	1
1.2 Standards compatibility.....	3
1.3 Normative references.....	3
1.4 Acronyms and definitions	5
1.5 Conformance	11
2. LLC sublayer Service specifications.....	12
2.1 General	12
2.2 Network layer/LLC sublayer interface Service specification.....	14
2.3 LLC sublayer/MAC sublayer interface Service specification	35
2.4 LLC sublayer/LLC sublayer management function interface service specification	38
3. LLC PDU structure	39
3.1 General	39
3.2 LLC PDU format.....	39
3.3 Elements of the LLC PDU	39
4. LLC types and classes of procedures.....	42
4.1 General	42
4.2 Classes of LLC (conformance clause)	43
4.3 Support of route determination entity (RDE) (conformance clause)	45
5. LLC Elements of procedure	46
5.1 General	46
5.2 Control field formats	46
5.3 Control field parameters.....	47
5.4 Commands and responses	50
6. LLC description of the Type 1 procedures	62
6.1 Mode of Operation.....	62
6.2 Procedure for addressing.....	62
6.3 Procedure for the use of the P/F bit	62
6.4 Procedures for logical data link setup and disconnection	62
6.5 Procedures for information transfer.....	62
6.6 Uses of the XID command PDU and response PDU	63
6.7 Uses of the TEST command PDU and response PDU	63
6.8 List of logical data link parameters	64
6.9 Precise description of the Type 1 procedures	64
7. LLC description of the Type 2 procedures	73
7.1 Modes	73
7.2 Procedure for addressing.....	74
7.3 Procedures for the use of the P/F bit	74
7.4 Procedures for data link setup and disconnection.....	74
7.5 Procedures for information transfer.....	76
7.6 Procedures for resetting.....	80
7.7 FRMR exception conditions	81
7.8 List of data link connection parameters	82
7.9 Precise description the Type 2 procedures.....	83

8.	LLC description of the Type 3 procedures	115
8.1	Modes of operation.....	115
8.2	Procedure for addressing	115
8.3	Procedure for the use of the P/F bit1	115
8.4	Procedures for link setup and disconnection	115
8.5	Procedures for information transfer	116
8.6	List of logical link parameters.....	119
8.7	Precise description of Type 3 procedures	121
9.	LLC RDE procedures.....	130
9.1	Overview of RDE.....	130
9.2	Support of the LLC service.....	130
9.3	Principles of operation.....	135
9.4	Encoding of RDE PDUs	139
9.5	Encoding of the routing Information field (RIF).....	140
9.6	RDE route control process	140
9.7	The route determination component (RDC).....	147
10.	LLC sublayer managed objects	154
10.1	LLCStation managed object	155
10.2	ILCSAP managed object	162
10.3	LLCConnectionless managed object	163
10.4	LLCConnection2 managed object.....	167
10.5	LLCConnection2IVMO managed object	180
10.6	LLCConnectionlessAck managed object.....	181
10.7	LLCConnectionlessAckIVMO managed object.....	188
10.8	RDE Setup managed object	189
10.9	1 RDE pair managed object	191
10.10	Resource Type ID managed object.....	193
10.11	Conformance	194
10.12	ASN.I LLCDefinitions.....	194

ANNEX

Annex A (normative) Protocol Implementation Conformance Statement (PICS) proforma.....	199
Annex B (informative) Relationship between LLC Type 3 and PROWAY (IEC 60955 : 1989)	223
Annex C (informative) LLC flow control techniques for bridged LANs	228
Annex D (informative) Subnetwork access protocol.....	230
Annex E (normative) Allocation of object identifier values.....	231