

# ISO/IEC 8802-11 :2005-08 (E)

## Information technology\_ - Telecommunications and information exchange between systems\_ - Local and metropolitan area networks\_ - Specific requirements\_ - Part\_11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications

---

### Contents

|         |   |    |
|---------|---|----|
| 1.      | Overview.....   | 1  |
| 1.1     | Scope.....  | 1  |
| 1.2     | Purpose.....  | 1  |
| 2.      | Normative references.....                                     | 3  |
| 3.      | Definitions .....   | 5  |
| 4.      | Abbreviations and acronyms .....                              | 9  |
| 5.      | General description .....                                     | 13 |
| 5.1     | General description of the architecture .....                 | 13 |
| 5.1.1   | How wireless LAN systems are different .....                  | 13 |
| 5.1.1.1 | Destination address does not equal destination location ..... | 13 |
| 5.1.1.2 | The media impact the design .....                             | 13 |
| 5.1.1.3 | The impact of handling mobile stations.....                   | 13 |
| 5.1.1.4 | Interaction with other IEEE 802 layers.....                   | 14 |
| 5.2     | Components of the IEEE 802.11 architecture.....               | 14 |
| 5.2.1   | The independent BSS (IBSS) as an ad hoc network.....          | 14 |
| 5.2.1.1 | STA to BSS association is dynamic .....                       | 14 |
| 5.2.2   | Distribution system (DS) concepts .....                       | 15 |
| 5.2.2.1 | Extended service set (ESS): The large coverage network .....  | 15 |
| 5.2.3   | Area concepts.....  | 16 |
| 5.2.4   | Integration with wired LANs .....                             | 18 |
| 5.3     | Logical service interfaces.....                               | 18 |
| 5.3.1   | SS.....   | 19 |
| 5.3.2   | DSS .....   | 19 |
| 5.3.3   | Multiple logical address spaces .....                         | 20 |
| 5.4     | Overview of the services.....                                 | 21 |
| 5.4.1   | Distribution of messages within a DS.....                     | 21 |
| 5.4.1.1 | Distribution .....  | 21 |
| 5.4.1.2 | Integration .....   | 22 |
| 5.4.2   | Services that support the distribution service .....          | 22 |
| 5.4.2.1 | Mobility types .....  | 22 |
| 5.4.2.2 | Association.....  | 22 |
| 5.4.2.3 | Reassociation .....   | 23 |
| 5.4.2.4 | Disassociation .....  | 23 |
| 5.4.3   | Access and confidentiality control services.....              | 23 |
| 5.4.3.1 | Authentication.....   | 24 |
| 5.4.3.2 | Deauthentication .....  | 25 |
| 5.4.3.3 | Privacy .....   | 25 |
| 5.5     | Relationships between services.....                           | 25 |
| 5.6     | Differences between ESS and IBSS LANs.....                    | 27 |
| 5.7     | Message information contents that support the services.....   | 28 |
| 5.7.1   | Data .....  | 29 |
| 5.7.2   | Association.....  | 29 |
| 5.7.3   | Reassociation .....   | 29 |
| 5.7.4   | Disassociation .....  | 30 |
| 5.7.5   | Privacy .....   | 30 |

|          |   |    |
|----------|---|----|
| 5.7.6    | Authentication.....                                   | 30 |
| 5.7.7    | Deauthentication.....                                 | 31 |
| 5.8      | Reference model.....                                  | 31 |
| 6.       | MAC service definition.....                           | 33 |
| 6.1      | Overview of MAC services.....                         | 33 |
| 6.1.1    | Asynchronous data service.....                        | 33 |
| 6.1.2    | Security services.....                                | 33 |
| 6.1.3    | MSDU ordering.....                                    | 33 |
| 6.2      | Detailed service specification.....                   | 34 |
| 6.2.1    | MAC data services.....                                | 34 |
| 6.2.1.1  | MA-UNITDATA.request.....                              | 34 |
| 6.2.1.2  | MA-UNITDATA.indication.....                           | 35 |
| 6.2.1.3  | MA-UNITDATA-STATUS.indication.....                    | 36 |
| 7.       | Frame formats.....                                    | 39 |
| 7.1      | MAC frame formats.....                                | 39 |
| 7.1.1    | Conventions.....                                      | 39 |
| 7.1.2    | General frame format.....                             | 39 |
| 7.1.3    | Frame fields.....                                     | 40 |
| 7.1.3.1  | Frame Control field.....                              | 40 |
| 7.1.3.2  | Duration/ID field.....                                | 43 |
| 7.1.3.3  | Address fields.....                                   | 43 |
| 7.1.3.4  | Sequence Control field.....                           | 45 |
| 7.1.3.5  | Frame Body field.....                                 | 45 |
| 7.1.3.6  | FCS field.....  | 45 |
| 7.2      | Format of individual frame types.....                 | 46 |
| 7.2.1    | Control frames.....                                   | 46 |
| 7.2.1.1  | RTS frame format.....                                 | 46 |
| 7.2.1.2  | CTS frame format.....                                 | 47 |
| 7.2.1.3  | ACK frame format.....                                 | 47 |
| 7.2.1.4  | PS-Poll frame format.....                             | 47 |
| 7.2.1.5  | CF-End frame format.....                              | 48 |
| 7.2.1.6  | CF-End+CF-Ack frame format.....                       | 48 |
| 7.2.2    | Data frames.....                                      | 48 |
| 7.2.3    | Management frames.....                                | 50 |
| 7.2.3.1  | Beacon frame format.....                              | 51 |
| 7.2.3.2  | IBSS ATIM frame format.....                           | 52 |
| 7.2.3.3  | Disassociation frame format.....                      | 52 |
| 7.2.3.4  | Association Request frame format.....                 | 52 |
| 7.2.3.5  | Association Response frame format.....                | 52 |
| 7.2.3.6  | Reassociation Request frame format.....               | 53 |
| 7.2.3.7  | Reassociation Response frame format.....              | 53 |
| 7.2.3.8  | Probe Request frame format.....                       | 53 |
| 7.2.3.9  | Probe Response frame format.....                      | 54 |
| 7.2.3.10 | Authentication frame format.....                      | 55 |
| 7.2.3.11 | Deauthentication.....                                 | 55 |
| 7.3      | Management frame body components.....                 | 56 |
| 7.3.1    | Fixed fields.....                                     | 56 |
| 7.3.1.1  | Authentication Algorithm Number field.....            | 56 |
| 7.3.1.2  | Authentication Transaction Sequence Number field..... | 56 |
| 7.3.1.3  | Beacon Interval field.....                            | 56 |

|          |   |    |
|----------|---|----|
| 7.3.1.4  | Capability Information field .....                  | 56 |
| 7.3.1.5  | Current AP Address field.....                       | 58 |
| 7.3.1.6  | Listen Interval field.....                          | 59 |
| 7.3.1.7  | Reason Code field.....                              | 59 |
| 7.3.1.8  | AID field .....                                     | 60 |
| 7.3.1.9  | Status Code field .....                             | 60 |
| 7.3.1.10 | Timestamp field .....                               | 61 |
| 7.3.2    | Information elements .....                          | 61 |
| 7.3.2.1  | SSID element .....                                  | 62 |
| 7.3.2.2  | Supported Rates element .....                       | 62 |
| 7.3.2.3  | FH Parameter Set element .....                      | 63 |
| 7.3.2.4  | DS Parameter Set element .....                      | 63 |
| 7.3.2.5  | CF Parameter Set element.....                       | 64 |
| 7.3.2.6  | TIM .....   | 64 |
| 7.3.2.7  | IBSS Parameter Set element.....                     | 65 |
| 7.3.2.8  | Challenge Text element .....                        | 65 |
| 7.3.2.9  | Country information element.....                    | 66 |
| 7.3.2.10 | Hopping Pattern Parameters information element..... | 67 |
| 7.3.2.11 | Hopping Pattern Table information element .....     | 67 |
| 7.3.2.12 | Request information element .....                   | 68 |
| 8.       | Authentication and privacy .....                    | 71 |
| 8.1      | Authentication services .....                       | 71 |
| 8.1.1    | Open System authentication .....                    | 71 |
| 8.1.1.1  | Open System authentication (first frame).....       | 71 |
| 8.1.1.2  | Open System authentication (final frame).....       | 71 |
| 8.1.2    | Shared Key authentication .....                     | 72 |
| 8.1.2.1  | Shared Key authentication (first frame).....        | 72 |
| 8.1.2.2  | Shared Key authentication (second frame).....       | 72 |
| 8.1.2.3  | Shared Key authentication (third frame) .....       | 73 |
| 8.1.2.4  | Shared Key authentication (final frame).....        | 73 |
| 8.2      | The WEP algorithm .....                             | 73 |
| 8.2.1    | Introduction.....                                   | 73 |
| 8.2.2    | Properties of the WEP algorithm.....                | 74 |
| 8.2.3    | WEP theory of operation .....                       | 74 |
| 8.2.4    | WEP algorithm specification .....                   | 76 |
| 8.2.5    | WEP Frame Body expansion.....                       | 76 |
| 8.3      | Security-Related MIB attributes .....               | 77 |
| 8.3.1    | Authentication-Related MIB attributes.....          | 77 |
| 8.3.2    | Privacy-Related MIB attributes .....                | 77 |
| 9.       | MAC sublayer functional description.....            | 83 |
| 9.1      | MAC architecture.....                               | 83 |
| 9.1.1    | DCF.....  | 83 |
| 9.1.2    | PCF .....   | 83 |
| 9.1.3    | Coexistence of DCF and PCF .....                    | 84 |
| 9.1.4    | Fragmentation/defragmentation overview .....        | 84 |
| 9.1.5    | MAC data service .....                              | 85 |
| 9.2      | DCF .....   | 85 |
| 9.2.1    | CS mechanism .....                                  | 86 |
| 9.2.2    | MAC-Level acknowledgments .....                     | 86 |
| 9.2.3    | IFS.....  | 86 |

|          |  |     |
|----------|--|-----|
| 9.2.3.1  | SIFS .....   | 87  |
| 9.2.3.2  | PIFS .....   | 87  |
| 9.2.3.3  | DIFS .....   | 88  |
| 9.2.3.4  | EIFS .....   | 88  |
| 9.2.4    | Random backoff time .....  | 88  |
| 9.2.5    | DCF access procedure .....                                       | 89  |
| 9.2.5.1  | Basic access .....   | 89  |
| 9.2.5.2  | Backoff procedure .....  | 90  |
| 9.2.5.3  | Recovery procedures and retransmit limits .....                  | 91  |
| 9.2.5.4  | Setting and resetting the NAV .....                              | 92  |
| 9.2.5.5  | Control of the channel .....                                     | 93  |
| 9.2.5.6  | RTS/CTS usage with fragmentation .....                           | 94  |
| 9.2.5.7  | CTS procedure .....  | 95  |
| 9.2.6    | Directed MPDU transfer procedure .....                           | 95  |
| 9.2.7    | Broadcast and multicast MPDU transfer procedure .....            | 96  |
| 9.2.8    | ACK procedure .....  | 96  |
| 9.2.9    | Duplicate detection and recovery .....                           | 97  |
| 9.2.10   | DCF timing relations .....                                       | 98  |
| 9.3      | PCF .....  | 99  |
| 9.3.1    | CFP structure and timing .....                                   | 100 |
| 9.3.2    | PCF access procedure .....                                       | 101 |
| 9.3.2.1  | Fundamental access .....   | 101 |
| 9.3.2.2  | NAV operation during the CFP .....                               | 102 |
| 9.3.3    | PCF transfer procedure .....                                     | 102 |
| 9.3.3.1  | PCF transfers when the PCF STA is transmitter or recipient ..... | 103 |
| 9.3.3.2  | Operation with overlapping point-coordinated BSSs .....          | 104 |
| 9.3.3.3  | CFPMaxDuration limit .....                                       | 105 |
| 9.3.3.4  | CF usage rules .....   | 105 |
| 9.3.4    | CF polling list .....  | 105 |
| 9.3.4.1  | Polling list processing .....                                    | 106 |
| 9.3.4.2  | Polling list update procedure .....                              | 106 |
| 9.4      | Fragmentation .....  | 106 |
| 9.5      | Defragmentation .....  | 107 |
| 9.6      | Multirate support .....  | 108 |
| 9.7      | Frame exchange sequences .....                                   | 109 |
| 9.8      | MSDU transmission restrictions .....                             | 110 |
| 9.9      | Operation across regulatory domains .....                        | 111 |
| 9.9.1    | Operation upon entering a regulatory domain .....                | 111 |
| 9.9.2    | Support for FH PHYs .....  | 111 |
| 9.9.2.1  | Determination of hopping patterns .....                          | 111 |
| 10.      | Layer management .....   | 115 |
| 10.1     | Overview of management model .....                               | 115 |
| 10.2     | Generic management primitives .....                              | 116 |
| 10.3     | MLME SAP interface .....   | 116 |
| 10.3.1   | Power management .....   | 117 |
| 10.3.1.1 | MLME-POWERMGT.request .....                                      | 117 |
| 10.3.1.2 | MLME-POWERMGT.confirm .....                                      | 117 |
| 10.3.2   | Scan .....   | 118 |
| 10.3.2.1 | MLME-SCAN.request .....  | 118 |
| 10.3.2.2 | MLME-SCAN.confirm .....  | 119 |
| 10.3.3   | Synchronization .....  | 120 |
| 10.3.3.1 | MLME-JOIN.request .....  | 120 |

|         |           |                                    |     |
|---------|-----------|------------------------------------|-----|
|         | 10.3.3.2  | MLME-JOIN.confirm                  | 121 |
| 10.3.4  |           | Authenticate                       | 122 |
|         | 10.3.4.1  | MLME-AUTHENTICATE.request          | 122 |
|         | 10.3.4.2  | MLME-AUTHENTICATE.confirm          | 123 |
|         | 10.3.4.3  | MLME-AUTHENTICATE.indication       | 123 |
| 10.3.5  |           | Deauthenticate                     | 124 |
|         | 10.3.5.1  | MLME-DEAUTHENTICATE.request        | 124 |
|         | 10.3.5.2  | MLME-DEAUTHENTICATE.confirm        | 125 |
|         | 10.3.5.3  | MLME-DEAUTHENTICATE.indication     | 125 |
| 10.3.6  |           | Associate                          | 126 |
|         | 10.3.6.1  | MLME-ASSOCIATE.request             | 126 |
|         | 10.3.6.2  | MLME-ASSOCIATE.confirm             | 127 |
|         | 10.3.6.3  | MLME-ASSOCIATE.indication          | 127 |
| 10.3.7  |           | Reassociate                        | 128 |
|         | 10.3.7.1  | MLME-REASSOCIATE.request           | 128 |
|         | 10.3.7.2  | MLME-REASSOCIATE.confirm           | 129 |
|         | 10.3.7.3  | MLME-REASSOCIATE.indication        | 129 |
| 10.3.8  |           | Disassociate                       | 130 |
|         | 10.3.8.1  | MLME-DISASSOCIATE.request          | 130 |
|         | 10.3.8.2  | MLME-DISASSOCIATE.confirm          | 130 |
|         | 10.3.8.3  | MLME-DISASSOCIATE.indication       | 131 |
| 10.3.9  |           | Reset                              | 131 |
|         | 10.3.9.1  | MLME-RESET.request                 | 132 |
|         | 10.3.9.2  | MLME-RESET.confirm                 | 132 |
| 10.3.10 |           | Start                              | 133 |
|         | 10.3.10.1 | MLME-START.request                 | 133 |
|         | 10.3.10.2 | MLME-START.confirm                 | 134 |
| 10.4    |           | PLME SAP interface                 | 135 |
| 10.4.1  |           | PLME-RESET.request                 | 135 |
|         | 10.4.1.1  | Function                           | 135 |
|         | 10.4.1.2  | Semantics of the service primitive | 135 |
|         | 10.4.1.3  | When generated                     | 135 |
|         | 10.4.1.4  | Effect of receipt                  | 135 |
| 10.4.2  |           | PLME-CHARACTERISTICS.request       | 135 |
|         | 10.4.2.1  | Function                           | 135 |
|         | 10.4.2.2  | Semantics of the service primitive | 135 |
|         | 10.4.2.3  | When generated                     | 136 |
|         | 10.4.2.4  | Effect of receipt                  | 136 |
| 10.4.3  |           | PLME-CHARACTERISTICS.confirm       | 136 |
|         | 10.4.3.1  | Function                           | 136 |
|         | 10.4.3.2  | Semantics of the service primitive | 136 |
|         | 10.4.3.3  | When generated                     | 138 |
|         | 10.4.3.4  | Effect of receipt                  | 138 |
| 10.4.4  |           | PLME-DSSSTESTMODE.request          | 138 |
|         | 10.4.4.1  | Function                           | 138 |
|         | 10.4.4.2  | Semantics of the service primitive | 138 |
|         | 10.4.4.3  | When generated                     | 139 |
|         | 10.4.4.4  | Effect of receipt                  | 139 |
| 10.4.5  |           | PLME-DSSSTESTOUTPUT.request        | 139 |
|         | 10.4.5.1  | Function                           | 139 |
|         | 10.4.5.2  | Semantics of the service primitive | 139 |
|         | 10.4.5.3  | When generated                     | 139 |
|         | 10.4.5.4  | Effect of receipt                  | 139 |

|          |   |     |
|----------|---|-----|
| 10.4.6   | PLME-TXTIME.request.....                                  | 140 |
| 10.4.6.1 | Function .....  | 140 |
| 10.4.6.2 | Semantics of the service primitive.....                   | 140 |
| 10.4.6.3 | When generated .....                                      | 140 |
| 10.4.6.4 | Effect of receipt .....                                   | 140 |
| 10.4.7   | PLME-TXTIME.confirm.....                                  | 140 |
| 10.4.7.1 | Function .....  | 140 |
| 10.4.7.2 | Semantics of the service primitive.....                   | 140 |
| 10.4.7.3 | When generated .....                                      | 140 |
| 10.4.7.4 | Effect of receipt .....                                   | 140 |
| 11.      | MLME .....  | 141 |
| 11.1     | Synchronization .....                                     | 141 |
| 11.1.1   | Basic approach.....                                       | 141 |
| 11.1.1.1 | TSF for infrastructure networks.....                      | 141 |
| 11.1.1.2 | TSF for an IBSS.....                                      | 141 |
| 11.1.2   | Maintaining synchronization .....                         | 141 |
| 11.1.2.1 | Beacon generation in infrastructure networks .....        | 141 |
| 11.1.2.2 | Beacon generation in an IBSS .....                        | 142 |
| 11.1.2.3 | Beacon reception.....                                     | 142 |
| 11.1.2.4 | TSF timer accuracy.....                                   | 143 |
| 11.1.3   | Acquiring synchronization, scanning .....                 | 143 |
| 11.1.3.1 | Passive scanning .....                                    | 144 |
| 11.1.3.2 | Active scanning.....                                      | 144 |
| 11.1.3.3 | Initializing a BSS.....                                   | 145 |
| 11.1.3.4 | Synchronizing with a BSS .....                            | 145 |
| 11.1.4   | Adjusting STA timers .....                                | 146 |
| 11.1.5   | Timing synchronization for FH PHYs.....                   | 146 |
| 11.2     | Power management .....                                    | 146 |
| 11.2.1   | Power management in an infrastructure network .....       | 146 |
| 11.2.1.1 | STA Power Management modes .....                          | 147 |
| 11.2.1.2 | AP TIM transmissions .....                                | 148 |
| 11.2.1.3 | TIM types.....  | 148 |
| 11.2.1.4 | AP operation during the CP .....                          | 149 |
| 11.2.1.5 | AP operation during the CFP.....                          | 149 |
| 11.2.1.6 | Receive operation for STAs in PS mode during the CP ..... | 150 |
| 11.2.1.7 | Receive operation for STAs in PS mode during the CFP..... | 150 |
| 11.2.1.8 | STAs operating in the Active mode.....                    | 151 |
| 11.2.1.9 | AP aging function .....                                   | 151 |
| 11.2.2   | Power management in an IBSS .....                         | 151 |
| 11.2.2.1 | Basic approach.....                                       | 151 |
| 11.2.2.2 | Initialization of power management within an IBSS.....    | 153 |
| 11.2.2.3 | STA power state transitions .....                         | 153 |
| 11.2.2.4 | ATIM and frame transmission.....                          | 153 |
| 11.3     | Association and reassociation .....                       | 154 |
| 11.3.1   | STA association procedures.....                           | 154 |
| 11.3.2   | AP association procedures .....                           | 154 |
| 11.3.3   | STA reassociation procedures .....                        | 155 |
| 11.3.4   | AP reassociation procedures.....                          | 155 |
| 11.4     | MIB definitions .....                                     | 155 |

|           |   |     |
|-----------|---|-----|
| 12.       | PHY service specification.....  | 157 |
| 12.1      | Scope.....  | 157 |
| 12.2      | PHY functions.....  | 157 |
| 12.3      | Detailed PHY service specifications.....  | 157 |
| 12.3.1    | Scope and field of application .....  | 157 |
| 12.3.2    | Overview of the service .....   | 157 |
| 12.3.3    | Overview of interactions.....   | 157 |
| 12.3.4    | Basic service and options.....  | 157 |
| 12.3.4.1  | PHY-SAP peer-to-peer service primitives.....  | 158 |
| 12.3.4.2  | PHY-SAP sublayer-to-sublayer service primitives .....   | 158 |
| 12.3.4.3  | PHY-SAP service primitives parameters.....  | 158 |
| 12.3.4.4  | Vector descriptions .....   | 159 |
| 12.3.5    | PHY-SAP detailed service specification .....  | 159 |
| 12.3.5.1  | PHY-DATA.request .....  | 159 |
| 12.3.5.2  | PHY-DATA.indication .....   | 159 |
| 12.3.5.3  | PHY-DATA.confirm .....  | 160 |
| 12.3.5.4  | PHY-TXSTART.request.....  | 160 |
| 12.3.5.5  | PHY-TXSTART.confirm .....   | 161 |
| 12.3.5.6  | PHY-TXEND.request.....  | 161 |
| 12.3.5.7  | PHY-TXEND.confirm.....  | 162 |
| 12.3.5.8  | PHY-CCARESET.request .....  | 162 |
| 12.3.5.9  | PHY-CCARESET.confirm .....  | 163 |
| 12.3.5.10 | PHY-CCA.indication.....   | 163 |
| 12.3.5.11 | PHY-RXSTART.indication.....   | 164 |
| 12.3.5.12 | PHY-RXEND.indication .....  | 164 |
| 13.       | PHY management.....   | 167 |
| 14.       | Frequency-Hopping spread spectrum (FHSS) PHY specification for the 2.4 GHz industrial, scientific, and medical (ISM) band ..... | 169 |
| 14.1      | Overview.....   | 169 |
| 14.1.1    | Overview of FHSS PHY.....   | 169 |
| 14.1.2    | FHSS PHY functions.....   | 169 |
| 14.1.2.1  | PLCP sublayer .....   | 169 |
| 14.1.2.2  | PLME.....   | 169 |
| 14.1.2.3  | PMD sublayer .....  | 169 |
| 14.1.3    | Service specification method and notation .....   | 169 |
| 14.2      | FHSS PHY-specific service parameter lists.....  | 170 |
| 14.2.1    | Overview.....   | 170 |
| 14.2.2    | TXVECTOR parameters.....  | 170 |
| 14.2.2.1  | TXVECTOR LENGTH.....  | 170 |
| 14.2.2.2  | TXVECTOR DATARATE.....  | 170 |
| 14.2.3    | RXVECTOR parameters .....   | 170 |
| 14.2.3.1  | TRXVECTOR LENGTH .....  | 171 |
| 14.2.3.2  | RXVECTOR RSSI .....   | 171 |
| 14.3      | FHSS PLCP sublayer .....  | 171 |
| 14.3.1    | Overview.....   | 171 |
| 14.3.1.1  | State diagram notation .....  | 171 |
| 14.3.2    | PLCP frame format.....  | 172 |
| 14.3.2.1  | PLCP Preamble.....  | 173 |
| 14.3.2.2  | PLCP Header field.....  | 173 |
| 14.3.2.3  | PLCP data whitener .....  | 174 |

|           |   |     |
|-----------|---|-----|
| 14.3.3    | PLCP state machines .....                             | 175 |
| 14.3.3.1  | Transmit PLCP .....                                   | 175 |
| 14.3.3.2  | CS/CCA procedure .....                                | 178 |
| 14.3.3.3  | Receive PLCP .....                                    | 181 |
| 14.4      | PLME SAP layer management .....                       | 184 |
| 14.4.1    | Overview .....  | 184 |
| 14.4.2    | FH PHY specific MLME procedures .....                 | 184 |
| 14.4.2.1  | Overview .....  | 184 |
| 14.4.2.2  | FH synchronization .....                              | 184 |
| 14.4.3    | FH PLME state machines .....                          | 184 |
| 14.4.3.1  | Overview .....  | 184 |
| 14.4.3.2  | PLME state machine .....                              | 184 |
| 14.4.3.3  | PLME management primitives .....                      | 186 |
| 14.5      | FHSS PMD sublayer services .....                      | 187 |
| 14.5.1    | Scope and field of application .....                  | 187 |
| 14.5.2    | Overview of services .....                            | 187 |
| 14.5.3    | Overview of interactions .....                        | 187 |
| 14.5.4    | Basic service and options .....                       | 187 |
| 14.5.4.1  | PMD_SAP peer-to-peer service primitives .....         | 187 |
| 14.5.4.2  | PMD_SAP sublayer-to-sublayer service primitives ..... | 188 |
| 14.5.4.3  | PMD_SAP service primitives parameters .....           | 188 |
| 14.5.5    | PMD_SAP detailed service specification .....          | 188 |
| 14.5.5.1  | PMD_DATA.request .....                                | 188 |
| 14.5.5.2  | PMD_DATA.indicate .....                               | 189 |
| 14.5.5.3  | PMD_TXRX.request .....                                | 189 |
| 14.5.5.4  | PMD_PA_RAMP.request .....                             | 190 |
| 14.5.5.5  | PMD_ANTSEL.request .....                              | 190 |
| 14.5.5.6  | PMD_TXPWRLVL.request .....                            | 191 |
| 14.5.5.7  | PMD_FREQ.request .....                                | 192 |
| 14.5.5.8  | PMD_RSSI.indicate .....                               | 192 |
| 14.5.5.9  | PMD_PWRMGMT.request .....                             | 193 |
| 14.6      | FHSS PMD sublayer, 1.0 Mbit/s .....                   | 193 |
| 14.6.1    | 1 Mbit/s PMD operating specifications, general .....  | 193 |
| 14.6.2    | Regulatory requirements .....                         | 193 |
| 14.6.3    | Operating frequency range .....                       | 194 |
| 14.6.4    | Number of operating channels .....                    | 195 |
| 14.6.5    | Operating channel center frequency .....              | 195 |
| 14.6.6    | Occupied channel bandwidth .....                      | 197 |
| 14.6.7    | Minimum hop rate .....                                | 197 |
| 14.6.8    | Hop sequences .....                                   | 198 |
| 14.6.9    | Unwanted emissions .....                              | 200 |
| 14.6.10   | Modulation .....                                      | 200 |
| 14.6.11   | Channel data rate .....                               | 201 |
| 14.6.12   | Channel switching/settling time .....                 | 201 |
| 14.6.13   | Receive to transmit switch time .....                 | 201 |
| 14.6.14   | PMD transmit specifications .....                     | 202 |
| 14.6.14.1 | Nominal transmit power .....                          | 202 |
| 14.6.14.2 | Transmit power levels .....                           | 202 |
| 14.6.14.3 | Transmit power level control .....                    | 202 |
| 14.6.14.4 | Transmit spectrum shape .....                         | 202 |
| 14.6.14.5 | Transmit center frequency tolerance .....             | 203 |
| 14.6.14.6 | Transmitter ramp periods .....                        | 203 |
| 14.6.15   | PMD receiver specifications .....                     | 203 |
| 14.6.15.1 | Input signal range .....                              | 203 |

|      |   |     |
|------|---|-----|
|      | 14.6.15.2 Receive center frequency acceptance range .....                         | 203 |
|      | 14.6.15.3 CCA power threshold .....   | 203 |
|      | 14.6.15.4 Receiver sensitivity .....  | 203 |
|      | 14.6.15.5 Intermodulation .....   | 204 |
|      | 14.6.15.6 Desensitization (Dp) .....  | 204 |
|      | 14.6.15.7 Receiver radiation .....  | 204 |
|      | 14.6.16 Operating temperature range .....   | 204 |
| 14.7 | FHSS PMD sublayer, 2.0 Mbit/s .....   | 204 |
|      | 14.7.1 Overview .....   | 204 |
|      | 14.7.2 4GFSK modulation .....   | 205 |
|      | 14.7.2.1 Frame structure for HS FHSS PHY .....                                    | 206 |
|      | 14.7.3 Channel data rate .....  | 206 |
|      | 14.7.3.1 Input dynamic range .....  | 206 |
|      | 14.7.3.2 Receiver sensitivity .....   | 207 |
|      | 14.7.3.3 IMp .....  | 207 |
|      | 14.7.3.4 Dp .....   | 207 |
| 14.8 | FHSS PHY MIB .....  | 207 |
|      | 14.8.1 FH PHY attributes .....  | 207 |
|      | 14.8.2 FH PHY attribute definitions .....   | 209 |
|      | 14.8.2.1 dot11PHYType .....   | 209 |
|      | 14.8.2.2 dot11RegDomainsSupported .....   | 209 |
|      | 14.8.2.3 dot11CurrentRegDomain .....  | 209 |
|      | 14.8.2.4 dot11TempType .....  | 210 |
|      | 14.8.2.5 dot11CurrentPowerState .....   | 210 |
|      | 14.8.2.6 dot11SupportedDataRatesTX .....  | 210 |
|      | 14.8.2.7 dot11SupportedDataRatesRX .....  | 210 |
|      | 14.8.2.8 aMPDUMaxLength .....   | 210 |
|      | 14.8.2.9 dot11SupportedTxAntennas .....   | 211 |
|      | 14.8.2.10 dot11CurrentTxAntenna .....   | 211 |
|      | 14.8.2.11 dot11SupportedRxAntenna .....   | 211 |
|      | 14.8.2.12 dot11DiversitySupport .....   | 211 |
|      | 14.8.2.13 dot11DiversitySelectionRx .....   | 212 |
|      | 14.8.2.14 dot11NumberSupportedPowerLevels .....                                   | 212 |
|      | 14.8.2.15 dot11TxPowerLevel1-8 .....  | 212 |
|      | 14.8.2.16 dot11CurrentTxPowerLevel .....  | 212 |
|      | 14.8.2.17 dot11HopTime .....  | 213 |
|      | 14.8.2.18 dot11CurrentChannelNumber .....   | 213 |
|      | 14.8.2.19 dot11MaxDwellTime .....   | 213 |
|      | 14.8.2.20 dot11CurrentSet .....   | 213 |
|      | 14.8.2.21 dot11CurrentPattern .....   | 213 |
|      | 14.8.2.22 dot11CurrentIndex .....   | 213 |
|      | 14.8.2.23 dot11CurrentPowerState .....  | 214 |
| 14.9 | FH PHY characteristics .....  | 214 |
| 15.  | DSSS PHY specification for the 2.4 GHz band designated for ISM applications ..... | 217 |
|      | 15.1 Overview .....   | 217 |
|      | 15.1.1 Scope .....  | 217 |
|      | 15.1.2 DSSS PHY functions .....   | 217 |
|      | 15.1.2.1 PLCP sublayer .....  | 217 |
|      | 15.1.2.2 PMD sublayer .....   | 217 |
|      | 15.1.2.3 PLME .....   | 217 |
|      | 15.1.3 Service specification method and notation .....                            | 218 |
| 15.2 | DSSS PLCP sublayer .....  | 218 |

|           |   |     |
|-----------|---|-----|
| 15.2.1    | Overview.....   | 218 |
| 15.2.2    | PLCP frame format.....  | 218 |
| 15.2.3    | PLCP field definitions .....  | 218 |
| 15.2.3.1  | PLCP SYNC field.....  | 218 |
| 15.2.3.2  | PLCP SFD.....   | 219 |
| 15.2.3.3  | PLCP IEEE 802.11 SIGNAL field .....                                   | 219 |
| 15.2.3.4  | PLCP IEEE 802.11 SERVICE field .....                                  | 219 |
| 15.2.3.5  | PLCP LENGTH field.....  | 219 |
| 15.2.3.6  | PLCP CRC field.....   | 219 |
| 15.2.4    | PLCP/DSSS PHY data scrambler and descrambler .....                    | 221 |
| 15.2.5    | PLCP data modulation and modulation rate change.....                  | 221 |
| 15.2.6    | Transmit PLCP .....   | 221 |
| 15.2.7    | Receive PLCP .....  | 222 |
| 15.3      | DSSS PLME .....   | 225 |
| 15.3.1    | PLME_SAP sublayer management primitives .....                         | 225 |
| 15.3.2    | DSSS PHY MIB .....  | 226 |
| 15.3.3    | DS PHY characteristics .....  | 227 |
| 15.4      | DSSS PMD sublayer.....  | 227 |
| 15.4.1    | Scope and field of application .....                                  | 227 |
| 15.4.2    | Overview of service .....   | 228 |
| 15.4.3    | Overview of interactions.....   | 228 |
| 15.4.4    | Basic service and options.....  | 228 |
| 15.4.4.1  | PMD_SAP peer-to-peer service primitives .....                         | 228 |
| 15.4.4.2  | PMD_SAP peer-to-peer service primitive parameters .....               | 229 |
| 15.4.4.3  | PMD_SAP sublayer-to-sublayer service primitives .....                 | 229 |
| 15.4.4.4  | PMD_SAP service primitive parameters.....                             | 229 |
| 15.4.5    | PMD_SAP detailed service specification .....                          | 230 |
| 15.4.5.1  | PMD_DATA.request .....  | 230 |
| 15.4.5.2  | PMD_DATA.indicate .....   | 231 |
| 15.4.5.3  | PMD_TXSTART.request .....   | 231 |
| 15.4.5.4  | PMD_TXEND.request.....  | 232 |
| 15.4.5.5  | PMD_ANTSEL.request.....   | 232 |
| 15.4.5.6  | PMD_ANTSEL.indicate.....  | 232 |
| 15.4.5.7  | PMD_TXPWRLVL.request .....  | 233 |
| 15.4.5.8  | PMD_RATE.request.....   | 233 |
| 15.4.5.9  | PMD_RATE.indicate.....  | 234 |
| 15.4.5.10 | PMD_RSSI.indicate.....  | 234 |
| 15.4.5.11 | PMD_SQ.indicate .....   | 235 |
| 15.4.5.12 | PMD_CS.indicate .....   | 235 |
| 15.4.5.13 | PMD_ED.indicate.....  | 236 |
| 15.4.5.14 | PMD_ED.request.....   | 236 |
| 15.4.5.15 | PHY-CCA.indicate .....  | 237 |
| 15.4.6    | PMD operating specifications, general.....                            | 237 |
| 15.4.6.1  | Operating frequency range.....  | 237 |
| 15.4.6.2  | Number of operating channels .....                                    | 238 |
| 15.4.6.3  | Spreading sequence.....   | 238 |
| 15.4.6.4  | Modulation and channel data rates .....                               | 239 |
| 15.4.6.5  | Transmit and receive in-band and out-of-band spurious emissions ..... | 239 |
| 15.4.6.6  | TX-to-RX turnaround time .....  | 239 |
| 15.4.6.7  | RX-to-TX turnaround time .....  | 239 |
| 15.4.6.8  | Slot time.....  | 240 |
| 15.4.6.9  | Transmit and receive antenna port impedance .....                     | 240 |
| 15.4.6.10 | Transmit and receive operating temperature range.....                 | 240 |

|          |  |     |
|----------|--|-----|
| 15.4.7   | PMD transmit specifications.....                         | 240 |
| 15.4.7.1 | Transmit power levels.....                               | 240 |
| 15.4.7.2 | Minimum transmitted power level.....                     | 240 |
| 15.4.7.3 | Transmit power level control.....                        | 240 |
| 15.4.7.4 | Transmit spectrum mask.....                              | 240 |
| 15.4.7.5 | Transmit center frequency tolerance.....                 | 241 |
| 15.4.7.6 | Chip clock frequency tolerance.....                      | 241 |
| 15.4.7.7 | Transmit power-on and power-down ramp.....               | 241 |
| 15.4.7.8 | RF carrier suppression.....                              | 242 |
| 15.4.7.9 | Transmit modulation accuracy.....                        | 242 |
| 15.4.8   | PMD receiver specifications.....                         | 244 |
| 15.4.8.1 | Receiver minimum input level sensitivity.....            | 244 |
| 15.4.8.2 | Receiver maximum input level.....                        | 244 |
| 15.4.8.3 | Receiver adjacent channel rejection.....                 | 244 |
| 15.4.8.4 | CCA.....   | 245 |
| 16.      | Infrared (IR) PHY specification.....                     | 247 |
| 16.1     | Overview.....  | 247 |
| 16.1.1   | Scope.....   | 248 |
| 16.1.2   | IR PHY functions.....                                    | 248 |
| 16.1.2.1 | PLCP sublayer.....                                       | 248 |
| 16.1.2.2 | PMD sublayer.....  | 248 |
| 16.1.2.3 | PLME.....  | 248 |
| 16.1.3   | Service specification method and notation.....           | 248 |
| 16.2     | IR PLCP sublayer.....                                    | 249 |
| 16.2.1   | Overview.....  | 249 |
| 16.2.2   | PLCP frame format.....                                   | 249 |
| 16.2.3   | PLCP modulation and rate change.....                     | 249 |
| 16.2.4   | PLCP field definitions.....                              | 250 |
| 16.2.4.1 | PLCP SYNC field.....                                     | 250 |
| 16.2.4.2 | PLCP SFD field.....                                      | 250 |
| 16.2.4.3 | PLCP DR field.....                                       | 250 |
| 16.2.4.4 | PLCP DCLA field.....                                     | 250 |
| 16.2.4.5 | PLCP LENGTH field.....                                   | 251 |
| 16.2.4.6 | PLCP CRC field.....                                      | 251 |
| 16.2.4.7 | PSDU field.....  | 251 |
| 16.2.5   | PLCPs.....   | 251 |
| 16.2.5.1 | Transmit PLCP.....                                       | 251 |
| 16.2.5.2 | Receive PLCP.....  | 252 |
| 16.2.5.3 | CCA procedure.....                                       | 252 |
| 16.2.5.4 | PMD_SAP peer-to-peer service primitive parameters.....   | 252 |
| 16.3     | IR PMD sublayer.....                                     | 253 |
| 16.3.1   | Overview.....  | 253 |
| 16.3.2   | PMD operating specifications, general.....               | 253 |
| 16.3.2.1 | Modulation and channel data rates.....                   | 253 |
| 16.3.2.2 | Octet partition and PPM symbol generation procedure..... | 254 |
| 16.3.2.3 | Operating environment.....                               | 254 |
| 16.3.2.4 | Operating temperature range.....                         | 255 |
| 16.3.3   | PMD transmit specifications.....                         | 255 |
| 16.3.3.1 | Transmitted peak optical power.....                      | 255 |
| 16.3.3.2 | Basic pulse shape and parameters.....                    | 255 |
| 16.3.3.3 | Emitter radiation pattern mask.....                      | 256 |
| 16.3.3.4 | Optical emitter peak wavelength.....                     | 258 |

|          |  |     |
|----------|--|-----|
| 16.3.3.5 | Transmit spectrum mask .....   | 258 |
| 16.3.4   | PMD receiver specifications .....  | 258 |
| 16.3.4.1 | Receiver sensitivity .....   | 258 |
| 16.3.4.2 | Receiver dynamic range .....   | 259 |
| 16.3.4.3 | Receiver field of view (FOV) .....   | 259 |
| 16.3.5   | ED, CS, and CCA definitions .....  | 259 |
| 16.3.5.1 | ED signal .....  | 259 |
| 16.3.5.2 | CS signal .....  | 259 |
| 16.3.5.3 | CCA .....  | 260 |
| 16.3.5.4 | CHNL_ID .....  | 260 |
| 16.4     | PHY attributes .....   | 260 |
| 17.      | Orthogonal frequency division multiplexing (OFDM) PHY specification for the 5 GHz band ..... | 263 |
| 17.1     | Introduction .....   | 263 |
| 17.1.1   | Scope .....  | 263 |
| 17.1.2   | OFDM PHY functions .....   | 263 |
| 17.1.2.1 | PLCP sublayer .....  | 263 |
| 17.1.2.2 | PMD sublayer .....   | 263 |
| 17.1.2.3 | PLME .....   | 263 |
| 17.1.2.4 | Service specification method .....   | 264 |
| 17.2     | OFDM PHY specific service parameter list .....   | 264 |
| 17.2.1   | Introduction .....   | 264 |
| 17.2.2   | TXVECTOR parameters .....  | 264 |
| 17.2.2.1 | TXVECTOR LENGTH .....  | 264 |
| 17.2.2.2 | TXVECTOR DATARATE .....  | 265 |
| 17.2.2.3 | TXVECTOR SERVICE .....   | 265 |
| 17.2.2.4 | TXVECTOR TXPWR_LEVEL .....   | 265 |
| 17.2.3   | RXVECTOR parameters .....  | 265 |
| 17.2.3.1 | RXVECTOR LENGTH .....  | 265 |
| 17.2.3.2 | RXVECTOR RSSI .....  | 265 |
| 17.2.3.3 | DATARATE .....   | 266 |
| 17.2.3.4 | SERVICE .....  | 266 |
| 17.3     | OFDM PLCP sublayer .....   | 266 |
| 17.3.1   | Introduction .....   | 266 |
| 17.3.2   | PLCP frame format .....  | 266 |
| 17.3.2.1 | Overview of the PPDU encoding process .....  | 266 |
| 17.3.2.2 | RATE-dependent parameters .....  | 268 |
| 17.3.2.3 | Timing related parameters .....  | 268 |
| 17.3.2.4 | Mathematical conventions in the signal descriptions .....                                    | 269 |
| 17.3.2.5 | Discrete time implementation considerations .....  | 270 |
| 17.3.3   | PLCP preamble (SYNC) .....   | 271 |
| 17.3.4   | SIGNAL field .....   | 272 |
| 17.3.4.1 | RATE field .....   | 273 |
| 17.3.4.2 | PLCP LENGTH field .....  | 273 |
| 17.3.4.3 | Parity (P), Reserved (R), and SIGNAL TAIL fields .....                                       | 274 |
| 17.3.5   | DATA field .....   | 274 |
| 17.3.5.1 | SERVICE field .....  | 274 |
| 17.3.5.2 | PPDU TAIL field .....  | 274 |
| 17.3.5.3 | Pad bits (PAD) .....   | 274 |
| 17.3.5.4 | PLCP DATA scrambler and descrambler .....  | 275 |
| 17.3.5.5 | Convolutional encoder .....  | 275 |
| 17.3.5.6 | Data interleaving .....  | 276 |
| 17.3.5.7 | Subcarrier modulation mapping .....  | 278 |

|           |   |     |
|-----------|---|-----|
| 17.3.5.8  | Pilot subcarriers .....   | 281 |
| 17.3.5.9  | OFDM modulation.....  | 281 |
| 17.3.6    | CCA .....   | 282 |
| 17.3.7    | PLCP data modulation and modulation rate change.....                  | 282 |
| 17.3.8    | PMD operating specifications (general) .....                          | 283 |
| 17.3.8.1  | Outline description.....  | 283 |
| 17.3.8.2  | Regulatory requirements.....  | 284 |
| 17.3.8.3  | Operating channel frequencies.....                                    | 284 |
| 17.3.8.4  | Transmit and receive in-band and out-of-band spurious emissions ..... | 285 |
| 17.3.8.5  | TX RF delay.....  | 285 |
| 17.3.8.6  | Slot time .....   | 286 |
| 17.3.8.7  | Transmit and receive antenna port impedance .....                     | 286 |
| 17.3.8.8  | Transmit and receive operating temperature range.....                 | 286 |
| 17.3.9    | PMD transmit specifications.....                                      | 286 |
| 17.3.9.1  | Transmit power levels.....  | 286 |
| 17.3.9.2  | Transmit spectrum mask.....   | 287 |
| 17.3.9.3  | Transmission spurious .....   | 287 |
| 17.3.9.4  | Transmit center frequency tolerance.....                              | 287 |
| 17.3.9.5  | Symbol clock frequency tolerance.....                                 | 287 |
| 17.3.9.6  | Modulation accuracy.....  | 288 |
| 17.3.9.7  | Transmit modulation accuracy test .....                               | 288 |
| 17.3.10   | PMD receiver specifications .....                                     | 289 |
| 17.3.10.1 | Receiver minimum input level sensitivity .....                        | 289 |
| 17.3.10.2 | Adjacent channel rejection.....                                       | 290 |
| 17.3.10.3 | Nonadjacent channel rejection.....                                    | 290 |
| 17.3.10.4 | Receiver maximum input level .....                                    | 291 |
| 17.3.10.5 | CCA sensitivity.....  | 291 |
| 17.3.11   | Transmit PLCP .....   | 291 |
| 17.3.12   | Receive PLCP .....  | 293 |
| 17.4      | OFDM PLME .....   | 295 |
| 17.4.1    | PLME_SAP sublayer management primitives .....                         | 295 |
| 17.4.2    | OFDM PHY MIB .....  | 295 |
| 17.4.3    | OFDM TXTIME calculation .....   | 297 |
| 17.4.4    | OFDM PHY characteristics .....  | 298 |
| 17.5      | OFDM PMD sublayer.....  | 299 |
| 17.5.1    | Scope and field of application .....                                  | 299 |
| 17.5.2    | Overview of service .....   | 299 |
| 17.5.3    | Overview of interactions.....   | 299 |
| 17.5.4    | Basic service and options.....  | 299 |
| 17.5.4.1  | PMD_SAP peer-to-peer service primitives .....                         | 299 |
| 17.5.4.2  | PMD_SAP sublayer-to-sublayer service primitives .....                 | 300 |
| 17.5.4.3  | PMD_SAP service primitive parameters .....                            | 300 |
| 17.5.5    | PMD_SAP detailed service specification .....                          | 300 |
| 17.5.5.1  | PMD_DATA.request .....  | 301 |
| 17.5.5.2  | PMD_DATA.indicate .....   | 301 |
| 17.5.5.3  | PMD_TXSTART.request .....   | 302 |
| 17.5.5.4  | PMD_TXEND.request.....  | 302 |
| 17.5.5.5  | PMD_TXPWRLVL.request .....  | 302 |
| 17.5.5.6  | PMD_RATE.request.....   | 303 |
| 17.5.5.7  | PMD_RSSI.indicate.....  | 303 |

|           |   |     |
|-----------|---|-----|
| 18.       | High Rate direct sequence spread spectrum (HR/DSSS) PHY specification ..... | 305 |
| 18.1      | Overview .....  | 305 |
| 18.1.1    | Scope .....   | 305 |
| 18.1.2    | High Rate PHY functions .....   | 305 |
| 18.1.2.1  | PLCP sublayer .....   | 306 |
| 18.1.2.2  | PMD sublayer .....  | 306 |
| 18.1.2.3  | PLME .....  | 306 |
| 18.1.3    | Service specification method and notation .....                             | 306 |
| 18.2      | High Rate PLCP sublayer .....   | 306 |
| 18.2.1    | Overview .....  | 306 |
| 18.2.2    | PPDU format .....   | 306 |
| 18.2.2.1  | Long PPDU format .....  | 307 |
| 18.2.2.2  | Short PPDU format (optional) .....  | 307 |
| 18.2.3    | PPDU field definitions .....  | 307 |
| 18.2.3.1  | Long PLCP SYNC field .....  | 308 |
| 18.2.3.2  | Long PLCP SFD .....   | 308 |
| 18.2.3.3  | Long PLCP SIGNAL field .....  | 308 |
| 18.2.3.4  | Long PLCP SERVICE field .....   | 309 |
| 18.2.3.5  | Long PLCP LENGTH field .....  | 309 |
| 18.2.3.6  | PLCP CRC (CRC-16) field .....   | 311 |
| 18.2.3.7  | Long PLCP data modulation and modulation rate change .....                  | 313 |
| 18.2.3.8  | Short PLCP synchronization (shortSYNC) .....                                | 313 |
| 18.2.3.9  | Short PLCP SFD field (shortSFD) .....                                       | 313 |
| 18.2.3.10 | Short PLCP SIGNAL field (shortSIGNAL) .....                                 | 314 |
| 18.2.3.11 | Short PLCP SERVICE field (shortSERVICE) .....                               | 314 |
| 18.2.3.12 | Short PLCP LENGTH field (shortLENGTH) .....                                 | 314 |
| 18.2.3.13 | Short CRC-16 field (shortCRC) .....   | 314 |
| 18.2.3.14 | Short PLCP data modulation and modulation rate change .....                 | 314 |
| 18.2.4    | PLCP/High Rate PHY data scrambler and descrambler .....                     | 314 |
| 18.2.5    | Transmit PLCP .....   | 315 |
| 18.2.6    | Receive PLCP .....  | 317 |
| 18.3      | High Rate PLME .....  | 320 |
| 18.3.1    | PLME_SAP sublayer management primitives .....                               | 320 |
| 18.3.2    | High Rate PHY MIB .....   | 321 |
| 18.3.3    | DS PHY characteristics .....  | 322 |
| 18.3.4    | High Rate TXTIME calculation .....  | 323 |
| 18.3.5    | Vector descriptions .....   | 323 |
| 18.4      | High Rate PMD sublayer .....  | 324 |
| 18.4.1    | Scope and field of application .....  | 324 |
| 18.4.2    | Overview of service .....   | 324 |
| 18.4.3    | Overview of interactions .....  | 324 |
| 18.4.4    | Basic service and options .....   | 324 |
| 18.4.4.1  | PMD_SAP peer-to-peer service primitives .....                               | 325 |
| 18.4.4.2  | PMD_SAP sublayer-to-sublayer service primitives .....                       | 325 |
| 18.4.5    | PMD_SAP detailed service specification .....                                | 325 |
| 18.4.5.1  | PMD_DATA.request .....  | 325 |
| 18.4.5.2  | PMD_DATA.indicate .....   | 326 |
| 18.4.5.3  | PMD_MODULATION.request .....  | 327 |
| 18.4.5.4  | PMD_PREAMBLE.request .....  | 327 |
| 18.4.5.5  | PMD_PREAMBLE.indicate .....   | 328 |
| 18.4.5.6  | PMD_TXSTART.request .....   | 328 |
| 18.4.5.7  | PMD_TXEND.request .....   | 329 |
| 18.4.5.8  | PMD_ANTSEL.request .....  | 329 |

|           |   |     |
|-----------|---|-----|
| 18.4.5.9  | PMD_TXPWRLVL.request .....  | 330 |
| 18.4.5.10 | PMD_RATE.request .....  | 330 |
| 18.4.5.11 | PMD_RSSI.indicate .....   | 331 |
| 18.4.5.12 | PMD_SQ.indicate .....   | 332 |
| 18.4.5.13 | PMD_CS.indicate .....   | 332 |
| 18.4.5.14 | PMD_ED.indicate .....   | 333 |
| 18.4.5.15 | PMD_ED.request .....  | 334 |
| 18.4.6    | PMD operating specifications, general .....   | 334 |
| 18.4.6.1  | Operating frequency range .....   | 334 |
| 18.4.6.2  | Number of operating channels .....  | 335 |
| 18.4.6.3  | Modulation and channel data rates .....   | 336 |
| 18.4.6.4  | Spreading sequence and modulation for 1 and 2 Mbit/s .....                              | 336 |
| 18.4.6.5  | Spreading sequences and modulation for CCK modulation at 5.5 Mbit/s and 11 Mbit/s ..... | 336 |
| 18.4.6.6  | DSSS/PBCC data modulation and modulation rate (optional) .....                          | 338 |
| 18.4.6.7  | Channel Agility (optional) .....  | 341 |
| 18.4.6.8  | Transmit and receive in-band and out-of-band spurious emissions .....                   | 344 |
| 18.4.6.9  | TX-to-RX turnaround time .....  | 344 |
| 18.4.6.10 | RX-to-TX turnaround time .....  | 344 |
| 18.4.6.11 | Slot time .....   | 344 |
| 18.4.6.12 | Channel switching/settling time .....   | 344 |
| 18.4.6.13 | Transmit and receive antenna port impedance .....                                       | 344 |
| 18.4.6.14 | Transmit and receive operating temperature range .....                                  | 344 |
| 18.4.7    | PMD transmit specifications .....   | 344 |
| 18.4.7.1  | Transmit power levels .....   | 345 |
| 18.4.7.2  | Transmit power level control .....  | 345 |
| 18.4.7.3  | Transmit spectrum mask .....  | 345 |
| 18.4.7.4  | Transmit center frequency tolerance .....   | 346 |
| 18.4.7.5  | Chip clock frequency tolerance .....  | 346 |
| 18.4.7.6  | Transmit power-on and power-down ramp .....   | 346 |
| 18.4.7.7  | RF carrier suppression .....  | 346 |
| 18.4.7.8  | Transmit modulation accuracy .....  | 347 |
| 18.4.8    | PMD receiver specifications .....   | 350 |
| 18.4.8.1  | Receiver minimum input level sensitivity .....  | 350 |
| 18.4.8.2  | Receiver maximum input level .....  | 350 |
| 18.4.8.3  | Receiver adjacent channel rejection .....   | 350 |
| 18.4.8.4  | CCA .....   | 350 |

|   |     |
|---|-----|
| Annex A (normative) Protocol Implementation Conformance Statement (PICS) proforma ..... | 353 |
|---|-----|

|       |  |     |
|-------|--|-----|
| A.1   | Introduction .....                                       | 353 |
| A.2   | Abbreviations and special symbols .....                  | 353 |
| A.2.1 | Symbols for Status column .....                          | 353 |
| A.2.2 | General abbreviations for Item and Support columns ..... | 353 |
| A.3   | Instructions for completing the PICS proforma .....      | 354 |
| A.3.1 | General structure of the PICS proforma .....             | 354 |
| A.3.2 | Additional information .....                             | 354 |
| A.3.3 | Exception information .....                              | 354 |
| A.3.4 | Conditional status .....                                 | 355 |
| A.4   | PICS proforma—IEEE Std 802.11, 2003 Edition .....        | 356 |
| A.4.1 | Implementation identification .....                      | 356 |
| A.4.2 | Protocol summary .....                                   | 356 |
| A.4.4 | MAC protocol .....                                       | 357 |
| A.4.3 | IUT configuration .....                                  | 357 |

|                       |  |     |
|-----------------------|--|-----|
| A.4.5                 | Frequency hopping (FH) PHY functions.....                          | 362 |
| A.4.6                 | Direct sequence PHY functions.....                                 | 364 |
| A.4.7                 | IR baseband PHY functions.....                                     | 367 |
| A.4.8                 | OFDM PHY functions.....  | 370 |
| A.4.9                 | High Rate, direct sequence PHY functions.....                      | 374 |
| A.4.10                | Regulatory Domain Extensions.....                                  | 379 |
| Annex B (informative) | Hopping sequences.....   | 381 |
| Annex C (normative)   | Formal description of MAC operation.....                           | 395 |
| C.1                   | Introduction to the MAC formal description.....                    | 398 |
| C.1.1                 | Fundamental assumptions.....                                       | 398 |
| C.1.2                 | Notation conventions.....  | 398 |
| C.1.3                 | Modeling techniques.....   | 399 |
| C.2                   | Data type and operator definitions for the MAC state machines..... | 400 |
| C.3                   | State machines for MAC stations.....                               | 449 |
| C.4                   | State machines for MAC AP.....                                     | 525 |
| Annex D (normative)   | ASN.1 encoding of the MAC and PHY MIB.....                         | 595 |
| Annex E (informative) | Bibliography.....  | 647 |
| E.1                   | General.....   | 647 |
| E.2                   | Specification and description language (SDL) documentation.....    | 648 |
| Annex F (informative) | High Rate PHY/FH interoperability.....                             | 649 |
| F.1                   | Additional CCA recommendations.....                                | 649 |
| Annex G (informative) | An example of encoding a frame for OFDM PHY.....                   | 651 |
| G.1                   | Introduction.....  | 651 |
| G.2                   | The message.....   | 651 |
| G.3                   | Generation of the preamble.....                                    | 653 |
| G.3.1                 | Generation of the short sequences.....                             | 653 |
| G.3.2                 | Generation of the long sequences.....                              | 656 |
| G.4                   | Generation of the SIGNAL field.....                                | 658 |
| G.4.1                 | SIGNAL field bit assignment.....                                   | 658 |
| G.4.2                 | Coding the SIGNAL field bits.....                                  | 658 |
| G.4.3                 | Interleaving the SIGNAL field bits.....                            | 658 |
| G.4.4                 | SIGNAL field frequency domain.....                                 | 659 |
| G.4.5                 | SIGNAL field time domain.....                                      | 661 |
| G.5                   | Generating the DATA bits.....                                      | 662 |
| G.5.1                 | Delineating, SERVICE field prepending, and zero padding.....       | 662 |
| G.5.2                 | Scrambling.....  | 663 |
| G.6                   | Generating the first DATA symbol.....                              | 666 |
| G.6.1                 | Coding the DATA bits.....  | 666 |
| G.6.2                 | Interleaving the DATA bits.....                                    | 667 |
| G.6.3                 | Mapping into symbols.....  | 670 |
| G.7                   | Generating the additional DATA symbols.....                        | 671 |
| G.8                   | The entire packet.....   | 672 |