ISO/IEC 17345:2006-12 (E)

Information technology - Da ta Interchange on 130 mm Rewritable and Write Once Read Many Ultra Density Optical (UDO) Disk Cartridges - Capacity: 30 Gbytes per Cartridge - First Generation

Contents

Page

Foreword vii

Introduction viii

Section 1 -- General 1

1 Scope 1

2 Conformance 2
2.1 Optical disk 2
2.2 Generating system 2
2.3 Receiving system 2
2.4 Compatibility statement 2

3 Normative references 2

4 Terms and definitions 2

5 Conventions and notations 6
5.1 Representation of numbers 6
5.2 Names 6

6 Acronyms 6

7 General description 7

8 General requirement 8
8.1 Environments 8
8.2 Temperature shock 9
8.3 Safety requirements 9
8.4 Flammability 9

9 Reference Drive 9
9.1 Optical system 9
9.2 Optical beam 10
9.3 Read Channel 11
9.4 Tracking 11
9.5 Rotation of the disk 11

Section 2 -- Mechanical and physical characteristics 11

10 Dimensional and physical characteristics of the case 11
10.1 General description of the case 11
10.2 Relationship of Sides A and B 11
10.3 Reference axes and case reference planes 12
10.4 Case drawings 12
10.5 Dimensions of the case 12
10.6 Mechanical characteristics 19
10.7 Drop test 20

10.8 Electro-static discharge test 20

11 Dimensional, mechanical, and physical characteristics of the disk 31
11.1 General description of the disk 31
11.2 Reference axis and plane of the disk 32
11.3 Dimensions of the disk 32
11.4 Mechanical characteristics 34
11.5 Optical characteristics 36

12 Interface between cartridge and drive 37
12.1 Clamping method 37
12.2 Clamping force 37
12.3 Capture cylinder 38
12.4 Disk position in operating condition 38

Section 3 -- Format of information 40

13 Track and Header geometry 40
13.1 Track and Header shape 40
13.2 Wobble groove 41
13.3 Mirror Area 41
13.4 Direction of spiral 41
13.5 Track pitch 41
13.6 Physical Track number 42

14 Track format 43
14.1 Physical Track layout 43
14.2 Physical Block Address (PBA) 43
14.3 Sectors with Mirror Area 46
14.4 Radial alignment 47

15 Sector format 47
15.1 Sector layout 47
15.2 IDL, IDG 49
15.3 Blank fields 50
15.4 Quadrature Wobble Marks (QWM) 50
15.5 Gap 51
15.6 Guard 51
15.7 Verify and Protect (VAP) 52
15.8 VFO1, VFO2 52
15.9 Sync 53
15.10 Data field 53
15.11 Postamble (PA) 54
15.12 Buffer 54
15.13 Transition Area (TA) 55

16 Recording codes 55
16.1 Preformatted Header 55
16.2 Data field 55

17 Formatted Zone 57
17.1 General description of the Formatted Zone 57
17.2 Division of the Formatted Zone 57
17.3 Drive test data patterns 64
17.4 SDI Zones usage 64
17.5 DDS Zones Usage 66

18 Layout of the User Zones 67
18.1 General description of the User Zones 67
18.2 Divisions of the User Zones 67
18.3 User Area 67
18.4 Defect Management Area (DMA) 69

18.5 Disk Definition Structure (DDS) 71

19 Defect Management in the Rewritable (RW) and Write Once Read Many (WORM) Zones ...73
19.1 Initialization of the disk 73
19.2 Certification 73
19.3 Disk not certified 74
19.4 Write procedure 75
19.5 Primary Defect List (PDL) format and content 75
19.6 Secondary Defect List (SDL) format and content 76

Section 4 -- Characteristics of embossed information 77

20 Embossed information - Method of testing 77
20.1 Environment 77
20.2 Use of the Reference Drive 77
20.3 Definition of signals 78

21 Signals from grooves and lands 79
21.1 Ratio of groove to land signal 79
21.2 Ratio of groove/land to Mirror Area signal 79
21.3 Divided push-pull signal 80
21.4 Wobble signal 80
21.5 Phase depth 81
21.6 Track location 81

22 Signals from Headers 81
22.1 Reference reflectance Itop 81
22.2 Address Mark and ID signals 81
22.3 QWM signals 82
22.4 Timing mean and jitter 83

Section 5 -- Characteristics of the recording layer 83

23 Method of testing 83
23.1 Environment 83
23.2 Reference Drive 83
23.3 Write conditions 84
23.4 Erase power for Type RW media 86
23.5 Read power damage 86

24 Phase Change characteristics 86
24.1 Mark polarity 86
24.2 Rewrite cycles for Type RW media 86

25 Write characteristics 86
25.1 Resolution 86
25.2 Narrow-Band Signal-to-Noise Ratio (NBSNR) 87
25.3 Cross-talk ratio 88
25.4 Timing mean 88
25.5 Timing jitter 89
25.6 Asymmetry 89

26 Erase power determination for Type RW media 89
26.1 Cross-Erase for Type RW Media 90

Section 6 -- Characteristics of user data 91

27 User Data - Method of testing 91
27.1 Environment 91
27.2 Reference Drive 91

28 Minimum quality of a sector 92

28.1 Headers ID 92
28.2 User-written data 93
28.3 Wobble signal 93

29 Data interchange requirements 93
29.1 Tracking 93
29.2 User-written data 93
29.3 Quality of disk 93

Annex A (normative) Air cleanliness class 100 000 94

Annex B (normative) Edge distortion test 96

Annex C (normative) Compliance test 98

Annex D (normative) Cartridge electro-static discharge test 101

Annex E (normative) Test method for measuring the adsorbent force of the hub 102

Annex F (normative) CRC for ID fields 104

Annex G (normative) Data field scrambler implementation 105

Annex H (normative) Interleave, CRC, ECC, Resync, and Reference for the Data field 107

Annex I (normative) Drive Information Record (DIR) usage 112

Annex J (normative) Determination of the Resync and Reference patterns 114

Annex K (normative) Specific Disk Information 116

Annex L (normative) Read Channel for measuring analog signals and jitter 132

Annex M (normative) Timing mean and timing jitter measuring procedure 133

Annex N (normative) Implementation Independent Mark Quality Determination (IIMQD) for the interchange of recorded media 134

Annex O (normative) Definition of the write pulse shape 136

Annex P (normative) Asymmetry measuring definition 137

Annex Q (normative) Enhanced Selective Inter-Symbol Interference Cancellation (ESISIC) algorithm 138

Annex R (normative) Requirements for interchange 140

Annex S (informative) Office environment 142

Annex T (informative) Derivation of the operating climatic environment 143

Annex U (informative) Transportation 148

Annex V (informative) Track deviation measurement 149

Annex W (informative) Measurement of the vertical birefringence of the cover layer 153

Annex X (informative) Quadrature Wobble offset control 154

Annex Y (informative) Start Position Shift (SPS) implementation 157

Annex Z (informative) Sector retirement guidelines 158

Annex AA (informative) Guidelines for the use of Type WORM ODCs 159

Annex BB (informative) Media type identification in existing and future standards 160

Annex CC (informative) Laser power calibration for evaluation of media power parameters 161