ISO 21757-1:2020 (E)

Document management — ECMAScript for PDF — Part 1: Use of ISO 32000-2 (PDF 2.0)

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Notation

5 Syntax

5.1 General
5.2 Method arguments

6 Paths

7 Safe path

8 Privileged context

9 Privileged versus non-privileged context

10 ECMAScript API

10.1 General
10.2 Annotation
10.2.1 General
10.2.2 Annotation types
10.2.3 Annotation properties
10.2.4 Annotation methods
10.2.4.1 General
10.2.4.2 destroy()
10.2.4.3 getProps()
10.2.4.4 getStateInModel(cStateModel)
10.2.4.5 setProps(cProps)
10.2.4.6 transitionToState(cStateModel, cState)
10.2.5 Annotation examples
10.2.5.1 Use the destroy() method to remove all FreeText annotations on page 0.
10.2.5.2 Create an annotation and create a copy of that annotation on each page in the document.
10.2.5.3 Print the status of all annotations on all pages of a document.
10.2.5.4 Assuming annot is an Annotation object, this example changes the border to dashed.
10.2.5.5 Set several properties of a Line annotation.
10.2.5.6 Define a custom set of transition states, then set the state of an annotation.
10.3 AnnotRichMedia
10.3.1 General
10.3.2 AnnotRichMedia properties
10.4 Annot3D
10.4.1 General
10.4.2 Annot3D properties
10.5 app
10.5.1 General

10.5.2 app properties
10.5.2.1 General
10.5.3 app methods
10.5.3.1 alert(cMsg, nIcon, nType, cTitle, oDoc, oCheckbox)
10.5.3.2 beep(nType)
10.5.3.3 clearInterval(oInterval)
10.5.3.4 clearTimeOut(oTime)
10.5.3.5 execDialog(monitor[, inheritDialog, parentDoc])
10.5.3.5.1 Dialog box handlers:
10.5.3.5.2 description property
10.5.3.5.3 elements property
10.5.3.5.4 Additional attributes of some dialog box elements
10.5.3.6 goForward()
10.5.3.7 launchURL(cUrl[, bNewFrame])
10.5.3.8 mailMsg(bUI, cTo[, cCc, cBcc, cSubject, cMsg])
10.5.3.9 newDoc([nWidth, nHeight])
10.5.3.10 newCollection()
10.5.3.11 openDoc(cPath[, oDoc, cFS, bHidden, bUseConv, cDest])
10.5.3.12 popUpMenu([cItem, Array])
10.5.3.13 popUpMenuEx(menuItems[, …])
10.5.3.14 response(cQuestion[, cTitle, cDefault, bPassword, cLabel])
10.5.3.15 setInterval(cExpr, nMilliseconds)
10.5.3.16 setTimeOut(cExpr, nilliseconds)
10.6 Bookmark
10.6.1 General
10.6.2 Bookmark properties
10.6.3 Bookmark methods
10.6.3.1 General
10.6.3.2 createChild(cName, cExpr, nIndex);
10.6.3.3 execute();
10.6.3.4 insertChild(oBookmark, nIndex);
10.6.3.5 remove();
10.6.3.6 setAction(cScript);
10.6.4 Bookmark Examples
10.6.4.1 Create a bookmark
10.6.4.2 List all Bookmarks
10.6.4.3 Search Bookmarks
10.7 Certificate
10.7.1 General
10.7.2 Certificate properties
10.7.2.1 General
10.7.2.1.1 Rights Object
10.7.2.1.2 Usage Object
10.8 color
10.8.1 General
10.8.2 color arrays
10.8.3 color properties
10.8.4 color methods
10.8.4.1 convert(colorArray, cColorspace)
10.8.4.2 equal(colorArray1, colorArray2)
10.9 collection
10.9.1 General
10.9.2 collection properties
10.9.3 collection methods
10.9.3.1 addField(name, text[, type, order, visible, readOnly])
10.9.3.2 getField(name)
10.9.3.3 removeField(name)
10.10 collectionField
10.10.1 General
10.10.2 collectionField properties
10.10.2.1 General
10.11 Data
10.11.1 General
10.11.2 Data properties

10.11.3 Data methods
10.11.3.1 getFieldValue(name[, includePrefix])
10.11.3.2 setFieldValue(name, value[, prefix])
10.12 Dialog
10.12.1 General
10.12.2 Dialog methods
10.12.2.1 General
10.12.2.2 enable(…)
10.12.2.3 end([itemId])
10.12.2.4 load(…)
10.12.2.5 store()
10.13 Doc
10.13.1 General
10.13.2 Doc properties
10.13.3 Doc methods
10.13.3.1 addAnnot(…)
10.13.3.2 addField(cName, cFieldType, nPageNum, oCoords)
10.13.3.3 addIcon(cName, icon)
10.13.3.4 addLink(nPage, oCoords)
10.13.3.5 addRecipientListCryptFilter(cCryptFilter, oGroup)
10.13.3.6 addRequirement(cType[, oReq])
10.13.3.6.1 Requirements enumerator object
10.13.3.6.2 Requirement object
10.13.3.6.3 ReqHandler object
10.13.3.6.4 ReqHandlers Enumerator object
10.13.3.7 addScript(cName, cScript)
10.13.3.8 addThumbnails([nStart, nEnd])
10.13.3.9 bringToFront()
10.13.3.10 calculateNow()
10.13.3.11 certifyInvisibleSign(oSig[, oInfo, cDIPath, bUI, cLegalAttest])
10.13.3.12 closeDoc(bNoSave)
10.13.3.13 createDataObject(cName, cValue[, cMediaType, cCryptFilter])
10.13.3.14 createTemplate (cName, nPage)
10.13.3.15 deletePages([nStart, nEnd])
10.13.3.16 embedDocAsDataObject(cName, oDoc[, cCryptFilter, bUI])
10.13.3.17 exportAsFDF([bAllFields, bNoPassword, aFields, bFlags, cPath, bAnnotations])
10.13.3.18 exportAsFDFStr([bAllFields, bNoPassword, aFields, bAnnotations, cHRef])
10.13.3.19 exportAsText([bNoPassword, aFields, cPath])
10.13.3.20 exportAsXFDF([bAllFields, bNoPassword, aFields, cPath, bAnnotations])
10.13.3.21 exportAsXFDFStr(bAllFields, bNoPassword, aFields, bFlags, bAnnotations, cHRef])
10.13.3.22 exportDataObject(cName[, cDIPath, bAllowAuth, nLaunch])
10.13.3.23 extractPages([nStart, nEnd, cPath])
10.13.3.24 flattenPages([nStart, nEnd, nNonPrint])
10.13.3.25 getAnnot(nPage, cName)
10.13.3.26 getAnnotRichMedia(nPage, cName)
10.13.3.27 getAnnot3D(nPage, cName)
10.13.3.28 getAnnots([nPage, nSortBy, bReverse, nFilterBy])
10.13.3.29 getAnnots3D(nPage)
10.13.3.30 getDataObject(cName)
10.13.3.31 getDataObjectContents(cName[, bAllowAuth])
10.13.3.32 getField(cName)
10.13.3.33 getIcon(cName)
10.13.3.34 getLegalWarnings(bExecute)
10.13.3.34.1 DocLegalWarning object
10.13.3.35 getLinks(nPage, oCoords)
10.13.3.36 getNthFieldName(nIndex)
10.13.3.37 getNthTemplate(nIndex)
10.13.3.38 getOCGs([nPage])
10.13.3.39 getOCGOrder()
10.13.3.40 getPageBox([cBox, nPage])
10.13.3.41 getPageLabel([nPage])
10.13.3.42 getPageNthWord([nPage, nWord, bStrip])
10.13.3.43 getPageNthWordQuads([nPage, nWord])
10.13.3.44 getPageNumWords(nPage)

10.13.3.45 getPageRotation([nPage])
10.13.3.46 getPageTransition([nPage])
10.13.3.47 getPrintParams()
10.13.3.48 getTemplate(cName)
10.13.3.49 gotoNamedDest(cName)
10.13.3.50 importAnFDF([cPath])
10.13.3.51 importAnXFDF([cPath])
10.13.3.52 importDataObject([cDlPath, cCryptFilter])
10.13.3.53 importIcon(cName[, cDlPath, nPage])
10.13.3.54 importTextData([cPath, nRow])
10.13.3.55 mailDoc(bUI[, cTo, cCc, cBcc, cSubject, cMsg])
10.13.3.56 mailForm(bUI[, cTo, cCc, cBcc, cSubject, cMsg])
10.13.3.57 movePage([nPage, nAfter])
10.13.3.58 newPage([nPage, nWidth, nHeight])
10.13.3.59 openDataObject(cName)
10.13.3.60 print([bUI, nStart, nEnd, bSilent, bShrinkToFit, bPrintAsImage, bReverse, bAnnotations, printParams])
10.13.3.61 removeDataObject(cName)
10.13.3.62 removeField(cName)
10.13.3.63 removeIcon(cName)
10.13.3.64 removeLinks(nPage, oCoords)
10.13.3.65 removeRequirement(cType)
10.13.3.66 removeScript(cName)
10.13.3.67 removeTemplate(cName)
10.13.3.68 removeThumbnails([nStart, nEnd])
10.13.3.69 resetForm([aFields])
10.13.3.70 scroll(nX, nY)
10.13.3.71 selectPageNthWord([nPage, nWord, bScroll])
10.13.3.72 setAction(cTrigger, cScript)
10.13.3.73 setDataObjectContents(cName, oStream[, cCryptFilter])
10.13.3.74 setOCGOrder(oOrderArray)
10.13.3.75 setPageAction(nPage, cTrigger, cScript)
10.13.3.76 setPageBoxes([cBox, nStart, nEnd, rBox])
10.13.3.77 setPageLabels([nPage, aLabel])
10.13.3.78 setPageRotations([nStart, nEnd, nRotate])
10.13.3.79 setPageTabOrder(nPage, cOrder)
10.13.3.80 setPageTransitions([nStart, nEnd, aTrans])
10.13.3.81 spawnPageFromTemplate(cTemplate[, nPage, bRename, bOverlay, oXObject])
10.13.3.82 submitForm(cURL[, bFDF, bEmpty, aFields, bGet, bAnnotations, bXML, bIncrChanges, bPDF, bCanonical, bExclNonUserAnnots, bExclFKey, cPassword, bEmbedForm, oEcmaScript, cSubmitAs, bInclNMKey, aPackets, cCharset, oXML, cPermID, cInstID, cUsageRights)
10.13.3.83 syncAnnotScan()
10.13.3.84 timestampSign([oSig, cDlPath, bUI])
10.14 Embedded PDF
10.14.1 General
10.14.2 Embedded PDF properties
10.14.2.1 General
10.14.2.1.1 messageHandler object details
10.14.3 Embedded PDF methods
10.14.3.1 General
10.14.3.2 postMessage(aMessage)
10.15 Error
10.15.1 General
10.15.2 Error properties
10.15.3 Error methods
10.15.3.1 toString(...)
10.16 event
10.16.1 General
10.16.2 Event type/name combinations
10.16.2.1 App/Init
10.16.2.2 Batch/Exec
10.16.2.3 Bookmark/Mouse Up
10.16.2.4 Console/Exec

10.16.2.5 Doc/DidPrint
10.16.2.6 Doc/DidSave
10.16.2.7 Doc/Open
10.16.2.8 Doc/WillClose
10.16.2.9 Doc/WillPrint
10.16.2.10 Doc/WillSave
10.16.2.11 External/Exec
10.16.2.12 Field/Blur
10.16.2.13 Field/Calculate
10.16.2.14 Field/Focus
10.16.2.15 Field/Format
10.16.2.16 Field/Keystroke
10.16.2.17 Field/Mouse Down
10.16.2.18 Field/Mouse Enter
10.16.2.19 Field/Mouse Exit
10.16.2.20 Field/Mouse Up
10.16.2.21 Field/Validate
10.16.2.22 Link/Mouse Up
10.16.2.23 Menu/Exec
10.16.2.24 Page/Open
10.16.2.25 Page/Close
10.16.2.26 Screen/Blur
10.16.2.27 Screen/Close
10.16.2.28 Screen/Focus
10.16.2.29 Screen/InView
10.16.2.30 Screen/Mouse Down
10.16.2.31 Screen/Mouse Enter
10.16.2.32 Screen/Mouse Exit
10.16.2.33 Screen/Mouse Up
10.16.2.34 Screen/Open
10.16.2.35 Screen/OutView
10.16.3 Document Event Processing
10.16.4 Form event processing
10.16.5 event properties
10.17 Field
10.17.1 General
10.17.2 Field versus widget attributes
10.17.3 Field properties
10.17.3.1 General
10.17.3.2 buttonPosition constants
10.17.3.3 buttonScaleHow keywords
10.17.3.4 buttonScaleWhen keywords
10.17.3.5 defaultStyle related properties
10.17.3.6 display keywords
10.17.3.7 Highlight keywords
10.17.3.8 Style keywords
10.17.3.9 textFont keywords
10.17.4 Field methods
10.17.4.1 General
10.17.4.2 browseForFileToSubmit()
10.17.4.3 buttonGetCaption([nFace])
10.17.4.4 buttonGetIcon([nFace])
10.17.4.5 buttonImportIcon([cPath, nPage])
10.17.4.6 buttonSetCaption(cCaption[, nFace])
10.17.4.7 buttonSetIcon(oIcon[, nFace])
10.17.4.8 checkThisBox(nWidget[, bCheckIt])
10.17.4.9 clearItems()
10.17.4.10 defaultIsChecked(...)
10.17.4.11 deleteItemAt([nIndex])
10.17.4.12 getArray()
10.17.4.13 getItemAt(nIndex[, bExportValue])
10.17.4.14 getLock()
10.17.4.15 insertItemAt(cName[, cExport, nIndex])
10.17.4.16 isBoxChecked(nWidget)

10.17.4.17 isDefaultChecked(nWidget)
10.17.4.18 setAction(cTrigger, cScript)
10.17.4.19 setFocus()
10.17.4.20 setItems(oArray)
10.17.4.21 setLock(oLock)
10.17.4.21.1 Lock Object
10.17.4.22 signatureGetModifications()
10.17.4.23 signatureGetSeedValue()
10.17.4.24 signatureInfo([oSig])
10.17.4.25 signatureSetSeedValue(oSigSeedValue)
10.17.4.25.1 SeedValue Object
10.17.4.25.2 CertificateSpecifier Object
10.17.4.25.3 Seed value timeStamp specifier object
10.17.4.26 signatureSign(oSig[, oInfo, cDIPath, bUI, cLegalAttest])
10.17.4.27 signatureValidate([oSig, bUI])
10.17.4.27.1 SignatureParameters object
10.18 FullScreen
10.18.1 General
10.18.2 FullScreen properties
10.18.2.1 General
10.18.2.2 Cursor Keywords
10.19 global
10.19.1 General
10.19.2 Creating global properties
10.19.3 Deleting global properties
10.19.4 Global object security policy
10.19.5 global object methods
10.19.5.1 General
10.19.5.2 setPersistent(cVariable, bPersist)
10.19.5.3 subscribe(cVariable, fCallback)
10.19.5.3.1 Callback Function
10.20 HostContainer
10.20.1 General
10.20.2 HostContainer properties
10.20.2.1 General
10.20.2.2 HostContainer.messageHandler Object Details
10.20.3 HostContainer methods
10.20.3.1 General
10.20.3.2 postMessage(...)
10.21 Icon
10.21.1 General
10.21.2 icon Properties
10.22 Link
10.22.1 General
10.22.2 Link properties
10.22.3 Link methods
10.22.3.1 General
10.22.3.2 setAction(cScript)
10.23 Net
10.23.1 General
10.23.2 Net properties
10.23.2.1 General
10.23.2.1.1 Net.SOAP properties
10.23.2.1.1.1 General
10.23.2.1.2 Net.SOAP Methods
10.23.2.1.2.1 connect
10.23.2.1.2.2 request
10.23.2.1.2.3 response
10.23.2.1.3 Net.Discovery Methods
10.23.2.1.3.1 queryServices
10.23.2.1.3.2 resolveService
10.23.3 Net methods
10.23.3.1 General
10.23.3.2 streamDecode(oStream, cEncoder)

10.23.3.3 streamDigest(oStream, cEncoder)
10.23.3.4 streamEncode(oStream, cEncoder)
10.24 OCG
10.24.1 General
10.24.2 OCG properties
10.24.2.1 General
10.24.2.2 OCG.constants Details
10.24.2.2.1 General
10.24.2.2.2 OCG.constants.intents Object details
10.24.2.2.3 OCG.constants.states Object details
10.24.3 OCG methods
10.24.3.1 General
10.24.3.2 getIntent()
10.24.3.3 setAction(cExpr)
10.24.3.4 setIntent(aIntentArray)
10.25 PrintParams
10.25.1 General
10.25.2 PrintParams properties
10.25.2.1 General
10.25.2.2 PrintParams.constants Properties
10.25.2.2.1 General
10.25.2.2.2 constants.duplexTypes Object
10.25.2.2.3 constants.flagValues object
10.25.2.2.4 constants.handling Object
10.25.2.2.5 constants.subsets Object
10.25.2.2.6 constants.printContents Object
10.26 RDN
10.26.1 General
10.26.2 RDN properties
10.27 ReadStream
10.27.1 General
10.27.2 ReadStream methods
10.28 security
10.28.1 General
10.28.2 security constants
10.28.2.1 General
10.28.2.2 security.HandlerName Object
10.28.2.3 security.EncryptTarget Object
10.28.3 security Properties
10.28.4 security Methods
10.28.4.1 General
10.28.4.2 chooseRecipientsDialog(oOptions)
10.28.4.2.1 Opens a dialog box that allows a user to choose a list of recipients. Returns an array of generic Group objects. DisplayOptions object
10.28.4.3 chooseSecurityPolicy([oOptions])
10.28.4.4 exportToFile(oObject, cDIPath)
10.28.4.5 getHandler(cName[, bUIEngine])
10.28.4.6 getSecurityPolicies([bUI, oOptions])
10.28.4.6.1 SecurityPolicyOptions object
10.28.4.7 importFromFile(cType[, cDIPath, bUI, cMsg])
10.29 SecurityHandler
10.29.1 General
10.29.2 SecurityHandler properties
10.29.2.1 General
10.29.2.2 SecurityHandler.digitalIDs Details
10.29.3 SecurityHandler methods
10.29.3.1 login([cPassword, cDIPath, oParams, bUI])
10.29.3.2 logout()
10.29.3.3 newDirectory()
10.29.3.3.1 LoginParameters Object
10.29.3.4 newUser([cPassword,cDIPath, oRDN, oCPS, bUI, cStore])
10.29.3.5 setPasswordTimeout(cPassword, iTimeout)
10.30 SecurityPolicy
10.30.1 General

10.30.2 SecurityPolicy properties
10.31 SignatureInfo
10.31.1 General
10.31.2 SignatureInfo Base properties
10.31.3 SignatureInfo object public key security handler properties
10.31.3.1 General
10.31.3.2 status and idValidity properties
10.31.3.3 Validity Values
10.31.3.4 Private Validity Values
10.31.4 Modification Detection and Prevention (MDP) Values
10.32 SOAP
10.32.1 General
10.32.2 SOAP properties
10.32.3 SOAP methods
10.32.3.1 General
10.32.3.2 connect(cURL)
10.32.3.2.1 WSDL Service Proxy Object
10.32.3.2.2 Exceptions
10.32.3.3 queryServices(cType, oAsync[, aDomains])
10.32.3.3.1 Service Query Object
10.32.3.3.2 Exceptions
10.32.3.3.3 Service Description Object
10.32.3.4 resolveService(cType, cDomain, cService, oResult)
10.32.3.4.1 Service Query Object
10.32.3.4.2 Exceptions
10.32.3.4.3 Additional notes on the oResult parameter
10.32.3.5 request(...)
10.32.3.5.1 oRequest Parameter Details
10.32.3.5.2 Mapping of Data Types
10.32.3.5.3 Exceptions
10.32.3.5.4 Additional notes on the oRequest parameter
10.32.3.6 response(...)
10.32.3.6.1 Exceptions
10.32.3.7 streamDecode(oStream, cEncoder)
10.32.3.8 streamDigest(oStream, cEncoder)
10.32.3.9 streamEncode(oStream, cEncoder)
10.32.3.10 streamFromString(cString)
10.32.3.11 stringFromStream(oStream)
10.33 Span
10.33.1 General
10.33.2 Span properties
10.34 Template
10.34.1 General
10.34.2 Template properties
10.34.3 Template methods
10.34.3.1 General
10.34.3.2 spawn([nPage, bRename, bOverlay, oXObject])
10.35 Thermometer
10.35.1 General
10.35.2 Thermometer properties
10.35.3 Thermometer methods
10.35.3.1 begin()
10.35.3.2 end()
10.36 this
10.36.1 General
10.36.2 Variable and function name conflicts
10.37 util
10.37.1 General
10.37.2 util methods
10.37.2.1 General
10.37.2.2 crackURL(cURL)
10.37.2.2.1 UrlParts object properties
10.37.2.3 iconStreamFromIcon(oIcon)
10.37.2.4 printd(cFormat, oDate[, bXFAPicture])

10.37.2.4.1 cFormat String Patterns
10.37.2.5 printf(cFormat[, ...])
10.37.2.5.1 Format String specification
10.37.2.6 printx(cFormat, cSource)
10.37.2.6.1 Format Masking Characters
10.37.2.7 readFileIntoStream([cDlPath, bBase64])
10.37.2.8 scand(cFormat, cDate)
10.37.2.9 spansToXML(aSpans)
10.37.2.10 streamFromString(cString[, cCharSet])
10.37.2.11 stringFromStream(oStream[, cCharSet])
10.37.2.12 xmlToSpans(cXml)

11 ECMAScript 3D API

11.1 General
11.1.1 Basic Objects
11.1.2 Scene object
11.1.3 Canvas object
11.1.4 Runtime object
11.1.5 Resource objects
11.2 Event handlers
11.2.1 General
11.2.2 CameraEvent
11.2.3 KeyEvent
11.2.4 MouseEvent
11.2.5 RenderEvent
11.2.6 ScrollWheelEvent
11.2.7 SelectionEvent
11.2.8 TimeEvent
11.2.9 ToolEvent

12 Object overview

12.1 General
12.2 Animation
12.2.1 General
12.2.2 Animation properties
12.3 Background
12.3.1 General
12.3.2 Background object properties
12.3.3 Background object methods
12.3.3.1 getColor()
12.3.3.2 setColor(topColor, bottomColor)
12.4 BoundingBox
12.4.1 General
12.4.2 BoundingBox properties
12.5 Camera
12.5.1 General
12.5.2 Camera properties
12.5.3 Camera methods
12.5.3.1 getScreenFromPosition(position, canvasWidth, canvasHeight)
12.5.3.2 getDirectionFromScreen(x, y, canvasWidth, canvasHeight)
12.6 CameraEvent
12.6.1 General
12.6.2 CameraEvent properties
12.7 CameraEventHandler
12.7.1 General
12.7.2 CameraEventHandler methods
12.7.2.1 new CameraEventHandler()
12.7.2.2 onEvent(event)
12.8 Canvas
12.8.1 General
12.8.2 Canvas properties
12.8.3 Canvas methods
12.8.3.1 getCamera
12.8.3.2 setCamera(camera)

12.9 ClippingPlane
12.9.1 General
12.9.2 ClippingPlane Methods
12.10 Color
12.10.1 General
12.10.2 Color properties
12.10.3 Color methods
12.10.3.1 new Color()
12.10.3.2 new Color(r, g, b)
12.10.3.3 Set(Color)
12.10.3.4 Set(r, g, b)
12.11 HitInfo
12.11.1 General
12.11.2 HitInfo properties
12.12 Host
12.12.1 General
12.13 Image
12.13.1 General
12.13.2 Image properties
12.13.3 Image methods
12.13.3.1 new Image(resource)
12.14 KeyEvent
12.14.1 General
12.14.2 KeyEvent properties
12.15 KeyEventHandler
12.15.1 General
12.15.2 KeyEventHandler methods
12.15.2.1 new KeyEventHandler()
12.15.2.2 onEvent(event)
12.16 Light
12.16.1 General
12.16.2 Light properties
12.17 Material
12.17.1 General
12.17.2 Material properties
12.18 Matrix4x4
12.18.1 General
12.18.2 Matrix4x4 Properties
12.18.3 Matrix4x4 Methods
12.18.3.1 new Matrix4x4()
12.18.3.2 new Matrix4x4(matrix)
12.18.3.3 invertInPlace()
12.18.3.4 isEqual(matrix)
12.18.3.5 multiply(matrix)
12.18.3.6 multiplyInPlace(matrix)
12.18.3.7 rotateAboutLine(angle, start, end)
12.18.3.8 rotateAboutLineInPlace(angle, start, end)
12.18.3.9 rotateAboutX(angle)
12.18.3.10 rotateAboutXInPlace(angle)
12.18.3.11 rotateAboutVector(angle, axis)
12.18.3.12 rotateAboutVectorInPlace(angle, axis)
12.18.3.13 rotateAboutY(angle)
12.18.3.14 rotateAboutYInPlace(angle)
12.18.3.15 rotateAboutZ(angle)
12.18.3.16 rotateAboutZInPlace(angle)
12.18.3.17 rotateWithQuaternion(quaternion)
12.18.3.18 rotateWithQuaternionInPlace(quaternion)
12.18.3.19 scale(x, y, z)
12.18.3.20 scaleInPlace(x, y, z)
12.18.3.21 set(matrix)
12.18.3.22 set(array)
12.18.3.23 set(v0, v1, v2, v3, v4, v5, v6, v7, v8, v9, v10, v11, v12, v13, v14, v15)
12.18.3.24 setIdentity()
12.18.3.25 setView(position, direction, up)

12.18.3.26 transformDirection(vector)
12.18.3.27 transformPosition(position)
12.18.3.28 translate(translation)
12.18.3.29 translateInPlace(translation)
12.18.3.30 transposeInPlace()
12.19 Mesh
12.19.1 General
12.19.2 Mesh properties
12.19.3 Mesh methods
12.19.3.1 computeBoundingBox()
12.19.3.2 setColor([color, faceIndex])
12.20 MouseEvent
12.20.1 General
12.20.2 MouseEvent properties
12.21 MouseEventHandler
12.21.1 General
12.21.2 MouseEventHandler properties
12.21.3 MouseEventHandler methods
12.21.3.1 new MouseEventHandler()
12.21.3.2 onEvent(event)
12.22 Node
12.22.1 General
12.22.2 Node properties
12.22.3 Node methods
12.22.3.1 detachFromCurrentAnimation()
12.23 Quaternion
12.23.1 General
12.23.2 Quaternion methods
12.23.2.1 new Quaternion()
12.23.2.2 Quaternion (matrix)
12.23.2.3 Quaternion(quaternion)
12.23.2.4 interpolate(quaternion, a)
12.23.2.5 interpolateInPlace(quaternion, a)
12.23.2.6 normalize()
12.24 RenderEvent
12.24.1 General
12.24.2 RenderEvent properties
12.25 RenderEventHandler
12.25.1 General
12.25.2 RenderEventHandler methods
12.25.2.1 new RenderEventHandler()
12.25.2.2 onEvent(event)
12.25.2.3 RenderOptions
12.26 Resource
12.26.1 General
12.26.2 Resource properties
12.26.3 Resource methods
12.26.3.1 Resource(path)
12.27 Runtime
12.27.1 General
12.27.2 Runtime properties
12.27.3 Runtime methods
12.27.3.1 addCustomMenuItem(name, label, type, checkedState)
12.27.3.2 addCustomToolButton(name, label, type)
12.27.3.3 addEventHandler(eventHandler)
12.27.3.4 disableTool(toolName)
12.27.3.5 enableTool(toolName)
12.27.3.6 getEventHandler(index)
12.27.3.7 getRendererName()
12.27.3.8 getView(index)
12.27.3.9 getView(name)
12.27.3.10 pause()
12.27.3.11 play()
12.27.3.12 refresh()

12.27.3.13 removeEventHandler(handler)
12.27.3.14 removeCustomMenuItem(menuName)
12.27.3.15 removeCustomToolButton(toolName)
12.27.3.16 setCurrentTool(toolName)
12.27.3.17 setCustomMenuItemChecked(menuItemName, checkedState)
12.27.3.18 setView(index, animate)
12.27.3.19 setView(name, animate)
12.28 Scene
12.28.1 General
12.28.2 Scene methods
12.28.2.1 activateAnimation(animation)
12.28.2.2 addModel(modelRes)
12.28.2.3 createClippingPlane()
12.28.2.4 createLight()
12.28.2.5 createSquareMesh(sizeX, sizeY[, name]))
12.28.2.6 computeBoundingBox()
12.28.2.7 update()
12.29 SceneObject
12.29.1 General
12.30 SceneObjectList
12.30.1 General
12.30.2 SceneObjectList methods
12.30.2.1 getByID(id)
12.30.2.2 getByIndex(index)
12.30.2.3 getByName(name)
12.31 ScrollWheelEvent
12.31.1 General
12.31.2 ScrollWheelEvent
12.32 ScrollWheelEventHandler
12.32.1 General
12.32.2 ScrollWheelEventHandler methods
12.32.2.1 new ScrollWheelEventHandler()
12.32.2.2 onEvent(event)
12.33 SelectionEvent
12.33.1 General
12.33.2 SelectionEvent properties
12.34 SelectionEventHandler
12.34.1 General
12.34.2 SelectionEventHandler methods
12.34.2.1 new SelectionEventHandler()
12.34.2.2 onEvent(event)
12.35 StateEvent
12.35.1 General
12.35.2 StateEvent properties
12.36 StateEventHandler
12.36.1 General
12.36.2 StateEventHandler methods
12.36.2.1 new StateEventHandler()
12.36.2.2 onEvent(event)
12.37 Texture
12.37.1 General
12.37.2 Texture properties
12.38 TimeEvent
12.38.1 General
12.38.2 TimeEvent properties
12.39 TimeEventHandler
12.39.1 General
12.39.2 TimeEventHandler methods
12.39.2.1 new TimeEventHandler()
12.39.2.2 onEvent(event)
12.40 ToolEvent
12.40.1 General
12.40.2 ToolEventHandler properties
12.41 ToolEventHandler

12.41.1 General
12.41.2 ToolEventHandler methods
12.41.2.1 new ToolEventHandler()
12.41.2.2 onEvent(event)
12.42 Vector3
12.42.1 General
12.42.2 Vector3 methods
12.42.2.1 new Vector3()
12.42.2.2 Vector3(x, y, z)
12.42.2.3 add(offset)
12.42.2.4 addInPlace(offset)
12.42.2.5 addScaled(offset, scale)
12.42.2.6 addScaledInPlace(offset, scale)
12.42.2.7 blend(vector, factor)
12.42.2.8 blendInPlace(vector, factor)
12.42.2.9 cross(vector)
12.42.2.10 dot(vector)
12.42.2.11 normalize()
12.42.2.12 scale(factor)
12.42.2.13 scaleInPlace(factor)
12.42.2.14 set(vector)
12.42.2.15 set(x, y, z)
12.42.2.16 set3(x, y, z)
12.42.2.17 subtract(offset)
12.42.2.18 subtractInPlace(offset)
12.43 View
12.43.1 General
12.43.2 View properties

Page count: 253