

# ISO 7761:2004-10 (E)

## Micrographics - Single-core cartridge for 16 mm processed microfilm - Dimensions and operational constraints

---

### Contents

Page

Foreword .....	iv
Introduction .....	v
1 Scope .....	1
2 Normative references .....	1
3 Terms and definitions .....	1
4 Requirements for cartridge assembly .....	2
4.1 Dimensions .....	2
4.1.1 Open cartridge .....	2
4.1.2 Enclosed cartridge .....	2
4.2 Test at maximum speed .....	5
4.3 Materials .....	7
4.3.1 Impact strength .....	7
4.3.2 Test conditions .....	7
4.3.3 Compatibility .....	7
4.4 Lubrication .....	7
4.5 Markings .....	7
4.6 Position of labels .....	7
4.7 Surface finish .....	7
5 Requirements for reel and film .....	9
5.1 Reel dimensions .....	9
5.2 Leader .....	9
5.2.1 Width .....	9
5.2.2 Thickness .....	9
5.2.3 Length .....	9
5.2.4 Terminators .....	9
5.3 Separate leaders .....	11
5.3.1 Dimensions .....	11
5.3.2 Leader-film secureness criterion .....	11
5.4 Trailer .....	11
5.4.1 Length .....	11
5.4.2 Affixing film to the core .....	11
5.4.3 Core-film secureness criteria .....	11
5.4.4 Test conditions .....	11
5.5 Image placement .....	15
5.6 Materials .....	16
5.6.1 Flexibility of flanges .....	16
5.6.2 Impact strength .....	16
5.6.3 Compatibility .....	16
5.7 Maximum roll diameter .....	16
5.8 Markings .....	16
5.9 Surface finishing .....	16
Annex A (normative) Reel capacity .....	17
Annex B (informative) Materials .....	18
Annex C (informative) Leading end of film .....	19
Bibliography .....	20