

# DIN EN 15431:2008-05 (E)

## Winter and road service area maintenance equipments - Power system and related controls - Interchangeability and performance requirements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Power System and related controls .....</b>	<b>5</b>
3.1	Hydraulic system for municipal vehicles - Specifications .....	5
3.1.1	Drive of the oil pump .....	5
3.1.2	Hydraulic Circuits .....	5
3.1.3	Connection between the hydraulic system of the vehicle and the implements .....	5
3.1.4	Flow Rates .....	5
3.1.5	Pressure .....	5
3.1.6	Power .....	6
3.1.7	Capacity of the oil tank .....	6
3.1.8	Maximum oil temperature, cooling capacity test procedure .....	6
3.1.9	Line cross sections .....	8
3.1.10	Couplings and functions .....	9
3.1.11	Hydraulic Fluid .....	10
3.2	Mechanical Front-Mounted Power Take Off PTO, shaft profile and Performance .....	10
3.2.1	General .....	10
3.2.2	Profile A: $n = 540 \text{ min}^{-1}$ $P_{\text{max}} = 60 \text{ kW}$ .....	10
3.2.3	Profile B: $n = 540 \text{ min}^{-1}$ or $n = 1\,000 \text{ min}^{-1}$ $P_{\text{max}} = 150 \text{ kW}$ .....	10
3.2.4	Power take-off shaft profile .....	11
3.3	Electrical Connectors .....	13
3.3.1	Connector 24 V, 7 pins, at the front of the vehicle, socket design according to ISO 1185 ..	13
3.3.2	Connector 12 V, 7 pins, at the front of the vehicle, socket design based on ISO 1724 .....	14
3.3.3	Electrical Connectors in the cabine, 24 V, 3 pin .....	15
3.3.4	Electrical Connectors in the cabin, 12 V, 3 pin .....	16
Bibliography .....		18