

DIN EN 12574-2:2017-05 (E)

Stationary waste containers - Part 2: Performance requirements and test methods

| Contents | | Page |
|-----------------|---|-------------|
| | European foreword | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Tests | 5 |
| 4.1 | General | 5 |
| 4.2 | Control before the tests | 5 |
| 4.2.1 | Visual aspects | 5 |
| 4.2.2 | Correspondence with EN 12574-1:2017 | 5 |
| 4.2.3 | Masses limit deviations | 6 |
| 4.2.4 | Colour | 6 |
| 4.2.5 | Marking | 6 |
| 4.3 | Control after the tests | 6 |
| 4.4 | Conditions of the tests | 6 |
| 4.5 | Test load | 6 |
| 4.6 | Tests on the containers | 6 |
| 4.6.1 | General | 6 |
| 4.6.2 | Impact test by ball drop | 6 |
| 4.6.3 | Impact on an inclined plane | 8 |
| 4.7 | Stability test | 9 |
| 4.8 | Dynamic tests | 9 |
| 4.8.1 | General | 9 |
| 4.8.2 | Pulling test | 9 |
| 4.8.3 | Immobilization test | 10 |
| 4.9 | Lifting-tilting tests | 10 |
| 4.9.1 | General | 10 |
| 4.9.2 | Lifting-tilting empty container | 10 |
| 4.9.3 | Lifting-tilting of the loaded container | 10 |
| 4.10 | Miscellaneous tests | 11 |
| 4.10.1 | Internal stress-cracking tests (for thermo plastics only) | 11 |
| 4.10.2 | Corrosion test | 11 |
| 4.10.3 | Weathering | 11 |
| 4.10.4 | Test method with child mannequin for containers with sliding mobile flap | 12 |
| 4.10.5 | Test for locked lid | 13 |
| 4.10.6 | Sequence of the tests | 13 |
| 5 | Tests report | 14 |
| | Annex A (normative) Device for ball drop test | 15 |
| | Annex B (informative) Apparatus for lateral impact test on inclined plane | 16 |
| | Annex C (normative) Weathering tests | 17 |
| | Annex D (informative) A-deviations | 18 |
| | Bibliography | 19 |