# ISO 10830:2011-07 (E)

## Space systems - Non-destructive testing - Automatic ultrasonic inspection method of graphite ingot for solid rocket motors

## Contents

Page


Foreword ..... iv

Introduction ..... v

1 Scope ..... 1

2 Normative references ..... 1

3 Terms and definitions ..... 1

4 General ..... 4
4.1 Requirements ..... 4
4.2 Test conductor ..... 5

5 Composition of ultrasonic test equipment ..... 5
5.1 Basic composition of equipment ..... 5
5.2 Ultrasonic test instrument ..... 5
5.3 Probe ..... 6
5.4 Scanning equipment ..... 6
5.5 Display and recording equipment ..... 6

6 Preparation of automatic ultrasonic inspection ..... 7
6.1 Reference blocks ..... 7
6.2 Water path ..... 8
6.3 Setting for angle-beam incidence ..... 8
6.4 Scanning zone and gate range ..... 8
6.5 Distance-amplitude correction ..... 9
6.6 Determination of apparent widths of beam spread ..... 9
6.7 Selection of scanning pitch in beam-index scanning ..... 10
6.8 Selection of data collection interval in incident-angle scanning ..... 10
6.9 Required compensation of detection sensitivity ..... 10

7 Procedure for automatic ultrasonic inspection ..... 11
7.1 Test blocks ..... 11
7.2 Test sequence ..... 12

8 Automatic ultrasonic inspection ..... 13
8.1 Preparation for testing ..... 13
8.2 Primary inspection ..... 13
8.3 Secondary inspection ..... 14

9 Acceptance criteria ..... 14

10 Reporting and recording ..... 14
10.1 General ..... 14
10.2 Report of test result ..... 14
10.3 Scanning details and corresponding gate range ..... 14
10.4 Inspection condition data ..... 15
10.5 Secondary inspection details ..... 15

**Annex A (normative) Reference blocks and test method for ultrasonic characteristic determination of graphite ingot ..... 16**

**Annex B (normative) Propagation-characteristic test of graphite ingot ..... 22**

**Bibliography ..... 25**