

ISO 10830:2011-07 (E)

Space systems - Non-destructive testing - Automatic ultrasonic inspection method of graphite ingot for solid rocket motors

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	General	4
4.1	Requirements	4
4.2	Test conductor	5
5	Composition of ultrasonic test equipment	5
5.1	Basic composition of equipment	5
5.2	Ultrasonic test instrument	5
5.3	Probe	6
5.4	Scanning equipment	6
5.5	Display and recording equipment	6
6	Preparation of automatic ultrasonic inspection	7
6.1	Reference blocks	7
6.2	Water path	8
6.3	Setting for angle-beam incidence	8
6.4	Scanning zone and gate range	8
6.5	Distance-amplitude correction	9
6.6	Determination of apparent widths of beam spread	9
6.7	Selection of scanning pitch in beam-index scanning	10
6.8	Selection of data collection interval in incident-angle scanning	10
6.9	Required compensation of detection sensitivity	10
7	Procedure for automatic ultrasonic inspection	11
7.1	Test blocks	11
7.2	Test sequence	12
8	Automatic ultrasonic inspection	13
8.1	Preparation for testing	13
8.2	Primary inspection	13
8.3	Secondary inspection	14
9	Acceptance criteria	14
10	Reporting and recording	14
10.1	General	14
10.2	Report of test result	14
10.3	Scanning details and corresponding gate range	14
10.4	Inspection condition data	15
10.5	Secondary inspection details	15

Annex A (normative) Reference blocks and test method for ultrasonic characteristic determination of graphite ingot	16
Annex B (normative) Propagation-characteristic test of graphite ingot	22
Bibliography	25