

ISO 26869:2012-04 (E)

Space systems - Small-auxiliary-spacecraft (SASC)-to- launch- vehicle interface control document

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative reference	1
3	Terms, definitions and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Abbreviated terms	1
4	Applicable and referenced documentation	2
4.1	Applicable documents	2
4.2	Reference documents	2
4.3	Waivers	2
5	SASC mission characteristics	2
5.1	SASC mission description	2
5.2	SASC additional constraints	2
5.3	SASC simulator	2
6	Mechanical interface	2
6.1	General	2
6.2	Mechanical configuration	3
6.3	SASC fundamental frequencies	3
6.4	Usable volume	3
6.5	LVSASC adapter interface	3
6.6	Connector and microswitch definition	3
6.7	Purges and fluid connection interface	3
7	Electrical interfaces	4
7.1	General	4
7.2	Umbilical wiring diagram	4
7.3	Umbilical connectors	4
7.4	Umbilical wiring links	4
7.5	Electrical commands dedication to SASC	5
7.6	Separation status transmission	6
7.7	Power supply	6
7.8	Earth potential continuity	6
8	Radio frequency and electromagnetic interface	6
9	LV and SASC mission characteristics	6
9.1	SASC input data for mission analysis	6
9.2	Trajectory and performance analysis	7
9.3	Launch windows	7
9.4	SASC pointing and separation	7
10	Induced environment	7
10.1	General	7

10.2	Mechanical environment	7
10.3	Thermal environment	8
10.4	Static pressure	9
10.5	Contamination and cleanliness	9
10.6	Radioandelectromagneticenvironment	9
10.7	Overallcompatibility	9
11	Verificationtests	9
11.1	General	9
11.2	SASCmechanicalenvironmentqualificationandacceptancetests	9
11.3	LV/SASC	10
11.4	Primary payload/SASC	10
12	Launch-rangeoperation	10
12.1	General	10
12.2	Rangecapabilities	10
12.3	Rangecommunicationfacility	13
12.4	Umbilicallinesandgroundlines	14
12.5	Overall data transmission	14
12.6	Operational constraints	15
12.7	Rangeservices	15