

ISO 22641:2012-07 (E)

Space data and information transfer systems - TM (telemetry) synchronization and channel coding

CONTENTS

<u>Section</u>	<u>Page</u>
1 INTRODUCTION	1-1
1.1 PURPOSE.....	1-1
1.2 SCOPE.....	1-1
1.3 APPLICABILITY.....	1-1
1.4 RATIONALE.....	1-2
1.5 DOCUMENT STRUCTURE.....	1-2
1.6 CONVENTIONS AND DEFINITIONS.....	1-3
1.7 PATENTED TECHNOLOGIES.....	1-5
1.8 REFERENCES.....	1-5
2 OVERVIEW	2-1
2.1 ARCHITECTURE.....	2-1
2.2 SUMMARY OF FUNCTIONS.....	2-1
2.3 INTERNAL ORGANIZATION OF SUBLAYER.....	2-3
3 CONVOLUTIONAL CODING	3-1
3.1 OVERVIEW.....	3-1
3.2 GENERAL.....	3-1
3.3 BASIC CONVOLUTIONAL CODE SPECIFICATION.....	3-2
3.4 PUNCTURED CONVOLUTIONAL CODES.....	3-4
4 REED-SOLOMON CODING	4-1
4.1 OVERVIEW.....	4-1
4.2 GENERAL.....	4-1
4.3 SPECIFICATION.....	4-1
4.4 DISCUSSION.....	4-6
5 CONCATENATED CODING	5-1
6 TURBO CODING	6-1
6.1 OVERVIEW.....	6-1
6.2 GENERAL.....	6-1
6.3 SPECIFICATION.....	6-1

CONTENTS (continued)

<u>Section</u>	<u>Page</u>
7 LOW-DENSITY PARITY-CHECK CODING	7-1
7.1 OVERVIEW	7-1
7.2 GENERAL	7-1
7.3 LOW-DENSITY PARITY-CHECK CODE WITH RATE 223/255	7-2
7.4 LOW-DENSITY PARITY-CHECK CODE FAMILY WITH RATES 1/2, 2/3, AND 4/5	7-7
8 FRAME SYNCHRONIZATION	8-1
8.1 OVERVIEW	8-1
8.2 THE ATTACHED SYNC MARKER (ASM)	8-2
8.3 ASM BIT PATTERNS	8-2
8.4 LOCATION OF ASM	8-4
8.5 RELATIONSHIP OF ASM TO REED-SOLOMON, TURBO, AND LDPC CODEBLOCKS AND CODEWORDS	8-4
8.6 ASM FOR EMBEDDED DATA STREAM	8-5
9 PSEUDO-RANDOMIZER	9-1
9.1 OVERVIEW	9-1
9.2 PSEUDO-RANDOMIZER DESCRIPTION	9-1
9.3 SYNCHRONIZATION AND APPLICATION OF PSEUDO-RANDOMIZER ...	9-2
9.4 SEQUENCE SPECIFICATION	9-2
9.5 LOGIC DIAGRAM	9-3
10 TRANSFER FRAME LENGTHS	10-1
10.1 OVERVIEW	10-1
10.2 GENERAL	10-1
10.3 CASE 1: UNCODED	10-1
10.4 CASE 2: CONVOLUTIONAL ONLY	10-1
10.5 CASE 3: REED-SOLOMON ONLY	10-1
10.6 CASE 4: CONCATENATED	10-2
10.7 CASE 5: TURBO	10-2
10.8 CASE 6: LDPC	10-3
11 MANAGED PARAMETERS	11-1
11.1 OVERVIEW	11-1
11.2 GENERAL	11-1

CONTENTS (continued)

<u>Section</u>	<u>Page</u>
11.3 MANAGED PARAMETERS FOR SELECTED OPTIONS	11-1
11.4 MANAGED PARAMETERS FOR CONVOLUTIONAL CODE	11-2
11.5 MANAGED PARAMETERS FOR REED-SOLOMON CODE	11-2
11.6 MANAGED PARAMETERS FOR TURBO CODE	11-3
11.7 MANAGED PARAMETERS FOR LOW-DENSITY PARITY-CHECK CODE	11-3
11.8 MANAGED PARAMETERS FOR FRAME SYNCHRONIZATION	11-3
ANNEX A SERVICE (NORMATIVE).....	A-1
ANNEX B SECURITY, SANA, AND PATENT CONSIDERATIONS (INFORMATIVE)	B-1
ANNEX C ANNEX TO SUBSECTION 7.3, LOW-DENSITY PARITY- CHECK CODE WITH RATE 223/255 (INFORMATIVE).....	C-1
ANNEX D ACRONYMS AND TERMS (INFORMATIVE).....	D-1
ANNEX E INFORMATIVE REFERENCES (INFORMATIVE)	E-1
ANNEX F TRANSFORMATION BETWEEN BERLEKAMP AND CONVENTIONAL REPRESENTATIONS (INFORMATIVE).....	F-1
ANNEX G EXPANSION OF REED-SOLOMON COEFFICIENTS (INFORMATIVE)	G-1
ANNEX H CHANGES FROM REFERENCES [E2] AND [E3] (INFORMATIVE)	H-1

Figure

1-1 Bit Numbering Convention.....	1-4
2-1 Relationship with OSI Layers	2-1
2-2 Internal Organization of the Sublayer at the Sending End.....	2-4
2-3 Internal Organization of the Sublayer at the Receiving End.....	2-5
3-1 Basic Convolutional Encoder Block Diagram	3-3
3-2 Punctured Encoder Block Diagram	3-4
4-1 Reed-Solomon Codeblock Partitioning	4-5
4-2 Functional Representation of R-S Interleaving.....	4-7
6-1 Interpretation of Permutation.....	6-5
6-2 Turbo Encoder Block Diagram	6-5
6-3 Turbo Codewords for Different Code Rates.....	6-8
6-4 Turbo Codeword with Attached Sync Marker.....	6-9
7-1 Base Parity Check Matrix of the Basic (8176, 7156) LDPC Code.....	7-3
7-2 Systematic Circulant Generator Matrix	7-6
7-3 Shortened Codeword.....	7-7
8-1 ASM Bit Pattern for Uncoded, Convolutional, Reed-Solomon, Concatenated, and Rate 7/8 LDPC Coded Data	8-3

CONTENTS (continued)

<u>Figure</u>	<u>Page</u>
8-2 ASM Bit Pattern for Rate 1/2 Turbo and Rates 1/2, 2/3, and 4/5 LDPC Coded Data	8-3
8-3 ASM Bit Pattern for Rate 1/3 Turbo Coded Data	8-3
8-4 ASM Bit Pattern for Rate 1/4 Turbo Coded Data	8-3
8-5 ASM Bit Pattern for Rate 1/6 Turbo Coded Data	8-4
8-6 Embedded ASM Bit Pattern	8-5
9-1 Pseudo-Randomizer Configuration	9-2
9-2 Pseudo-Randomizer Logic Diagram	9-3
F-1 Transformational Equivalence	F-2

Table

3-1 Puncture Code Patterns for Convolutional Code Rates	3-4
6-1 Specified Information Block Lengths	6-3
6-2 Codeword Lengths for Supported Code Rates (Measured in Bits)	6-3
6-3 Parameters k_1 and k_2 for Specified Information Block Lengths	6-4
7-1 Specification of Circulants	7-4
7-2 Values of Submatrix Size M for Supported Codes	7-7
7-3 Description of $\phi_k(0, M)$ and $\phi_k(1, M)$	7-9
7-4 Description of $\phi_k(2, M)$ and $\phi_k(3, M)$	7-10
7-5 Codeword Lengths for Supported Code Rates (Measured in Bits)	7-11
11-1 Managed Parameters for Selected Options	11-2
11-2 Managed Parameters for Convolutional Code	11-2
11-3 Managed Parameters for Reed-Solomon Code	11-2
11-4 Managed Parameters for Turbo Code	11-3
11-5 Managed Parameters for Low Density Parity Check Code	11-3
11-6 Managed Parameters for Frame Synchronization	11-3
C-1 Table of Circulants for the Generator Matrix	C-1
F-1 Equivalence of Representations	F-5
H-1 Terms That Have Been Changed from Reference [E2]	H-2
H-2 Terms That Have Been Changed from Reference [E3]	H-2