

# DIN 65251:2013-05 (E)

Aerospace series - Bolts, with MJ threads, in titanium alloys, strength class 900 MPa and 1 100 MPa - Technical specification

---

<b>Contents</b>	<b>Page</b>
Foreword .....	3
<b>1 Scope .....</b>	<b>4</b>
<b>2 Normative references .....</b>	<b>4</b>
<b>3 Terms and definitions.....</b>	<b>5</b>
<b>4 Quality assurance .....</b>	<b>7</b>
<b>4.1 General .....</b>	<b>7</b>
<b>4.1.1 Approval of manufacturer.....</b>	<b>7</b>
<b>4.1.2 Certification of inspection results .....</b>	<b>7</b>
<b>4.1.3 Qualification of bolts .....</b>	<b>7</b>
<b>4.1.4 Acceptance of bolts .....</b>	<b>7</b>
<b>4.2 Qualification inspection conditions.....</b>	<b>7</b>
<b>4.3 Acceptance inspection conditions.....</b>	<b>8</b>
<b>4.4 Use of 'Statistical process control — (SPC)' .....</b>	<b>8</b>
<b>5 Requirements.....</b>	<b>8</b>
<b>Annex A (normative) Cross-sectional areas and formulae for tensile test and tension fatigue test loads .....</b>	<b>25</b>
<b>A.1 Cross-sectional area.....</b>	<b>25</b>
<b>A.2 Equations.....</b>	<b>25</b>
<b>A.2.1 Cross-sectional area.....</b>	<b>25</b>
<b>A.2.2 Cross-sectional area for threads &lt; M4/MJ4 .....</b>	<b>26</b>
<b>A.2.3 Tensile test load .....</b>	<b>26</b>
<b>A.2.4 Tension fatigue test loads.....</b>	<b>26</b>
<b>Annex B (normative) Cross-sectional areas and formulae for double shear loads .....</b>	<b>27</b>
<b>B.1 Cross-sectional area values (single section).....</b>	<b>27</b>
<b>B.2 Formulae.....</b>	<b>27</b>
<b>B.2.1 Shear strength cross-sectional area (single section) .....</b>	<b>27</b>
<b>B.2.2 Double shear strength test load .....</b>	<b>27</b>
<b>Bibliography.....</b>	<b>28</b>