DIN EN 16603-50-04:2014-12 (E)

Space engineering - Space data links - Telecommand protocols, synchronization and channel coding; English version EN 16603-50-04:2014

Contents

Page

Foreword 10

1 Scope 11

2 Normative references 12

3 Terms, definitions and abbreviated terms 13

3.1 Terms from other standards 13

3.2 Terms specific to the present standard 13

3.3 Abbreviated terms 14

3.4 Conventions 15

3.4.1 Bit 0, bit 1, bit N−1 15

3.4.2 Most significant bit 15

3.4.3 Use of capitals for the names of data structures and fields 15

4 Overview 16

4.1 Presentation 16

4.2 Protocol profiles 16

4.3 Segmentation sublayer 17

4.4 Transfer sublayer 18

4.5 Synchronization and channel coding sublayer 18

4.6 Physical layer 18

4.7 Virtual channels 19

5 Segmentation sublayer 20

5.1 Overview 20

5.2 TC Segment 21

5.2.1 General 21

5.2.2 Segment Header 22

5.2.3 Segment Data Field 23

5.3 Transfer notification 23

5.3.1 Overview 23

5.3.2 Requirements 24

5.4 Blocking of packets 25

5.4.1 Overview 25
5.4.2 Virtual channels where TC Segments are used 25
5.4.3 Virtual channels where TC Segments are not used 26
5.4.4 Packet properties 26
5.4.5 Blocking function 27
5.4.6 Deblocking function 27
5.5 Segmentation 27
5.5.1 Overview 27
5.5.2 Segmenting function 28
5.5.3 Reassembly function 28
5.5.4 Packet assembly controller 29
5.6 MAP multiplexing 32
6 Transfer sublayer 33
6.1 Overview 33
6.1.1 Data structures in the transfer sublayer 33
6.1.2 Procedures in the transfer sublayer 33
6.2 TC Transfer Frame definition 35
6.2.1 General 35
6.2.2 Transfer Frame Primary Header 36
6.2.3 Transfer Frame Data Field 40
6.2.4 Frame Error Control Field 41
6.3 CLCW definition 43
6.3.1 General 43
6.3.2 Control Word Type 45
6.3.3 CLCW Version Number 45
6.3.4 Status Field 45
6.3.5 COP in Effect 45
6.3.6 Virtual Channel Identification 45
6.3.7 Reserved Spare 46
6.3.8 No RF Available Flag 46
6.3.9 No Bit Lock Flag 47
6.3.10 Lockout Flag 47
6.3.11 Wait Flag 48
6.3.12 Retransmit Flag 48
6.3.13 FARM-B Counter 48
6.3.14 Reserved Spare 48
6.3.15 Report Value 49

6.4 Frame header procedure 49
6.5 Frame error control procedure at the sending end 49
6.6 Frame delimiting and fill removal procedure....49
6.6.1 Overview....49
6.6.2 Actions....50
6.7 Frame error control procedure at the receiving end 50
6.8 Frame header validation procedure 50
6.8.1 Overview....50
6.8.2 Actions....51
6.9 Virtual channel multiplexing 51
6.9.1 Overview....51
6.9.2 Multiplexing mechanism....52
6.9.3 Demultiplexing 52
7 COP-1....53
7.1 Overview 53
7.1.1 Scope....53
7.1.2 Interfaces....53
7.1.3 Retransmission protocol....53
7.1.4 Frames....54
7.1.5 Services....54
7.1.6 Protocol machine 56
7.2 Internal variables 56
7.2.1 Overview....56
7.2.2 FOP-1 Variables 57
7.2.3 FARM-1 variables 64
7.3 Features of COP-1 interfaces 69
7.3.1 Overview....69
7.3.2 Parameters 70
7.4 Upper interface of COP-1 at the sending end 70
7.4.1 Overview....70
7.4.2 Sequence-controlled service management interface....71
7.4.3 Sequence-controlled service data transfer interface....77
7.4.4 Expedited service data transfer interface 80
7.5 Upper interface of COP-1 at the receiving end....82
7.5.1 Overview....82
7.5.2 Buffer management mechanism....82
7.5.3 The wait system....82

7.5.4 Single back-end buffer 83
7.5.5 FDU Arrived Indication 84
7.6 Lower interface of COP-1 at the sending end 84
7.6.1 Overview 84
7.6.2 Transmit Request for Frame signal 85
7.6.3 Abort request signal 85
7.6.4 Response signal 86
7.7 Lower interface of COP-1 at the receiving end 86
7.7.1 Overview 86
7.7.2 Valid Frame Arrived Indication 87
7.8 Format of COP-1 control commands 87
7.8.1 Overview 87
7.8.2 General 87
7.8.3 Unlock 87
7.8.4 Set V(R) 88
7.9 Actions 88
7.9.1 Format of the state tables 88
7.9.2 FOP-1 89
7.9.3 FARM-1 96
8 Synchronization and channel coding sublayer 111
8.1 Overview 111
8.2 BCH codeblock 111
8.2.1 General 111
8.2.2 Information 112
8.2.3 Error Control 112
8.3 Communications link transmission unit (CLTU) 113
8.3.1 General 113
8.3.2 Start Sequence 113
8.3.3 Encoded Data 114
8.3.4 Tail Sequence 114
8.4 Randomization procedure 115
8.4.1 Overview 115
8.4.2 General 115
8.4.3 Random sequence 115
8.4.4 Application of the randomizer 116
8.5 BCH codeblock encoding procedure 116
8.6 Fill bits 117

8.6.1 Overview 117
8.6.2 General 117
8.7 Channel logic at the receiving end 118
8.8 BCH codeblock decoding procedures 119
8.8.1 Overview 119
8.8.2 General 120

9 Physical layer 121
9.1 Overview 121
9.2 Physical layer data structures 121
9.2.1 Acquisition sequence 121
9.2.2 CLTU 122
9.2.3 Idle sequence 122
9.3 Physical layer procedures 122
9.3.1 Overview 122
9.3.2 Carrier modulation modes 122
9.3.3 Telecommand session 124
9.3.4 Physical layer operation procedure (PLOP) 124

Annex A (informative) Frame error control 127
A.1 Overview 127
A.2 Encoding 127
A.3 Decoding 128

Annex B (informative) Changes from ESA-PSS-04-107 129
B.1 Overview 129
B.2 Technical changes 129

Annex C (informative) Differences from CCSDS recommendations 132
C.1 Overview 132
C.2 Differences 132

Annex D (informative) Performance issues 135
D.1 Introduction 135
D.2 Performance components 136
D.3 Factors affecting frame rejection rate 136
D.3.1 Bit synchronization factor 136
D.3.2 CLTU Start Sequence factors 137
D.3.3 BCH Codeblock Factor 138
D.3.4 Tail Sequence factor 140

D.3.5 Frames and CLTUs 141
D.4 Factors affecting frame undetected error rate 143
Annex E (informative) Mission configuration parameters 147
E.1 Introduction 147
E.2 Parameters of a physical channel 147
E.2.1 Overview 147
E.2.2 Fixed parameters 147
E.2.3 Length of the acquisition sequence 147
E.2.4 Physical layer operation procedure 148
E.2.5 Transfer Frame Version Number 148
E.2.6 Maximum length of a TC Transfer Frame 148
E.2.7 Virtual channels 148
E.2.8 Use of the expedited service 148
E.2.9 Multiplexing parameters 148
E.3 Parameters of a virtual channel 149
E.3.1 Overview 149
E.3.2 Spacecraft Identifier and Virtual Channel Identifier 149
E.3.3 Maximum length of a TC Transfer Frame 149
E.3.4 FOP-1 parameters 149
E.3.5 CLCW reporting rate 149
E.3.6 Status Field of CLCW 149
E.3.7 Fixed parameters 149
E.3.8 FARM-1 sliding window parameters 150
E.3.9 Use of TC Segments 150
E.3.10 Parameters of a virtual channel with TC Segments 150
E.3.11 Parameters of a virtual channel without TC Segments 150
E.4 Parameters of a MAP 151
E.4.1 Overview 151
E.4.2 MAP Identifier 151
E.4.3 Use of the blocking function 151
E.4.4 Segmentation function 151
E.5 Parameters for packet types 152
E.5.1 Overview 152
E.5.2 Valid packet version numbers 152
Bibliography 153

Figures

Figure 3-1: numbering convention 15
Figure 4-1: Layers and sublayers specified in this Standard 17
Figure 5-1: TC Segment 21
Figure 5-2: Example of blocking of packets 25
Figure 5-3: Example of segmentation of a user data unit 28
Figure 6-1: TC Transfer Frame format 36
Figure 6-2: Format of a CLCW 44
Figure 7-1: COP-1 sequence variables 55
Figure 7-2: FARM sliding window concept 67
Figure 7-3: State table format 89
Figure 7-4: Actions for look for directive 94
Figure 7-5: Actions for look for FDU 95
Figure 7-6: FOP-1 state transitions for main protocol 105
Figure 7-7: FOP-1 state transitions for initialisation protocol 106
Figure 7-8: FOP-1 state transitions 107
Figure 7-9: FARM-1 state transitions 110
Figure 8-1: BCH codeblock format 112
Figure 8-2: Format of a CLTU 113
Figure 8-3: Bit pattern of the Start Sequence 113
Figure 8-4: Bit transition generator logic diagram 116
Figure 8-5: (63,56) Modified BCH code generator 117
Figure 8-6: State diagram for the channel (receiving end) 119
Figure 9-1: Sequence of CMMs comprising PLOP-2 125
Figure 9-2: Sequence of CMMs comprising PLOP-1 126

Figure A-1 : Encoder 127
Figure A-2 : Decoder 128
Figure D-1 : Frame rejection probability, P_{FY}, in SEC mode using PLOP-2 143
Figure D-2 : Probability of undetected error in a frame in SEC mode 146

Tables

Table 6-1: Sending-end procedures in the transfer sublayer 34
Table 6-2: Receiving-end procedures in the transfer sublayer 35
Table 6-3: Combined Bypass Flag and Control Command Flag 38
Table 6-4: Fields in a CLCW 43
Table 7-1: COP-1 interfaces 70

Table 7-2: Signals for management interface 71
Table 7-3: FOP-1 directive types and qualifiers 73
Table 7-4: Reasons for an Alert notification 75
Table 7-5: Signals for sequence-controlled service data transfer interface 78
Table 7-6: Signals for expedited service data transfer interface....80
Table 7-7: Signals for the interface of FOP-1 to the lower procedures....84
Table 7-8: FOP-1 state table 98
Table 7-9: FARM-1 state table....108
Table 8-1: Channel states (receiving end) 118
Table 8-2: Channel events (receiving end) 119
Table 9-1: Carrier modulation modes 123

Table B-1 : Field name differences from ESA-PSS-04-107 131
Table B-2 : Names with “Communications” or “Command”....131
Table C-1 : Name differences from CCSDS recommendations 134
Table D-1 : Probability of not recognizing the Start Sequence....138
Table D-2 : Meaning of decoding values 138
Table D-3 : Decoding cases in SEC mode....138
Table D-4 : Probability of codeblock rejection for a CLTU during decoding in SEC mode...140
Table D-5 : Parity and Syndrome when Tail Sequence has errors....141
Table D-6 : Probability of missing the Tail Sequence....141
Table D-7 : Frame rejection probability, P_{FY} (PLOP-2)....142
Table D-8 : Sources of undetected errors (SEC mode)....143
Table D-9 : Probability of *n* errors occurring in a codeblock....144
Table D-10 : Error detection performance when decoding a codeblock in SEC mode 144
Table D-11 : Probability of undetected error in a frame, SEC mode, with CRC 145