DIN EN 16603-50-05:2017-06 (E)

Space engineering - Radio frequency and modulation; English version EN 16603-50-05:2014 + AC:2017

Inhalt

Seite

Foreword 6

Introduction 7

1 Scope 8

2 Normative references 9

3 Terms, definitions and abbreviated terms 10

3.1 Terms from other standards 10

3.2 Terms specific to the present standard 10

3.3 Abbreviated terms 12

4 Frequency allocations, assignment and use 15

4.1 Frequency allocations to the Space Operation, Space Research and Earth Exploration-Satellite services 15

4.1.1 Overview 15

4.1.2 Frequency bands allocated to the Space Radiocommunications services 15

4.2 Specific conditions for the use of certain frequency bands 17

4.2.1 2 025 MHz – 2 120 MHz and 2 200 MHz – 2 300 MHz bands 17

4.2.2 8 025 MHz – 8 400 MHz band 18

4.2.3 8 400 MHz - 8 450 MHz band 19

4.2.4 8 450 MHz – 8 500 MHz band 19

4.2.5 25,5 GHz – 27,0 GHz, 37,0 GHz – 38 GHz and 40,0 GHz – 40,5 GHz bands 19

4.3 Frequency assignment procedure 20

4.3.1 Choice of frequencies 20

4.3.2 Advance publication, coordination and notification of frequencies 21

5 Transmitted signals 22

5.1 Turnaround frequency ratio for coherent transponders 22

5.1.1 Generation of the transmitted carrier 22

5.1.2 Band pairs 22

5.2 Carrier frequency stability 24

5.2.1 Spacecraft transmitter 24

5.2.2 Spacecraft receiver 25
5.2.3 Ground station equipment 25
5.3 Polarization 26
5.4 Occupied bandwidth considerations 26
5.5 Emissions 28
5.5.1 Unwanted emission power level 28
5.5.2 Cessation of emissions 32
5.5.3 Power flux density limits at the Earth's surface 32
5.5.4 Power flux density limits at the GSO in the 25,5 GHz - 27,0 GHz band 33
5.5.5 Power limits for Earth station emissions 34
5.5.6 Time limitations on transmissions 35

6 Modulation 36

6.1 Phase modulation with residual carriers 36
6.1.1 Application 36
6.1.2 Modulating waveforms 36
6.1.3 PCM waveforms and data rates 37
6.1.4 Use of subcarriers 39
6.1.5 Data transition density 41
6.1.6 Carrier modulation index 42
6.1.7 Sense of modulation 42
6.1.8 Modulation linearity 42
6.1.9 Residual amplitude modulation 42
6.1.10 Carrier phase noise 43
6.1.11 Residual carrier, out-of-band emission and discrete spectral lines 43
6.2 Suppressed carrier modulation 44
6.2.1 Application and modulation schemes 44
6.2.2 Modulating waveforms 45
6.2.3 Carrier modulation 45
6.2.4 Data transition density 51
6.2.5 Symbol rate stability 51
6.2.6 Carrier phase noise 51
6.2.7 Carrier suppression, out-of-band emission and discrete spectral lines 51
6.3 Spectral roll-off 52

7 Link acquisition procedures 53

7.1 Space-Earth 53
7.1.1 Normal operation 53

7.1.2 Alternative mode of operation 53
7.1.3 Coherent mode 53
7.2 Earth-space 54
7.2.1 2 025 MHz - 2 110 MHz category A 54
7.2.2 2 110 MHz - 2 120 MHz category B 55
7.2.3 7 145 MHz - 7 190 MHz category B 55
7.2.4 7 190 MHz – 7 235 MHz category A....55

8 RF interface control....57

8.1 RF interface control documents 57
8.2 Spacecraft-Earth station interface control document....57
8.2.1 Overview....57
8.2.2 Process....57
8.3 Link budget tables....58
8.3.1 General....58
8.3.2 Parameters 58
8.4 Spacecraft-ground network compatibility test....61

9 GMSK and 8PSK TCM modulation formats 63

9.1 GMSK modulation format....63
9.2 8PSK TCM modulation format 64
9.2.1 General principles 64
9.2.2 4 dimensional 8PSK-TCM encoder 64
9.2.3 Differential encoders for SEF = 2 and 2,5....65
9.2.4 Trellis encoder structure....66
9.2.5 Constellation mapper for 4 dimensional 8PSK-TCM....66
9.2.6 Channel filtering 68

Annex A (normative) Spacecraft-Earth station interface control document - DRD 71

Annex B (informative) Cross-support from other networks 72

Annex C (informative) Protection of Ariane-5 RF system 73

Annex D (informative) Differences from CCSDS recommendations....76

Annex E (informative) Tailoring guidelines....78

Bibliography....79

Figures

Figure 4-1: Maximum allowable bandwidth in the band 8 400 MHz - 8 450 MHz 20
Figure 6-1: PCM waveforms and symbol duration definition 38
Figure 6-2: Symbol rate reference point 39
Figure 6-3: QPSK/OQPSK constellation mapping 46
Figure 6-4: OQPSK post-amplifier filter transfer function 49
Figure 6-5: Spectral emission masks for telemetry transmission at symbol rates above 60 ksps 52
Figure 8-1: Parameter distributions and their equations.....60
Figure 9-1: General principle of the 4D-8PSK TCM modulator 65
Figure 9-2: Codes to eliminate 22,5° phase ambiguity on carrier synchronization 66
Figure 9-3: Representation of a 64 state L=7, rate 3/4 systematic trellis encoder 66
Figure 9-4: Constellation mapper for SEF = 2.....67
Figure 9-5: Constellation mapper for SEF = 2,5.....67
Figure 9-6: Transmit structure for baseband, square root raised-cosine shaping.....69
Figure 9-7: Transfer function for a 4 poles/2 zeros elliptic filter.....69
Figure 9-8: Transmit structure for post-amplifier shaping.....70

Tables

Table 4-1: Frequency allocations to the Space Operation, Space Research and Earth Exploration-Satellite services 16
Table 5-1: Turnaround frequency ratios for coherent transponder operation 23
Table 5-2 Alternative turnaround frequency ratios for coherent transponder operation.....24
Table 5-3: Frequency stability for spacecraft transmitters.....24
Table 5-4: Frequency stability for spacecraft receivers.....25
Table 5-5: Occupied bandwidth.....27
Table 5-6: Maximum level of spurious emissions.....28
Table 5-7: Threshold levels of interference detrimental to radio astronomy spectral line (i.e. narrow bandwidth) observations at the surface of the Earth due to terrestrial interference sources (Recommendation ITU-R RA.769-2).....30
Table 5-8: Threshold levels of interference detrimental to radio astronomy continuum (i.e. wide bandwidth) observations at the surface of the Earth due to terrestrial interference sources (Recommendation ITU-R RA.769-2).....31
Table 5-9: Harmful interference levels at deep space antenna sites.....32
Table 5-10: Power flux density limits at the Earth's surface.....33
Table 6-1: PCM waveforms and rates for residual carrier modulation.....37
Table 6-2: Subcarriers used with phase-modulated carriers 39
Table 6-3: Limits of the peak modulation index.....42
Table 6-4: PCM waveforms 45
Table 8-1: Probability density functions for link budgets 60