

# DIN EN 16603-50-05:2017-06 (E)

Space engineering - Radio frequency and modulation; English version EN 16603-50-05:2014 + AC:2017

---

Inhalt	Seite
<b>Foreword</b> .....	<b>6</b>
<b>Introduction</b> .....	<b>7</b>
<b>1 Scope</b> .....	<b>8</b>
<b>2 Normative references</b> .....	<b>9</b>
<b>3 Terms, definitions and abbreviated terms</b> .....	<b>10</b>
3.1 Terms from other standards.....	10
3.2 Terms specific to the present standard .....	10
3.3 Abbreviated terms.....	12
<b>4 Frequency allocations, assignment and use</b> .....	<b>15</b>
4.1 Frequency allocations to the Space Operation, Space Research and Earth Exploration-Satellite services .....	15
4.1.1 Overview .....	15
4.1.2 Frequency bands allocated to the Space Radiocommunications services.....	15
4.2 Specific conditions for the use of certain frequency bands.....	17
4.2.1 2 025 MHz – 2 120 MHz and 2 200 MHz – 2 300 MHz bands .....	17
4.2.2 8 025 MHz – 8 400 MHz band.....	18
4.2.3 8 400 MHz - 8 450 MHz band .....	19
4.2.4 8 450 MHz – 8 500 MHz band.....	19
4.2.5 25,5 GHz – 27,0 GHz, 37,0 GHz – 38 GHz and 40,0 GHz – 40,5 GHz bands .....	19
4.3 Frequency assignment procedure.....	20
4.3.1 Choice of frequencies .....	20
4.3.2 Advance publication, coordination and notification of frequencies .....	21
<b>5 Transmitted signals</b> .....	<b>22</b>
5.1 Turnaround frequency ratio for coherent transponders .....	22
5.1.1 Generation of the transmitted carrier .....	22
5.1.2 Band pairs.....	22
5.2 Carrier frequency stability .....	24
5.2.1 Spacecraft transmitter .....	24

5.2.2	Spacecraft receiver .....	25
5.2.3	Ground station equipment.....	25
5.3	Polarization.....	26
5.4	Occupied bandwidth considerations .....	26
5.5	Emissions .....	28
5.5.1	Unwanted emission power level .....	28
5.5.2	Cessation of emissions .....	32
5.5.3	Power flux density limits at the Earth's surface.....	32
5.5.4	Power flux density limits at the GSO in the 25,5 GHz - 27,0 GHz band .....	33
5.5.5	Power limits for Earth station emissions .....	34
5.5.6	Time limitations on transmissions.....	35
<b>6</b>	<b>Modulation .....</b>	<b>36</b>
6.1	Phase modulation with residual carriers.....	36
6.1.1	Application .....	36
6.1.2	Modulating waveforms .....	36
6.1.3	PCM waveforms and data rates .....	37
6.1.4	Use of subcarriers .....	39
6.1.5	Data transition density.....	41
6.1.6	Carrier modulation index .....	42
6.1.7	Sense of modulation .....	42
6.1.8	Modulation linearity .....	42
6.1.9	Residual amplitude modulation .....	42
6.1.10	Carrier phase noise.....	43
6.1.11	Residual carrier, out-of-band emission and discrete spectral lines .....	43
6.2	Suppressed carrier modulation .....	44
6.2.1	Application and modulation schemes .....	44
6.2.2	Modulating waveforms .....	45
6.2.3	Carrier modulation.....	45
6.2.4	Data transition density.....	51
6.2.5	Symbol rate stability .....	51
6.2.6	Carrier phase noise.....	51
6.2.7	Carrier suppression, out-of-band emission and discrete spectral lines .....	51
6.3	Spectral roll-off .....	52
<b>7</b>	<b>Link acquisition procedures.....</b>	<b>53</b>
7.1	Space-Earth.....	53
7.1.1	Normal operation .....	53

7.1.2	Alternative mode of operation .....	53
7.1.3	Coherent mode .....	53
7.2	Earth-space .....	54
7.2.1	2 025 MHz - 2 110 MHz category A .....	54
7.2.2	2 110 MHz - 2 120 MHz category B .....	55
7.2.3	7 145 MHz - 7 190 MHz category B .....	55
7.2.4	7 190 MHz – 7 235 MHz category A.....	55
<b>8</b>	<b>RF interface control.....</b>	<b>57</b>
8.1	RF interface control documents .....	57
8.2	Spacecraft-Earth station interface control document.....	57
8.2.1	Overview.....	57
8.2.2	Process.....	57
8.3	Link budget tables.....	58
8.3.1	General.....	58
8.3.2	Parameters .....	58
8.4	Spacecraft-ground network compatibility test.....	61
<b>9</b>	<b>GMSK and 8PSK TCM modulation formats .....</b>	<b>63</b>
9.1	GMSK modulation format.....	63
9.2	8PSK TCM modulation format .....	64
9.2.1	General principles .....	64
9.2.2	4 dimensional 8PSK-TCM encoder .....	64
9.2.3	Differential encoders for SEF = 2 and 2,5.....	65
9.2.4	Trellis encoder structure.....	66
9.2.5	Constellation mapper for 4 dimensional 8PSK-TCM.....	66
9.2.6	Channel filtering .....	68
<b>Annex A (normative)</b>	<b>Spacecraft-Earth station interface control document - DRD .....</b>	<b>71</b>
<b>Annex B (informative)</b>	<b>Cross-support from other networks .....</b>	<b>72</b>
<b>Annex C (informative)</b>	<b>Protection of Ariane-5 RF system .....</b>	<b>73</b>
<b>Annex D (informative)</b>	<b>Differences from CCSDS recommendations.....</b>	<b>76</b>
<b>Annex E (informative)</b>	<b>Tailoring guidelines.....</b>	<b>78</b>
<b>Bibliography.....</b>		<b>79</b>

## Figures

Figure 4-1: Maximum allowable bandwidth in the band 8 400 MHz - 8 450 MHz .....	20
Figure 6-1: PCM waveforms and symbol duration definition .....	38
Figure 6-2: Symbol rate reference point .....	39
Figure 6-3: QPSK/OQPSK constellation mapping .....	46
Figure 6-4: OQPSK post-amplifier filter transfer function .....	49
Figure 6-5: Spectral emission masks for telemetry transmission at symbol rates above 60 ksp/s .....	52
Figure 8-1: Parameter distributions and their equations.....	60
Figure 9-1: General principle of the 4D-8PSK TCM modulator .....	65
Figure 9-2: Codes to eliminate 22,5° phase ambiguity on carrier synchronization .....	66
Figure 9-3: Representation of a 64 state L=7, rate 3/4 systematic trellis encoder .....	66
Figure 9-4: Constellation mapper for SEF = 2.....	67
Figure 9-5: Constellation mapper for SEF = 2,5.....	67
Figure 9-6: Transmit structure for baseband, square root raised-cosine shaping.....	69
Figure 9-7: Transfer function for a 4 poles/2 zeros elliptic filter .....	69
Figure 9-8: Transmit structure for post-amplifier shaping.....	70

## Tables

Table 4-1: Frequency allocations to the Space Operation, Space Research and Earth Exploration-Satellite services .....	16
Table 5-1: Turnaround frequency ratios for coherent transponder operation .....	23
Table 5-2 Alternative turnaround frequency ratios for coherent transponder operation .....	24
Table 5-3: Frequency stability for spacecraft transmitters.....	24
Table 5-4: Frequency stability for spacecraft receivers .....	25
Table 5-5: Occupied bandwidth .....	27
Table 5-6: Maximum level of spurious emissions.....	28
Table 5-7: Threshold levels of interference detrimental to radio astronomy spectral line (i.e. narrow bandwidth) observations at the surface of the Earth due to terrestrial interference sources (Recommendation ITU-R RA.769-2).....	30
Table 5-8: Threshold levels of interference detrimental to radio astronomy continuum (i.e. wide bandwidth) observations at the surface of the Earth due to terrestrial interference sources (Recommendation ITU-R RA.769-2).....	31
Table 5-9: Harmful interference levels at deep space antenna sites .....	32
Table 5-10: Power flux density limits at the Earth's surface .....	33
Table 6-1: PCM waveforms and rates for residual carrier modulation.....	37
Table 6-2: Subcarriers used with phase-modulated carriers .....	39
Table 6-3: Limits of the peak modulation index.....	42
Table 6-4: PCM waveforms .....	45
Table 8-1: Probability density functions for link budgets .....	60