

Table of contents

- European foreword.....7**
- Introduction.....8**
- 1 Scope.....9**
- 2 Normative references 10**
- 3 Terms, definitions and abbreviated terms..... 12**
 - 3.1 Terms from other standards..... 12
 - 3.2 Terms specific to the present standard 12
 - 3.3 Abbreviated terms..... 16
 - 3.4 Bit numbering convention 17
 - 3.5 Nomenclature 17
- 4 Overview of the standard and principles..... 19**
 - 4.1 Document organization 19
 - 4.2 Relationship of CAN Bus Network to existing Architectures 19
 - 4.3 CANbus network..... 20
 - 4.4 Physical layer 21
 - 4.5 Communication model 21
 - 4.6 CANopen higher layer protocol 21
 - 4.7 Time distribution 23
 - 4.7.1 Overview 23
 - 4.7.2 SYNC message and protocol 24
 - 4.7.3 Bit timing 24
 - 4.8 Redundancy management and monitoring 24
 - 4.8.1 Overview 24
 - 4.8.2 Node Monitoring via Node-Guarding or Heartbeat Messages 25
 - 4.8.3 Bus monitoring and reconfiguration management 26
 - 4.9 Connectors and pin assignments..... 27
 - 4.10 Minimal protocol set..... 27
- 5 Physical layer..... 28**
 - 5.1 Topology..... 28

5.1.1	Physical topology	28
5.1.2	Maximum bus length and drop length.....	30
5.1.3	Number of network devices.....	30
5.2	Medium.....	31
5.2.1	Cable requirements.....	31
5.2.2	Connectors	32
5.3	Transceiver characteristics	32
5.3.1	General.....	32
5.3.2	ISO 11898-2:2003 transceiver electrical characteristics	33
5.3.3	Resistance to electrical CAN Network faults.....	33
5.3.4	Transceiver isolation	38
5.3.5	Physical layer implementation based on RS-485 transceivers	38
5.3.6	Detailed implementation for RS-485 transceiver	39
5.4	Bit timing.....	39
5.4.1	Bit rate 1 Mbps.....	39
5.4.2	Other bit rates	39
5.4.3	Bit timing	39
5.5	Electromagnetic compatibility (EMC)	40
5.6	Data link layer.....	40
5.6.1	ISO 11898 compliance.....	40
5.6.2	Fault confinement	40
6	CANopen higher layer protocol.....	42
6.1	Service data objects	42
6.2	Process data objects	42
6.3	Synchronisation object.....	42
6.4	Emergency object.....	43
6.5	Network management objects.....	43
6.5.1	Module control services	43
6.5.2	Error control services	43
6.5.3	Bootup service	43
6.5.4	Node state diagram.....	43
6.6	Electronic data sheets	44
6.7	Device and application profiles	44
6.8	Object dictionary.....	45
6.9	Synchronous communications	45
6.10	COB-ID and NODE-ID assignment.....	45
7	Time distribution	47

7.1	Time objects	47
7.1.1	Time code formats	47
7.1.2	Spacecraft elapsed time objects.....	48
7.1.3	Spacecraft universal time coordinated objects	48
7.2	Time distribution and synchronization protocols.....	49
7.2.1	General	49
7.2.2	Time distribution protocol	49
7.2.3	High-resolution time distribution protocol.....	50
8	Redundancy management	52
8.1	General.....	52
8.2	Node internal bus redundancy architectures	52
8.2.1	General	52
8.2.2	Parallel bus access architecture.....	52
8.2.3	Selective bus access architecture	52
8.3	Bus monitoring and reconfiguration management.....	53
8.3.1	Bus redundancy management parameters.....	53
8.3.2	Start-up procedure	56
8.3.3	Bus monitoring protocol	57
9	Minimal implementation of the CANopen protocol for highly asymmetrical control applications	60
9.1	COB-ID assignment.....	60
9.2	Object dictionary	60
9.3	Minimal set CANopen Objects	60
9.4	Minimal Set Protocol.....	61
9.4.1	Definitions	61
9.4.2	Use of data bytes in application layer	62
9.4.3	Minimal Set Protocol data transmission.....	63
9.4.4	PDO transmit triggered by telemetry request.....	64
9.4.5	PDO mapping	64
9.4.6	Network management objects	65
9.4.7	Special function objects	65
9.4.8	Communication error object	66
9.4.9	NMT error control objects.....	66
9.4.10	Miscellaneous authorized objects.....	66
9.5	Free COB-ID.....	70
10	Connectors and pin assignments	73

10.1 Overview	73
10.2 Naming convention	73
10.3 Circular connectors.....	73
10.3.1 MIL-C D38999 configuration B: Dual CAN Network.....	73
10.3.2 MIL-C D38999 configuration D: Single CAN Network.....	74
10.4 Sub-miniature D connectors (9-pin D-sub).....	75
10.5 Sub-miniature D connectors (9-pin D-sub) – RS-485	76
11 CANopen standard applicability matrix.....	77
11.1 Introduction.....	77
Annex A (informative) Electrical connectivity.....	88
A.1 Transceivers	88
A.1.2 Detailed implementation for RS-485 transceiver	88
A.2 Example Implementation of a RS-485 physical layer	90
A.3 CAN Network Bus termination	93
A.4 Bus management and redundancy	93
A.4.1 Selective bus access architecture	93
A.4.2 Parallel bus access architecture.....	94
Bibliography.....	95
Figures	
Figure 3-1: Bit numbering convention	17
Figure 4-1: Relationship between ISO layering, ISO 11898, CiA 301 and ECSS CAN standard definitions	20
Figure 4-2: Example of minimal implementation topology.....	21
Figure 4-3: Format of heartbeat message.....	26
Figure 5-1: Linear multi-drop topology	28
Figure 5-2: Daisy chain topology.	29
Figure 7-1: Format for objects containing the SCET	48
Figure 7-2: Format for objects containing the Spacecraft UTC	49
Figure 8-1: Node start up procedure.....	56
Figure 8-2: Bus monitoring logic.....	58
Figure 8-3: Slave bus selection process, toggling mechanism.....	59
Figure 9-1: Unconfirmed Command exchange overview (example with PDO1).....	61
Figure 9-2: Telemetry request exchange overview (example with PDO2).....	62
Figure 10-1: Illustration of a 9-pin D-Sub connector.....	75
Figure A-1 : Principle of Isolated CAN Operation.....	88
Figure A-2 : RS-485 CAN physical interface for OBC/Bus Master	90

Figure A-3 : RS-485 CAN physical interface for nodes using single connector for redundant buses	91
Figure A-4 : RS-485 CAN physical interface nodes using dual connector for redundant buses	91
Figure A-5 : Split (left) and standard (right) Termination schemes.....	93
Figure A-6 : Selective bus access architecture	94
Figure A-7 : Parallel bus access architecture.....	94

Tables

Table 5-1: CAN levels in ISO 11898-2:2003	33
Table 5-2 – CAN failure modes and recommended FDIR actions.....	36
Table 8-1: BUS redundancy management parameters for slaves.....	54
Table 8-2: BUS redundancy management parameters for master	55
Table 9-1: Peer-to-Peer objects of the minimal set	61
Table 9-2: Broadcast objects of the minimal set	61
Table 9-3: PDO Communication Object description:.....	63
Table 9-4: PDO Communication Entry Description:	63
Table 9-5 PDO Communication Object description:.....	64
Table 9-6: PDO Communication Entry Description:	64
Table 9-7 : SYNC Message Object description:.....	65
Table 9-8: SYNC Message Entry Description:	65
Table 9-9 SYNC used with NMT master Object description:.....	66
Table 9-10 SYNC used with NMT master Entry Description:	66
Table 9-11: CANopen Object dictionary Data Types	67
Table 9-12: Authorized and Forbidden Object Dictionary Entries of the Communication profile	68
Table 9-13 : COB ID -Predefined connection set.....	71
Table 10-1 : Signal terminology	73
Table 10-2: Pin function for MIL-C D38999 configuration B	74
Table 10-3: Pin function for MIL-C D38999 configuration D	74
Table 10-4: Pin function for sub D-type with CAN Network.....	75
Table 10-5: Pin function for sub D-type with RS-485 CAN Network.....	76
Table 11-1: DiA 301 (former CIA DS301) applicability matrix.....	78
Table A-1 : Logic Table, RS-485 Driver implementation	92
Table A-2 : Logic Table, RS-485 Receiver implementation.....	92
Table A-3 : Component item values.....	92