

ISO 12334:2000-02 (E)

Aerospace - Hydraulic, pressure-compensated, variable delivery pumps - General requirements for 35000 kPa systems

Contents		Page
Foreword		vi
1	Scope	1
2	Normative references	1
3	Functional requirements	2
3.1	Hydraulic fluid	2
3.2	Rated discharge pressure	2
3.3	Maximum full-flow pressure	3
3.4	Inlet pressure	3
3.4.1	Rated inlet pressure	3
3.4.2	Cavitation pressure	3
3.4.3	Minimum inlet pressure	3
3.5	Case drain pressure	3
3.5.1	Rated case-drain pressure	3
3.5.2	Case proof-pressure	3
3.6	Case drain flow	3
3.7	Rated temperature	4
3.8	Maximum displacement	4
3.9	Rated delivery	4
3.10	Rated speed	4
3.11	Endurance	6
3.12	Torque	6
3.13	Efficiency	6
3.14	Discharge pressure pulsations	6
3.15	Variable delivery control	6
3.15.1	General	6
3.15.2	Response time	7
3.15.3	Stability	7
3.16	Maximum transient pressure	8
3.17	Depressurization	8
3.18	Balance	8
3.19	Adjustment	9
3.20	Safety wire sealing	9
3.21	Directionally critical components	9
3.22	Environmental requirements	9
3.23	Installation requirements	9
3.23.1	Dimensions	9
3.23.2	Mass	10
3.23.3	Mounting	10
3.23.4	Drive coupling	10
3.23.5	Ports	10
3.24	Detail requirements	11
3.24.1	Material	11
3.24.2	Metals	11
3.24.3	Corrosion protection	11
3.24.4	Castings	12
3.24.5	Seals	12
3.24.6	Identification marking	12
3.24.7	Design and construction	13

3.25	Maintainability	13
3.25.1	Maintenance concept	13
3.25.2	Useful life and storage conditions	13
3.26	Reliability	13
3.26.1	Equipment compliance	13
3.26.2	Requirements	13
4	Quality assurance provisions	14
4.1	Responsibility for inspection	14
4.2	Classification of tests	14
5	Qualification tests	14
5.1	General	14
5.2	Qualification procedure	14
5.2.1	Detail specification	14
5.2.2	Qualification by analogy	14
5.2.3	Pump qualification test report	14
5.3	Samples and programme of qualification tests	15
5.4	General conditions for qualification tests	15
5.5	Acceptance tests	16
5.6	Dimensional check	16
5.7	Proof-pressure and overspeed test	16
5.8	Calibration	16
5.8.1	Pump inlet pressurized	16
5.8.2	Flow rate and driving torque values	16
5.8.3	Minimum operating speed	16
5.9	Maximum pressure, response time and pressure pulsation tests	16
5.9.1	General	16
5.9.2	System impedance	17
5.9.3	Maximum pressure test	17
5.9.4	Determination of response time	17
5.9.5	Pressure pulsation test	18
5.10	Heat rejection test	18
5.10.1	Principle	18
5.10.2	Determination of heat rejection	18
5.11	Vibration tests	18
5.11.1	Mounting of the test pump	18
5.11.2	Pump operating during vibration tests	19
5.11.3	Resonant frequency vibration test	19
5.11.4	Cyclic frequency vibration test	19
5.11.5	Other vibration tests	19
5.12	Low temperature test	19
5.13	Endurance testing	20
5.13.1	Test programme	20
5.13.2	Filtration for normal endurance tests	20
5.13.3	Filter check	20
5.13.4	Calibration	20
5.13.5	Start-stop cycles	20
5.13.6	Pump case pressure cycles	23
5.13.7	Air ingestion	23
5.13.8	Thermal cycles	23
5.13.9	Thermal shock	24
5.13.10	Hydraulic fluid	24
5.13.11	Failure of parts	24
5.14	Cavitation test	24
5.15	Drive coupling shear test	24
5.16	Teardown inspection	24
6	Acceptance tests	25
6.1	General	25
6.2	Examination of the product	25
6.3	Test programme	25

6.3.1	Break-in run	25
6.3.2	Proof-pressure and overspeed tests	25
6.3.3	Teardown inspection examination	26
6.3.4	Break-in run	26
6.3.5	Functional tests	26
6.3.6	External leakage test	26
6.3.7	Pressure control test	27
6.3.8	Calibration	27
6.3.9	Filter patch test	27
7	Storage and packaging	28