

## Table of contents

---

<b>European Foreword</b> .....	<b>7</b>
<b>1 Scope</b> .....	<b>8</b>
<b>2 Normative references</b> .....	<b>9</b>
<b>3 Terms, definitions and abbreviated terms</b> .....	<b>10</b>
3.1 Terms from other standards.....	10
3.2 Terms specific to the present standard .....	10
3.3 Abbreviated terms.....	20
3.4 Conventions.....	21
3.4.1 Numbers .....	21
3.4.2 Differential signals.....	21
3.4.3 Order of sending bits in symbols .....	21
3.4.4 Graphical representation of packets.....	22
3.4.5 State diagram notation .....	22
3.4.6 UML diagram notation.....	23
3.5 Nomenclature .....	24
<b>4 Overview of SpaceWire</b> .....	<b>25</b>
4.1 Introduction.....	25
4.2 SpaceWire Spacecraft Data-Handling Network.....	25
4.2.1 The Rationale for SpaceWire .....	25
4.2.2 Example SpaceWire Application .....	26
4.2.3 How SpaceWire Works .....	28
<b>5 Requirements</b> .....	<b>33</b>
5.1 Overview .....	33
5.2 Protocol stack and interface architecture .....	33
5.2.1 Protocol stack .....	33
5.2.2 Network layer .....	34
5.2.3 Data Link layer .....	34
5.2.4 Encoding layer .....	35
5.2.5 Physical layer.....	35

5.2.6	Management Information Base .....	36
5.2.7	Service interfaces .....	36
5.2.8	SpaceWire Port architecture .....	36
5.3	Physical layer .....	37
5.3.1	Introduction .....	37
5.3.2	Cables.....	38
5.3.3	Connectors .....	41
5.3.4	Cable assemblies.....	45
5.3.5	PCB tracks.....	50
5.3.6	Line drivers and receivers .....	51
5.3.7	Data-Strobe skew .....	59
5.3.8	Physical layer management parameters .....	62
5.4	Encoding layer.....	63
5.4.1	Introduction .....	63
5.4.2	Serialisation and de-serialisation.....	63
5.4.3	Character and control code encoding.....	63
5.4.4	Data strobe encoding and decoding.....	66
5.4.5	First Null.....	68
5.4.6	Null detection .....	68
5.4.7	Parity error .....	69
5.4.8	Disconnect.....	69
5.4.9	ESC error.....	69
5.4.10	Data signalling rate .....	70
5.4.11	Encoding layer management parameters.....	71
5.5	Data link layer.....	71
5.5.1	Introduction .....	71
5.5.2	Data link layer interfaces.....	71
5.5.3	Data link layer management interface .....	72
5.5.4	Flow control.....	73
5.5.5	Flow control errors .....	74
5.5.6	Sending priority .....	75
5.5.7	Link initialisation behaviour .....	75
5.5.8	Link error recovery .....	80
5.5.9	Accepting broadcast codes for sending.....	82
5.6	SpaceWire network layer.....	82
5.6.1	Introduction .....	82
5.6.2	SpaceWire packets .....	83

5.6.3	Broadcast codes .....	83
5.6.4	SpaceWire time-codes .....	84
5.6.5	SpaceWire distributed interrupts .....	87
5.6.6	SpaceWire nodes.....	94
5.6.7	SpaceWire node management parameters .....	96
5.6.8	SpaceWire routing.....	96
5.6.9	SpaceWire routing switch management parameters .....	104
5.6.10	SpaceWire network.....	104
5.7	SpaceWire management information base .....	106
5.7.1	Introduction .....	106
5.7.2	General .....	106
5.7.3	Physical layer management parameters .....	106
5.7.4	Encoding layer management parameters.....	106
5.7.5	Data link layer management parameters.....	106
5.7.6	Network layer management parameters.....	106
<b>6</b>	<b>Service interfaces .....</b>	<b>107</b>
6.1	Network layer service interface .....	107
6.1.1	Packet service interface .....	107
6.1.2	Time-code service interface .....	108
6.1.3	Distributed interrupt service interface .....	109
6.2	Data link layer service interface .....	111
6.2.1	N-Char service interface.....	111
6.2.2	Broadcast code service interface .....	113
6.3	Encoding layer service interface .....	114
6.3.1	Encoding service interface .....	114
6.3.2	Decoding service interface.....	115
6.4	Physical layer service interface.....	117
6.4.1	Line transmit service interface.....	117
6.4.2	Line receive service interface.....	118
6.5	Management information base service interface.....	119
6.5.1	Set parameter service interface.....	119
6.5.2	Get parameter service interface .....	119
	<b>Annex A (informative) Technical Changes.....</b>	<b>121</b>
	<b>Bibliography.....</b>	<b>123</b>

## Figures

Figure 3-1: Convention for first bit to be sent .....	21
Figure 3-2: Graphical packet notation.....	22
Figure 3-3: State diagram style.....	22
Figure 3-4: UML notation.....	23
Figure 4-1: Example SpaceWire Architecture without redundancy .....	27
Figure 4-2: SpaceWire Packet Format.....	29
Figure 4-3: Path Addressing .....	31
Figure 4-4 Logical Addressing .....	32
Figure 5-1: SpaceWire protocol stack.....	34
Figure 5-2: SpaceWire port architecture .....	37
Figure 5-3: SpaceWire connector contact identification .....	44
Figure 5-4: SpaceWire cable assembly Type A .....	47
Figure 5-5: SpaceWire cable assembly Type AL .....	49
Figure 5-6: SpaceWire LVDS .....	53
Figure 5-7: LVDS line driver output signals.....	54
Figure 5-8: LVDS line driver differential output signal .....	56
Figure 5-9: Physical layer components.....	59
Figure 5-10: Skew and jitter.....	62
Figure 5-11: Data character encoding .....	64
Figure 5-12: Control character encoding .....	65
Figure 5-13: Null control code encoding .....	65
Figure 5-14: Broadcast code encoding .....	66
Figure 5-15: Parity coverage .....	66
Figure 5-16: Data-Strobe (DS) encoding .....	67
Figure 5-17: Data and strobe signals for first Null.....	68
Figure 5-18: Null detection sequence .....	69
Figure 5-19: Link initialisation behaviour.....	76
Figure 5-20: Link error recovery behaviour .....	81
Figure 5-21: SpaceWire packet format .....	83
Figure 5-22: Specialisations and relationships of a SpaceWire broadcast code .....	84
Figure 5-23 Network layer time-code.....	85
Figure 5-24: Network layer interrupt .....	88
Figure 5-25: Network layer interrupt acknowledgement code .....	89
Figure 5-26: Components and specialisations of a SpaceWire node .....	95
Figure 5-27: Components of a SpaceWire routing switch .....	97
Figure 5-28: Components of a SpaceWire network .....	105

## Tables

Table 5-1: Constants for a SpW cable using 28 AWG differential pairs .....	39
Table 5-2: Insertion loss values 28AWG SpW cable.....	40
Table 5-3: Constants for a SpaceWire cable using 26 AWG differential pairs.....	40
Table 5-4: Insertion loss values for 26 AWG SpaceWire cable.....	40
Table 5-5: Cable PSNEXT specification .....	41
Table 5-6: Cable PSELFEXT specification .....	41
Table 5-7: Connector contact identification.....	43
Table 5-8: Cable assembly Type A signal wire connections .....	47
Table 5-9: Cable assembly Type AL signal wire connections .....	49
Table 5-10 Example calculation of maximum bit rate.....	61
Table 5-11: Address function.....	99