

Table of contents

| | |
|--|-----------|
| European Forward | 9 |
| Introduction | 11 |
| 1 Scope | 13 |
| 2 Normative references | 14 |
| 3 Terms, definitions and abbreviated terms | 15 |
| 3.1 Terms defined in other standards | 15 |
| 3.2 Terms specific to the present standard | 15 |
| 3.3 Abbreviated terms..... | 18 |
| 3.4 Nomenclature | 19 |
| 4 Overview | 21 |
| 4.1 Plasma interaction effects..... | 21 |
| 4.1.1 Presentation..... | 21 |
| 4.1.2 Most common engineering concerns..... | 21 |
| 4.1.3 Overview of physical mechanisms | 22 |
| 4.2 Relationship with other standards | 24 |
| 5 Protection programme | 26 |
| 6 Surface material requirements | 27 |
| 6.1 Overview | 27 |
| 6.1.1 Description and applicability..... | 27 |
| 6.1.2 Purpose common to all spacecraft | 28 |
| 6.1.3 A special case: scientific spacecraft with plasma measurement instruments | 28 |
| 6.2 General requirements | 28 |
| 6.2.1 Maximum permitted voltage | 28 |
| 6.2.2 Maximum resistivity..... | 29 |
| 6.3 Electrical continuity, including surfaces and structural and mechanical parts..... | 29 |
| 6.3.1 Grounding of surface metallic parts..... | 29 |
| 6.3.2 Exceptions | 30 |

| | | |
|-----------|--|-----------|
| 6.3.3 | Electrical continuity for surface materials | 31 |
| 6.4 | Surface charging analysis..... | 35 |
| 6.5 | Deliberate potentials | 35 |
| 6.6 | Testing of materials and assemblies..... | 35 |
| 6.6.1 | General..... | 35 |
| 6.6.2 | Material characterization tests..... | 37 |
| 6.6.3 | Material and assembly qualification..... | 37 |
| 6.7 | Scientific spacecraft with plasma measurement instruments | 38 |
| 6.8 | Verification..... | 38 |
| 6.8.1 | Grounding | 38 |
| 6.8.2 | Material selection | 39 |
| 6.8.3 | Environmental effects..... | 39 |
| 6.8.4 | Computer modelling | 39 |
| 6.9 | Triggering of ESD | 40 |
| 7 | Secondary arc requirements | 41 |
| 7.1 | Description and applicability | 41 |
| 7.2 | Solar arrays | 42 |
| 7.2.1 | Overview..... | 42 |
| 7.2.2 | General requirement | 42 |
| 7.2.3 | Testing of solar arrays..... | 43 |
| 7.3 | Other exposed parts of the power system including solar array drive mechanisms | 47 |
| 8 | High voltage system requirements | 48 |
| 8.1 | Description | 48 |
| 8.2 | Requirements | 48 |
| 8.3 | Validation..... | 48 |
| 9 | Internal parts and materials requirements | 49 |
| 9.1 | Description | 49 |
| 9.2 | General..... | 49 |
| 9.2.1 | Internal charging and discharge effects..... | 49 |
| 9.2.2 | Grounding and connectivity..... | 49 |
| 9.2.3 | Dielectric electric fields and voltages..... | 50 |
| 9.3 | Validation..... | 51 |
| 10 | Tether requirements | 55 |
| 10.1 | Description | 55 |
| 10.2 | General..... | 55 |

| | | |
|----------------|---|-----------|
| 10.2.1 | Hazards arising on tethered spacecraft due to voltages generated by conductive tethers | 55 |
| 10.2.2 | Current collection and resulting problems | 55 |
| 10.2.3 | Hazards arising from high currents flowing through the tether and spacecraft structures..... | 56 |
| 10.2.4 | Continuity of insulation..... | 56 |
| 10.2.5 | Hazards from undesired conductive paths | 56 |
| 10.2.6 | Hazards from electro-dynamic tether oscillations | 56 |
| 10.2.7 | Other effects | 56 |
| 10.3 | Validation..... | 57 |
| 11 | Electric propulsion requirements | 58 |
| 11.1 | Overview | 58 |
| 11.1.1 | Description..... | 58 |
| 11.1.2 | Coverage of the requirements..... | 58 |
| 11.2 | General..... | 60 |
| 11.2.1 | Spacecraft neutralization..... | 60 |
| 11.2.2 | Beam neutralization | 61 |
| 11.2.3 | Contamination..... | 62 |
| 11.2.4 | Sputtering | 62 |
| 11.2.5 | Neutral gas effects | 62 |
| 11.3 | Validation..... | 63 |
| 11.3.1 | Ground testing | 63 |
| 11.3.2 | Computer modelling characteristics | 63 |
| 11.3.3 | In-flight monitoring..... | 63 |
| 11.3.4 | Sputtering | 63 |
| 11.3.5 | Neutral gas effects | 64 |
| Annex A | (normative) Electrical hazard mitigation plan - DRD..... | 65 |
| A.1 | DRD identification..... | 65 |
| A.1.1 | Requirement identification and source document..... | 65 |
| A.1.2 | Purpose and objective..... | 65 |
| A.2 | Expected response..... | 65 |
| A.2.1 | Scope and content | 65 |
| A.2.2 | Special remarks | 66 |
| Annex B | (informative) Tailoring guidelines..... | 67 |
| B.1 | Overview | 67 |
| B.2 | LEO..... | 67 |
| B.2.1 | General..... | 67 |

| | | |
|--|---|-----------|
| B.2.2 | LEO orbits with high inclination | 68 |
| B.3 | MEO and GEO orbits..... | 68 |
| B.4 | Spacecraft with onboard plasma detectors | 68 |
| B.5 | Tethered spacecraft..... | 69 |
| B.6 | Active spacecraft | 69 |
| B.7 | Solar Wind..... | 69 |
| B.8 | Other planetary magnetospheres..... | 69 |
| Annex C (informative) Physical background to the requirements | | 70 |
| C.1 | Introduction..... | 70 |
| C.2 | Definition of symbols..... | 70 |
| C.3 | Electrostatic sheaths..... | 70 |
| C.3.1 | Introduction | 70 |
| C.3.2 | The electrostatic potential | 71 |
| C.3.3 | The Debye length..... | 71 |
| C.3.4 | Presheath | 72 |
| C.3.5 | Models of current through the sheath..... | 73 |
| C.3.6 | Thin sheath – space-charge-limited model..... | 73 |
| C.3.7 | Thick sheath – orbit motion limited (OML) model | 74 |
| C.3.8 | General case..... | 75 |
| C.3.9 | Magnetic field modification of charging currents..... | 75 |
| C.4 | Current collection and grounding to the plasma | 75 |
| C.5 | External surface charging | 76 |
| C.5.1 | Definition..... | 76 |
| C.5.2 | Processes | 76 |
| C.5.3 | Effects..... | 77 |
| C.5.4 | Surface emission processes | 77 |
| C.5.5 | Floating potential..... | 78 |
| C.5.6 | Conductivity and resistivity | 79 |
| C.5.7 | Time scales..... | 81 |
| C.6 | Spacecraft motion effects | 81 |
| C.6.1 | Wakes..... | 81 |
| C.6.2 | Motion across the magnetic field | 84 |
| C.7 | Induced plasmas | 85 |
| C.7.1 | Definition..... | 85 |
| C.7.2 | Electric propulsion thrusters..... | 86 |
| C.7.3 | Induced plasma characteristics | 86 |
| C.7.4 | Charge-exchange effects | 87 |

| | | |
|------------------------------|--|------------|
| C.7.5 | Neutral particle effects | 88 |
| C.7.6 | Effect on floating potential | 88 |
| C.8 | Internal and deep-dielectric charging | 88 |
| C.8.1 | Definition | 88 |
| C.8.2 | Relationship to surface charging | 89 |
| C.8.3 | Charge deposition | 90 |
| C.8.4 | Material conductivity | 90 |
| C.8.5 | Time dependence | 93 |
| C.8.6 | Geometric considerations | 93 |
| C.8.7 | Isolated internal conductors | 94 |
| C.8.8 | Electric field sensitive systems | 94 |
| C.9 | Discharges and transients | 95 |
| C.9.1 | General definition | 95 |
| C.9.2 | Review of the process | 95 |
| C.9.3 | Dielectric material discharge | 96 |
| C.9.4 | Metallic discharge | 98 |
| C.9.5 | Internal dielectric discharge | 99 |
| C.9.6 | Secondary powered discharge | 100 |
| C.9.7 | Discharge thresholds | 100 |
| Annex D (informative) | Charging simulation | 102 |
| D.1 | Surface charging codes | 102 |
| D.1.1 | Introduction | 102 |
| D.2 | Internal charging codes | 104 |
| D.2.1 | DICTAT | 104 |
| D.2.2 | ESADDC | 104 |
| D.2.3 | GEANT-4 | 105 |
| D.2.4 | NOVICE | 105 |
| D.3 | Environment model for internal charging | 105 |
| D.3.1 | FLUMIC | 105 |
| D.3.2 | Worst case GEO spectrum | 105 |
| Annex E (informative) | Testing and measurement. | 106 |
| E.1 | Definition of symbols | 106 |
| E.2 | Solar array testing | 106 |
| E.2.1 | Solar cell sample | 106 |
| E.2.2 | Pre-testing of the solar array simulator (SAS) | 107 |
| E.2.3 | Solar array test procedure | 109 |
| E.2.4 | Other elements | 113 |

| | | |
|-------|---|-----|
| E.2.5 | The solar panel simulation device | 114 |
| E.3 | Measurement of conductivity and resistivity | 116 |
| E.3.1 | Determination of intrinsic bulk conductivity by direct measurement | 116 |
| E.3.2 | Determination of radiation-induced conductivity coefficients by direct measurement | 117 |
| E.3.3 | Determination of conductivity and radiation-induced conductivity by electron irradiation..... | 118 |
| E.3.4 | The ASTM method for measurement of surface resistivity and its adaptation for space used materials..... | 118 |

References 120

Bibliography..... 124

Figures

| | | |
|---------------|---|-----|
| Figure 6-1: | Applicability of electrical continuity requirements | 32 |
| Figure 7-1: | Solar array test set-up | 45 |
| Figure C-1 : | Schematic diagram of potential variation through sheath and pre-sheath. | 72 |
| Figure C-2 : | Example secondary yield curve | 78 |
| Figure C-3 : | Schematic diagram of wake structure around an object at relative motion with respect to a plasma..... | 82 |
| Figure C-4 : | Schematic diagram of void region | 83 |
| Figure C-5 : | Schematic diagram of internal charging in a planar dielectric..... | 89 |
| Figure C-6 : | Dielectric discharge mechanism. | 97 |
| Figure C-7 : | Shape of the current in relation to discharge starting point..... | 97 |
| Figure C-8 : | Example of discharge on pierced aluminized Teflon® irradiated by electrons with energies ranging from 0 to 220 keV. | 98 |
| Figure C-9 : | Schematic diagram of discharge at a triple point in the inverted voltage gradient configuration with potential contours indicated by colour scale. | 99 |
| Figure E-1 : | Photograph of solar cells sample – Front face & Rear face (Stentor Sample. Picture from Denis Payan - CNES®)..... | 107 |
| Figure E-2 : | Schematic diagram of power supply test circuit..... | 108 |
| Figure E-3 : | Example of a measured power source switch response..... | 108 |
| Figure E-4 : | Example solar array simulator..... | 109 |
| Figure E-5 : | Absolute capacitance of the satellite | 110 |
| Figure E-6 : | Junction capacitance of a cell versus to voltage..... | 112 |
| Figure E-7 : | The shortened solar array sample and the missing capacitances | 113 |
| Figure E-8 : | Discharging circuit oscillations | 114 |
| Figure E-9 : | Effect of an added resistance in the discharging circuit (SAS + resistance) | 114 |
| Figure E-10 : | Setup simulating the satellite including flashover current | 115 |

| | |
|---|-----|
| Figure E-11 : Basic arrangement of apparatus for measuring dielectric conductivity in planar samples..... | 116 |
| Figure E-12 : Arrangement for measuring cable dielectric conductivity and cross-section through co-axial cable..... | 116 |
| Figure E-13 : Arrangement for carrying out conductivity tests on planar samples under irradiation | 118 |
| Figure E-14 : Basic experimental set up for surface conductivity | 119 |

Tables

| | |
|--|----|
| Table 4-1: List of electrostatic and other plasma interaction effects on space systems..... | 23 |
| Table 7-1: Tested voltage-current combinations..... | 42 |
| Table 7-2: Typical inductance per unit length for cables | 46 |
| Table C-1 : Parameters in different regions in space | 72 |
| Table C-2 : Typical plasma parameters for LEO and GEO | 83 |
| Table C-3 : Plasma conditions on exit plane of several electric propulsion thrusters | 87 |
| Table C-4 : Emission versus backflow current magnitudes for several electric propulsion thrusters..... | 87 |
| Table C-5 : Value of E_a for several materials | 91 |