

# DIN EN 16603-50-11:2020-11 (E)

Space engineering - SpaceFibre - Very high-speed serial link; English version EN 16603-50-11:2020

---

Contents	Page
<b>European Foreword</b> .....	<b>9</b>
<b>1 Scope</b> .....	<b>10</b>
<b>2 Normative references</b> .....	<b>11</b>
<b>3 Terms, definitions and abbreviated terms</b> .....	<b>13</b>
3.1 Terms defined in other standards .....	13
3.2 Terms specific to the present standard .....	13
3.3 Abbreviated terms.....	26
3.4 Conventions.....	29
3.4.1 Numbers .....	29
3.4.2 Multiplication .....	29
3.4.3 Differential signals.....	29
3.4.4 Order of sending bits in symbols .....	29
3.4.5 Graphical representation of packets.....	30
3.4.6 State diagram notation .....	30
3.4.7 UML diagram notation.....	31
3.4.8 D/K notation for 8B/10B characters .....	32
3.5 Nomenclature .....	32
<b>4 Principles</b> .....	<b>34</b>
4.1 SpaceFibre purpose .....	34
4.2 SpaceFibre overview .....	35
<b>5 Requirements</b> .....	<b>37</b>
5.1 Overview .....	37
5.2 Protocol stack and interface architecture .....	37
5.2.1 General.....	37
5.2.2 Network layer .....	39
5.2.3 Data Link layer .....	39
5.2.4 Multi-Lane layer .....	40
5.2.5 Lane layer .....	40
5.2.6 Physical layer.....	41

5.2.7	Management Information Base .....	41
5.3	Formats .....	41
5.3.1	Control words and encoding/decoding .....	41
5.3.2	8B/10B encode/decode .....	42
5.3.3	Lane control words .....	44
5.3.4	Multi-Lane control words .....	51
5.3.5	Data Link control words .....	53
5.3.6	Receive error indication control word (RXERR) .....	62
5.3.7	Characters .....	63
5.3.8	Frames .....	66
5.3.9	Packets .....	70
5.3.10	Control word and frame precedence .....	70
5.3.11	K-code summary .....	73
5.3.12	Control word symbol summary .....	73
5.4	Physical layer .....	74
5.4.1	Physical layer responsibilities .....	74
5.4.2	Serialisation .....	75
5.4.3	Electrical physical layer .....	77
5.4.4	Electrical medium .....	88
5.4.5	Fibre optic physical layer .....	97
5.4.6	Fibre optic medium .....	103
5.5	Lane layer .....	112
5.5.1	Lane layer responsibilities .....	112
5.5.2	Lane initialisation and standby management .....	114
5.5.3	Data signalling rate compensation .....	126
5.5.4	IDLE words .....	126
5.5.5	Parallel loopback .....	127
5.5.6	Symbol synchronisation .....	127
5.5.7	Word synchronisation .....	127
5.5.8	Receive synchronisation state machine .....	129
5.6	Multi-Lane layer .....	131
5.6.1	Multi-Lane layer responsibilities .....	131
5.6.2	Multi-Lane link .....	132
5.6.3	Multi-Lane bypass .....	133
5.6.4	Multi-Lane distribution .....	133
5.6.5	Multi-Lane concentration .....	137
5.6.6	Lane Alignment .....	137

5.6.7	Alignment state diagram .....	141
5.6.8	Asymmetric links .....	144
5.6.9	Initialisation of unidirectional lanes .....	145
5.6.10	Hot redundant lanes.....	146
5.7	Data Link layer.....	149
5.7.1	Data Link layer responsibilities .....	149
5.7.2	Virtual channels .....	151
5.7.3	Flow control.....	153
5.7.4	Medium access controller.....	155
5.7.5	Broadcast flow control.....	163
5.7.6	Framing.....	164
5.7.7	Error recovery .....	177
5.7.8	Data word identification state machine .....	184
5.7.9	Link Reset state machine .....	189
5.7.10	Link reset .....	192
5.8	Network layer.....	194
5.8.1	Network layer responsibilities .....	194
5.8.2	SpaceFibre network .....	195
5.8.3	Virtual networks .....	196
5.8.4	Links .....	199
5.8.5	Packet format.....	199
5.8.6	Sending a packet .....	200
5.8.7	Receiving a packet.....	200
5.8.8	Routing switch.....	201
5.8.9	Packet addressing.....	207
5.8.10	Group adaptive routing.....	209
5.8.11	Packet multicast.....	209
5.8.12	Broadcast messages.....	210
5.8.13	SpaceFibre nodes .....	212
5.8.14	SpaceFibre units .....	213
5.9	Management Information Base .....	214
5.9.1	Management Information Base responsibilities .....	214
5.9.2	Network management.....	214
5.9.3	Configuration parameters.....	215
5.9.4	Status parameters.....	219
<b>6</b>	<b>Service interfaces .....</b>	<b>221</b>
6.1	Overview .....	221

6.2	Network layer service interface .....	221
6.2.1	Network layer services .....	221
6.2.2	Packet Transfer service .....	221
6.2.3	Broadcast message service .....	223
6.3	Data Link layer service interface .....	224
6.3.1	Data Link layer services .....	224
6.3.2	Virtual Channel service .....	224
6.3.3	Broadcast message service .....	225
6.3.4	Schedule synchronisation service .....	226
6.4	Physical layer service interfaces .....	227
6.4.1	Physical layer services .....	227
6.4.2	Transfer symbols service .....	227
6.4.3	Control service .....	228
6.5	Management Information Base service interface .....	230
6.5.1	Management Information Base services .....	230
6.5.2	Link Management service .....	230

**Bibliography.....232**

**Figures**

Figure 3-1: Convention for first bit to be sent .....	29
Figure 3-2: Graphical packet notation .....	30
Figure 3-3: State diagram style .....	30
Figure 3-4: UML notation .....	31
Figure 3-5: D/K notation for 8B/10B characters .....	32
Figure 4-1: Overview of SpaceFibre protocol stack .....	35
Figure 5-1: SpaceFibre protocol stack - single-lane .....	38
Figure 5-2: SpaceFibre protocol stack - multi-lane .....	39
Figure 5-3: Fills at the end of packets .....	65
Figure 5-4: Fills at the start and end of a packet .....	66
Figure 5-5: Data frame format for a single lane .....	66
Figure 5-6: Idle frame format .....	67
Figure 5-7: Broadcast frame format .....	68
Figure 5-8: Interfaces to the Physical layer .....	75
Figure 5-9: One direction of electrical Physical layer, showing series capacitors, discharge resistors, and different grounds .....	77
Figure 5-10: Serial output signals .....	79
Figure 5-11: Serial output test circuit .....	80

Figure 5-12: Serial eye pattern mask.....	80
Figure 5-13: Serial input signals .....	86
Figure 5-14: Type-A electrical flight cable assembly .....	89
Figure 5-15: Type-A electrical flight connector saver .....	90
Figure 5-16: Type-C electrical EGSE cable assembly .....	93
Figure 5-17: Type-C electrical EGSE to flight adaptor cable assembly .....	94
Figure 5-18: One direction of fibre optic Physical layer, showing fibre optic transmitter, receiver, connectors and cable.....	97
Figure 5-19: One direction of active optical cable type of fibre optic Physical layer.....	97
Figure 5-20: Electro-optical eye pattern for 1 Gbit/s to 5 Gbit/s transmitters .....	99
Figure 5-21: Electro-optical eye pattern for 1 Gbit/s to 10 Gbit/s transmitters .....	100
Figure 5-22: SpaceFibre lane comprising two Type-A fibre optic flight cable assemblies, one for each direction.....	105
Figure 5-23: Type-B fibre optic flight cable assembly with one lane.....	107
Figure 5-24: Type-B fibre optic flight cable assembly with several lanes .....	108
Figure 5-25: Type-B fibre optic flight cable assembly for an asymmetric link .....	108
Figure 5-26: Type-C flight active optical cable assembly .....	111
Figure 5-27: Interfaces to the Lane layer for a single lane link.....	113
Figure 5-28: Interfaces to the Lane layer for a multi-lane link.....	114
Figure 5-29: Lane initialisation state machine.....	115
Figure 5-30: Receive synchronisation state machine.....	129
Figure 5-31: Interfaces to Multi-Lane layer .....	132
Figure 5-32: Multi-Lane link with different number of lanes at each end .....	133
Figure 5-33: Words forming a row across a multi-lane link .....	134
Figure 5-34: Spreading data across a multi-lane link .....	135
Figure 5-35: PAD control words in a multi-lane link .....	135
Figure 5-36: Row alignment across a multi-lane link.....	140
Figure 5-37: Alignment state machine .....	141
Figure 5-38: Multi-Lane link incorporating some unidirectional lanes .....	144
Figure 5-39: Interfaces to the Data Link layer for a single lane link.....	150
Figure 5-40: Interfaces to the Data Link layer for a multi-lane link .....	150
Figure 5-41: Scrambler / de-scrambler .....	165
Figure 5-42: Example of scrambling of a short data frame.....	166
Figure 5-43: Effect of scrambling on an idle frame.....	167
Figure 5-44: Examples of CRC calculation for a short data frame .....	172
Figure 5-45: Illustration of bit ordering during 16-bit CRC calculation .....	172
Figure 5-46: Examples of CRC calculation for a broadcast frame and FCT.....	175
Figure 5-47: Illustration of bit ordering during 8-bit CRC calculation .....	176

Figure 5-48: Receive Error state machine .....	182
Figure 5-49: Data Word Identification state machine .....	185
Figure 5-50: Link Reset state machine .....	190
Figure 5-51: Interfaces to the Network layer .....	194
Figure 5-52: Components of a SpaceFibre network.....	195
Figure 5-53: Relationships of a SpaceFibre virtual network .....	197
Figure 5-54: SpaceFibre packet format .....	199
Figure 5-55: Components of a SpaceFibre routing switch .....	202
Figure 5-56: Components and specialisations of a SpaceFibre node .....	212
Figure 5-57: Components and specialisations of a SpaceFibre unit .....	214

## Tables

Table 5-1: 5B/6B encoding .....	43
Table 5-2: 3B/4B encoding .....	44
Table 5-3: Lane control words .....	44
Table 5-4: Multi-Lane control words.....	51
Table 5-5: Data framing control words.....	53
Table 5-6: Flow control word .....	58
Table 5-7: Error recovery control words.....	60
Table 5-8: Receive error indication control word.....	63
Table 5-9: SpaceFibre N-Char Symbols .....	64
Table 5-10: Fill control character symbol .....	64
Table 5-11: Meaning of K-codes.....	73
Table 5-12: Meaning of control word symbols .....	73
Table 5-13: Serial output interface.....	77
Table 5-14: Serial eye pattern mask intervals 1 Gbit/s to 3,125 Gbit/s.....	81
Table 5-15: Serial eye pattern mask intervals above 3,125 Gbit/s to 6,25 Gbit/s .....	81
Table 5-16: Coefficient $\alpha$ for different values of BER .....	82
Table 5-17: Driver and receiver characteristics 1 Gbit/s to 3,125 Gbit/s.....	83
Table 5-18: Driver and receiver characteristics above 3,125 Gbit/s to 6,25 Gbit/s .....	84
Table 5-19: Serial input interface .....	85
Table 5-20: Type-A electrical flight cable assembly connector contact terminations .....	89
Table 5-21: Type-A electrical flight connector saver connector contact terminations .....	89
Table 5-22: Type-B electrical flight cable assembly connector contact terminations .....	92
Table 5-23: Type-C electrical EGSE cable assembly connector contact terminations .....	93
Table 5-24: Type-C electrical EGSE to flight adaptor cable assembly connector contact terminations .....	94
Table 5-25: Type-D electrical EGSE cable assembly connector contact terminations .....	96

Table 5-26: Electro-optical characteristics for 1 Gbit/s to 5 Gbit/s transmitters .....	100
Table 5-27: Electro-optical characteristics for 1 Gbit/s to 10 Gbit/s transmitters .....	101
Table 5-28: Electro-optical characteristics for 1 Gbit/s to 5 Gbit/s receivers.....	102
Table 5-29: Electro-optical characteristics for 1 Gbit/s to 10 Gbit/s receivers.....	103
Table 5-30: Connection of SpaceFibre lane using Type-A flight fibre optic cable assemblies .....	105
Table 5-31: Type-B flight fibre optic cable assembly connector contact terminations for each SpaceFibre lane .....	107
Table 5-32: Type-C flight active optical cable connector terminations for each SpaceFibre lane .....	109
Table 5-33: Type-C flight active optical cable assembly connector contact terminations for each SpaceFibre lane .....	110
Table 5-34: Precedence for different qualities of service .....	158
Table 5-35: Routing switch addresses .....	204
Table 5-36: SpaceFibre configuration parameters .....	216
Table 5-37: SpaceFibre status parameters.....	219