

ISO 22181:2021-02 (E)

Aerospace fluid systems and components - Variable displacement hydraulic motors - General specifications

Contents		Page
Foreword		vi
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Classification	7
5	General requirements	7
5.1	Order of precedence	7
5.2	Hydraulic system characteristics	7
5.3	Airworthiness regulations	8
5.4	Qualification	8
6	Functional requirements	8
6.1	Hydraulic fluid	8
6.2	Pressures	8
6.2.1	Rated supply pressure	8
6.2.2	Rated differential pressure	8
6.2.3	No-load break-out pressure	8
6.2.4	Motor return port pressure	9
6.2.5	Case drain pressure	9
6.3	Flows	9
6.3.1	Rated consumption	9
6.3.2	Case drain flow	9
6.3.3	Shaft seal leakage	10
6.3.4	External leakage	10
6.4	Speed and direction of rotation	10
6.4.1	Speed	10
6.5	Torque	11
6.5.1	Rated torque	11
6.5.2	Break-out torque	11
6.5.3	Stalling torque	11
6.5.4	Maximum stalling torque	11
6.5.5	Torque pulsations	11
6.6	Variable output load control	11
6.6.1	General	11
6.6.2	Response time	12
6.6.3	Stability	12
6.7	Motor overall efficiency	12
6.8	Dynamic characteristics	13
6.8.1	General	13
6.8.2	Dynamic braking	13
6.8.3	Rapid reversals	13
6.9	Passive operation	13
6.10	Fluid and ambient temperature	13
6.10.1	Fluid temperature	13

6.10.2	Ambient temperature	13
6.11	Acoustic noise level	14
6.12	Rated endurance	14
6.13	Environmental requirements	14
7	Detail design requirements	15
7.1	Dimensionally critical components	15
7.2	Maintainability features	15
7.3	Seals	15
7.4	Lubrication	15
7.5	Balance	15
7.6	Self-contained failure	16
7.7	Safety wire sealing	16
7.8	Electro-conductive bonding	16
7.9	Marking	16
7.9.1	Nameplate	16
7.9.2	Modification standard	16
7.9.3	Fluid identification	16
7.9.4	Ports	16
8	Strength requirements	17
8.1	General	17
8.2	Proof pressure	17
8.2.1	Motor case	17
8.2.2	Motor inlet port	17
8.2.3	Motor return port	17
8.3	Ultimate pressure	17
8.3.1	Motor case	17
8.3.2	Motor inlet port	17
8.3.3	Motor return port	17
8.4	Pressure impulse (fatigue)	17
8.5	Port strength	18
9	Construction requirements	18
9.1	Materials	18
9.1.1	General	18
9.1.2	Metals	18
9.2	Corrosion protection	18
9.2.1	General	18
9.2.2	Ferrous and copper alloys	19
9.2.3	Aluminium alloys	19
9.3	Castings	19
10	Installation requirements	19
10.1	Dimensions	19
10.2	Mass	19
10.3	Mounting	20
10.4	Orientation	20
10.5	Drive shaft	20
10.6	Ports	20
11	Maintenance requirements	21
11.1	Maintenance concept	21
11.2	Service life limitations and storage specifications	21
12	Reliability requirements	21
12.1	Equipment compliance	21
12.2	Requirements	21
13	Quality assurance provisions	21
13.1	Responsibility for inspection	21

13.2	Classification of tests	21
13.3	Test stand requirements	22
14	Acceptance tests	22
14.1	General	22
14.2	Examination of the product	22
14.3	Test programme	23
14.3.1	General	23
14.3.2	External leakage requirements	23
14.3.3	Break-in run	23
14.3.4	Proof pressure and overspeed tests	23
14.3.5	Operational tests at rated conditions	24
14.3.6	Break-out torque test	24
14.3.7	Teardown inspection examination	24
14.3.8	Run-in	25
14.3.9	Speed control test	25
14.3.10	Performance data	25
14.3.11	Fluid contamination test	26
14.4	Storage and packaging	27
15	Qualification procedures	27
15.1	General	27
15.2	Qualification procedure	27
15.2.1	Qualification by analogy	27
15.2.2	Motor qualification test report	27
15.2.3	Samples and program of qualification tests	27
15.3	Qualification testing	28
15.3.1	Dimensional check	28
15.3.2	Expanded envelope acceptance tests	28
15.3.3	Overspeed test	28
15.3.4	Operational test at overpressure	29
15.3.5	Calibration	29
15.3.6	Endurance testing	31
15.3.7	Environmental tests	34
15.3.8	Structural tests	35
15.3.9	Combination tests	37
15.3.10	Supplementary tests	37
	Bibliography	38