

# ISO 24071:2022-08 (E)

## Aircraft - Auto-transformer rectifier units (ATRU) - General requirements

---

| <b>Contents</b>    |   | <b>Page</b> |
|--------------------|---|-------------|
| Foreword .....     |   | v           |
| Introduction ..... |   | vi          |
| <b>1</b>           | <b>Scope .....</b>  | <b>1</b>    |
| <b>2</b>           | <b>Normative references .....</b>                         | <b>1</b>    |
| <b>3</b>           | <b>Terms and definitions .....</b>                        | <b>1</b>    |
| <b>4</b>           | <b>General requirements .....</b>                         | <b>1</b>    |
| 4.1                | Specification sheets .....                                | 1           |
| 4.2                | Materials .....   | 1           |
| 4.2.1              | Selection of materials .....                              | 1           |
| 4.2.2              | Metal materials .....                                     | 1           |
| 4.2.3              | Non-metal materials .....                                 | 2           |
| 4.3                | Design and construction .....                             | 2           |
| 4.3.1              | General mechanical and electrical design .....            | 2           |
| 4.3.2              | Electrical design .....                                   | 2           |
| 4.3.3              | Mechanical design .....                                   | 3           |
| 4.4                | Size and mass .....                                       | 4           |
| 4.5                | Colour .....  | 4           |
| 4.6                | Processing quality and appearance quality .....           | 4           |
| 4.6.1              | Processing quality .....                                  | 4           |
| 4.6.2              | Appearance quality .....                                  | 4           |
| 4.7                | Markings .....  | 4           |
| 4.7.1              | Components and parts .....                                | 4           |
| 4.7.2              | Nameplate of ATRUs .....                                  | 4           |
| 4.8                | Performance .....   | 5           |
| 4.8.1              | Input power .....   | 5           |
| 4.8.2              | Output power .....  | 5           |
| 4.8.3              | Efficiency .....  | 7           |
| 4.8.4              | Overload .....  | 7           |
| 4.8.5              | Short circuit .....                                       | 7           |
| 4.8.6              | Soft starting .....                                       | 7           |
| 4.8.7              | Insulation resistance and dielectric strength .....       | 8           |
| 4.8.8              | Influence on the input power system .....                 | 8           |
| 4.8.9              | Electrical protection .....                               | 8           |
| 4.9                | Acoustical noise .....                                    | 8           |
| 4.10               | Reliability .....   | 8           |
| 4.11               | Maintainability .....                                     | 8           |
| 4.12               | Interchangeability .....                                  | 9           |
| <b>5</b>           | <b>Environmental conditions and test procedures .....</b> | <b>9</b>    |
| <b>6</b>           | <b>Qualification inspection .....</b>                     | <b>10</b>   |
| 6.1                | General .....   | 10          |
| 6.2                | Methods of inspection .....                               | 10          |
| 6.2.1              | Processing quality and appearance quality .....           | 10          |
| 6.2.2              | Colour .....  | 11          |
| 6.2.3              | Markings .....  | 11          |
| 6.2.4              | Size and mass .....                                       | 11          |

|        |   |    |
|--------|---|----|
| 6.2.5  | Insulation resistance and dielectric strength ..... | 11 |
| 6.2.6  | Normal steady-state input voltage .....             | 11 |
| 6.2.7  | Abnormal steady-state input voltage .....           | 11 |
| 6.2.8  | Input voltage spikes .....                          | 12 |
| 6.2.9  | Input power interruptions .....                     | 12 |
| 6.2.10 | Input frequency transients .....                    | 12 |
| 6.2.11 | Output voltage ripple .....                         | 12 |
| 6.2.12 | Output voltage frequency characteristics .....      | 12 |
| 6.2.13 | Output voltage distortion factor .....              | 12 |
| 6.2.14 | Output voltage transients .....                     | 12 |
| 6.2.15 | Output power interruptions .....                    | 13 |
| 6.2.16 | Efficiency .....                                    | 13 |
| 6.2.17 | Overload .....                                      | 13 |
| 6.2.18 | Short circuit .....                                 | 13 |
| 6.2.19 | Soft starting .....                                 | 13 |
| 6.2.20 | Influence on the input power system .....           | 13 |
| 6.2.21 | Electrical protection .....                         | 13 |
| 6.2.22 | Acoustical noise .....                              | 13 |
| 6.2.23 | Reliability .....                                   | 13 |
| 6.2.24 | Maintainability .....                               | 14 |
| 6.2.25 | Interchangeability .....                            | 14 |