

DIN EN 14607-2:2006-12 (E)

Space engineering - Mechanical - Part 2: Structural; English version EN 14607-2:2004

| Contents | page |
|---|-------------|
| Foreword | 5 |
| 1 Scope | 7 |
| 2 Normative references..... | 7 |
| 3 Terms, definitions, abbreviated terms and units | 7 |
| 3.1 Terms and definitions | 7 |
| 3.2 Abbreviated terms | 10 |
| 4 Requirements..... | 11 |
| 4.1 General | 11 |
| 4.2 Mission | 11 |
| 4.2.1 Lifetime | 11 |
| 4.2.2 Natural and induced environment | 12 |
| 4.2.3 Mechanical environment | 12 |
| 4.2.4 Microgravity, audible noise and human vibration | 13 |
| 4.2.5 Corrosion effects..... | 13 |
| 4.2.6 Ablation and pyrolysis | 13 |
| 4.2.7 Micrometeoroid and debris collision..... | 13 |
| 4.2.8 Venting and purging..... | 13 |
| 4.2.9 Mass and inertia properties..... | 13 |
| 4.2.10 Load events..... | 14 |
| 4.2.11 Limit loads..... | 15 |
| 4.2.12 Design loads | 15 |
| 4.2.13 Structural reliability | 15 |
| 4.3 Functionality | 16 |
| 4.3.1 Strength | 16 |
| 4.3.2 Buckling | 16 |
| 4.3.3 Stiffness | 16 |
| 4.3.4 Dynamic behaviour | 16 |
| 4.3.5 Thermal..... | 16 |
| 4.3.6 Pressure | 17 |
| 4.3.7 Damage tolerance..... | 17 |
| 4.3.8 Fracture control | 17 |
| 4.3.9 Tolerances and alignments | 18 |
| 4.3.10 Electrical conductivity | 18 |
| 4.3.11 Lightning protection..... | 18 |
| 4.3.12 Electromagnetic compatibility | 18 |
| 4.3.13 Dimensional stability..... | 18 |
| 4.4 Constraints..... | 18 |
| 4.5 Interface..... | 18 |
| 4.6 Design..... | 19 |
| 4.6.1 Inspectability..... | 19 |
| 4.6.2 Interchangeability..... | 20 |
| 4.6.3 Maintainability..... | 20 |
| 4.6.4 Availability..... | 20 |
| 4.6.5 Design concept..... | 20 |
| 4.6.6 Design optimization | 21 |
| 4.6.7 Material allowables..... | 21 |
| 4.6.8 Metals | 22 |
| 4.6.9 Non- metallic materials | 22 |
| 4.6.10 Composite fibre reinforced materials..... | 23 |
| 4.6.11 Adhesive materials in bonded joints..... | 23 |
| 4.6.12 Margin of safety (MOS) | 23 |

| | | |
|--------|--|----|
| 4.6.13 | Factors of safety (FOS) | 23 |
| 4.6.14 | Scatter factors | 24 |
| 4.7 | Verification | 24 |
| 4.7.1 | General verification | 24 |
| 4.7.2 | Verification by analysis | 24 |
| 4.7.3 | Modelling aspects | 24 |
| 4.7.4 | Static analysis | 25 |
| 4.7.5 | Modal analysis | 25 |
| 4.7.6 | Response analysis | 25 |
| 4.7.7 | Acoustics analysis | 25 |
| 4.7.8 | Fluid structure interaction (FSI) | 25 |
| 4.7.9 | Fatigue analysis | 26 |
| 4.7.10 | Fracture mechanics analysis | 26 |
| 4.7.11 | Verification of composite structures | 26 |
| 4.7.12 | Buckling analysis | 26 |
| 4.7.13 | Thermo-elastic analysis | 26 |
| 4.7.14 | Adhesive connections | 26 |
| 4.7.15 | Bolted connections | 27 |
| 4.7.16 | Welded connections | 27 |
| 4.7.17 | Riveted connections | 27 |
| 4.7.18 | Insert connections | 27 |
| 4.7.19 | Aeroelasticity | 27 |
| 4.7.20 | Mass and inertia properties | 27 |
| 4.7.21 | Alignments | 27 |
| 4.7.22 | Dimensional stability | 27 |
| 4.7.23 | Microgravity, audible noise and human vibration analysis | 28 |
| 4.7.24 | Verification by test | 28 |
| 4.7.25 | Static test | 28 |
| 4.7.26 | Modal survey test | 29 |
| 4.7.27 | Dynamic tests: sine, random, shock | 29 |
| 4.7.28 | Acoustic test | 29 |
| 4.7.29 | Fatigue and fracture test | 29 |
| 4.7.30 | Microgravity, audible noise and human vibration tests | 29 |
| 4.7.31 | Non- destructive inspection and test | 30 |
| 4.7.32 | Thermal stress and distortion test | 30 |
| 4.7.33 | Thermal cycling test | 30 |
| 4.7.34 | Ageing test | 30 |
| 4.7.35 | Contamination test | 30 |
| 4.7.36 | Mass and Inertia properties measurement | 30 |
| 4.7.37 | Alignment checks | 30 |
| 4.7.38 | Dimensional stability tests | 30 |
| 4.7.39 | Geometrical control | 30 |
| 4.7.40 | Interface verification | 30 |
| 4.7.41 | Aerothermodynamic test | 31 |
| 4.7.42 | Aeroelasticity test | 31 |
| 4.7.43 | Lightning protection verification | 31 |
| 4.8 | Production and manufacturing | 31 |
| 4.8.1 | General | 31 |
| 4.8.2 | Procurement | 31 |
| 4.8.3 | Manufacturing process | 31 |
| 4.8.4 | Manufacturing drawings | 31 |
| 4.8.5 | Tooling | 32 |
| 4.8.6 | Component manufacture | 32 |
| 4.8.7 | Assembly | 32 |
| 4.8.8 | Storage | 33 |
| 4.8.9 | Cleanliness | 33 |
| 4.8.10 | Health and safety | 33 |
| 4.9 | In-service | 33 |
| 4.9.1 | Ground inspection | 33 |
| 4.9.2 | In-orbit inspection | 33 |
| 4.9.3 | Evaluation of damage | 34 |
| 4.9.4 | Maintenance | 34 |

| | | |
|--|--|----|
| 4.9.5 | Repair | 35 |
| 4.10 | Data exchange | 35 |
| 4.10.1 | General | 35 |
| 4.10.2 | System and structure subsystem..... | 36 |
| 4.10.3 | Design and manufacturing..... | 36 |
| 4.10.4 | Design and structural analysis | 36 |
| 4.10.5 | Other subsystem and structural analysis..... | 36 |
| 4.10.6 | Tests and structural analysis..... | 36 |
| 4.10.7 | Structural mathematical models..... | 36 |
| 4.11 | Product assurance | 37 |
| 4.11.1 | General | 37 |
| 4.11.2 | Model traceability | 37 |
| 4.12 | Deliverables | 37 |
| 4.12.1 | General | 37 |
| 4.12.2 | Documents | 37 |
| Annex A (informative) Effective mass definition..... | | 40 |
| Annex B (informative) Spacecraft (STM approach) development assumptions..... | | 43 |
| B.1 | Development assumptions..... | 43 |
| B.2 | Loads and factors relationship | 43 |
| B.3 | Common factors values..... | 44 |
| Annex C (informative) Launcher structural element | | 46 |
| C.1 | Development assumptions..... | 46 |
| C.2 | Loads and factors relationships | 46 |
| C.3 | Common factors values for ARIANE..... | 47 |