

# ISO 23933:2006-01 (E)

Aerospace - Aramid reinforced lightweight polytetrafluoroethylene (PTFE) hose assemblies, classification 135 °C/20.684 kPa (275 °F/3.000 psi) and 135 °C/21.000 kPa (275 °F/3.046 psi) - Procurement specification

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Classification .....</b>	<b>2</b>
<b>4</b>	<b>Requirements .....</b>	<b>2</b>
4.1	Limits of application .....	2
4.2	Qualification .....	2
4.3	Materials .....	2
4.4	Construction .....	3
4.5	Inner tube requirements .....	4
4.6	Hose assembly .....	5
4.7	Fitting threads .....	6
4.8	Part numbering of interchangeable parts .....	7
4.9	Identification of products .....	7
4.10	Workmanship .....	7
4.11	Hose assembly -- Test and performance requirements .....	8
<b>5</b>	<b>Quality assurance .....</b>	<b>12</b>
5.1	Responsibility for inspection .....	12
5.2	Classification of inspections .....	12
5.3	Qualification inspections .....	12
5.4	Quality conformance inspections .....	15
5.5	Test conditions .....	16
5.6	Inspection methods .....	17
<b>6</b>	<b>Preparation for delivery .....</b>	<b>18</b>
6.1	Storage and packaging .....	18
6.2	Marking .....	18
<b>7</b>	<b>Ordering data .....</b>	<b>18</b>
<b>Annex A (informative) Equivalent materials .....</b>		<b>19</b>
<b>Annex B (informative) Qualification procedures and fire resistance specifications .....</b>		<b>21</b>
<b>Bibliography .....</b>		<b>22</b>