ISO 7169:2007-02 (E)

Aerospace - Separable tube fittings for fluid systems, for 24° cones, for pressures up to 3000 psi or 2100 0 kPa - Procurement specification, inch/metric

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Classification 1

4 Requirements 2
4.1 Qualification 2
4.1.1 Manufacturer qualification 2
4.1.2 Product qualification 2
4.2 Materials 2
4.2.1 Fittings 2
4.2.2 Tubing 2
4.3 Design and manufacture 5
4.3.1 Threads 5
4.3.2 Fluid passages 5
4.4 Surface protection and colour identification 5
4.4.1 Surface protection 5
4.4.2 Colour identification 6
4.5 Marking 6
4.6 Performance 6
4.6.1 Proof pressure 6
4.6.2 Gaseous pressure 7
4.6.3 Hydraulic impulse resistance 7
4.6.4 Minimum burst pressure 7
4.6.5 Flexure fatigue resistance 7
4.6.6 Re-use capability 8
4.6.7 Tensile load capability 8
4.7 Workmanship 8

5 Quality assurance provisions 9
5.1 Responsibility for inspection 9
5.2 Inspection lot 9
5.2.1 Material certification 10
5.2.2 Heat-treating certification 10
5.3 Classification of inspections and tests 10
5.3.1 Qualification inspection 10
5.3.2 Quality conformance inspection 10
5.4 Quality control records 11
5.5 Quality conformance inspection procedures 11
5.5.1 Examination of product 11
5.5.2 Material certification 11
5.5.3 Rolled threads 11
5.5.4 Fluid passages 11
5.5.5 Sampling instructions 12
5.6 Test conditions 12
5.6.1 Test fluids 12

5.6.2 Specimen preparation 12
5.6.3 Lubricants 15
5.6.4 Qualification test procedures 15
5.6.5 Sampling instructions 15

6 Preparation for delivery 15
6.1 Cleaning 15
6.2 Preservative material 16
6.3 Packaging 16
6.4 Package identification 16
6.5 Packing for shipment 16
6.6 Inspection 16

Annex A (informative) Equivalent materials and processes 17

Bibliography 20