

# DIN EN 15586:2008-09 (E)

## Textiles - Methods of testing the fibre proof properties of fabrics: Rubbing test

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>4</b>
<b>4</b>	<b>Principle .....</b>	<b>4</b>
<b>5</b>	<b>Apparatus .....</b>	<b>4</b>
<b>5.1</b>	<b>Rubbing apparatus .....</b>	<b>4</b>
<b>5.2</b>	<b>Thickness tester .....</b>	<b>5</b>
<b>5.3</b>	<b>UV-light source .....</b>	<b>5</b>
<b>5.4</b>	<b>Magnification device .....</b>	<b>5</b>
<b>6</b>	<b>Materials .....</b>	<b>5</b>
<b>6.1</b>	<b>Protective fabric (for wadding test) .....</b>	<b>5</b>
<b>6.2</b>	<b>Additional fibres (for wadding test) .....</b>	<b>5</b>
<b>7</b>	<b>Atmosphere for conditioning and testing .....</b>	<b>5</b>
<b>8</b>	<b>Preparation of test cushions .....</b>	<b>5</b>
<b>8.1</b>	<b>Specimens for testing loose fibres as filling material .....</b>	<b>5</b>
<b>8.2</b>	<b>Specimens for testing wadding .....</b>	<b>8</b>
<b>9</b>	<b>Procedure .....</b>	<b>12</b>
<b>10</b>	<b>Test report .....</b>	<b>13</b>