

DIN EN ISO 11782-2:2008-08 (E)

Corrosion of metals and alloys - Corrosion fatigue testing - Part 2: Crack propagation testing using precracked specimens (ISO 11782-2:1998)

Contents		Page
Foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Definitions	5
4	Test	7
4.1	Principle of corrosion fatigue crack propagation testing	7
4.2	Specimens for corrosion fatigue crack propagation testing	8
4.2.1	General	8
4.2.2	Specimen design	8
4.2.3	Stress intensity factor considerations	8
4.2.4	Specimen preparation	9
4.2.5	Specimen identification	9
5	Apparatus	9
5.1	Environmental chamber	9
5.2	Crack length measurement	9
6	Fatigue precracking	10
6.1	General	10
6.2	Precracking procedure	10
6.3	Precracking for low crack growth rates or K _{th} determination	10
7	Test conditions	11
7.1	Environmental considerations	11
7.2	Stressing considerations	12
7.2.1	Cyclic frequency	12
7.2.2	Stress ratio	12
7.2.3	Waveform	12
7.2.4	Crack tip shielding (closure) effects	12
8	Test procedure	13
8.1	General	13
8.2	Starting procedure	13
8.3	Environmental control and monitoring	13
8.4	Determination of corrosion fatigue crack propagation rates	13
8.4.1	Length of crack	13
8.4.2	Growth rate of crack	14
8.5	Determination of corrosion fatigue threshold stress intensity factor range	15
9	Test report	15
Anhang A (informative) Information on methods for measuring crack lengths		17
A.1	Visual methods	17
A.2	Electrical resistance measurement methods	17
A.2.1	DC potential drop method	17
A.2.2	AC potential drop methods	18
A.3	Compliance methods	18