

# DIN EN ISO 12732:2008-07 (E)

## Corrosion of metals and alloys - Electrochemical potentiokinetic reactivation measurement using the double loop method (based on Cihal's method) (ISO 12732:2006)

---

<b>Contents</b>		Page
Foreword.....		3
1	<b>Scope</b> .....	4
2	<b>Normative references</b> .....	4
3	<b>Terms and definitions</b> .....	4
4	<b>Principle</b> .....	5
5	<b>Apparatus</b> .....	6
6	<b>Test solutions</b> .....	8
7	<b>Test specimen preparation</b> .....	8
8	<b>Procedure</b> .....	8
9	<b>Metallographic inspection</b> .....	9
10	<b>Evaluation of results</b> .....	9
11	<b>Test report</b> .....	10
<b>Annex A</b> (informative) <b>Flushed port cell and flushed electrode holder</b> .....		12
<b>Annex B</b> (informative) <b>Potential of selected reference electrodes at 25 °C with respect to the standard hydrogen electrode (SHE)</b> .....		15
<b>Annex C</b> (informative) <b>Suggested method for sensitizing test specimens</b> .....		16
<b>Annex D</b> (informative) <b>Correlation of <math>I_r/I_p</math> with the degree of grain-boundary sensitization, <math>P_a</math> (ASTM G108), <math>Q_{GBA}</math> and <math>Q_{GBL}</math></b> .....		17