

# ISO 15548-1:2008-09 (E)

## Non-destructive testing - Equipment for eddy current examination - Part 1: Instrument characteristics and verification

---

| Contents                                                                | Page |
|-------------------------------------------------------------------------|------|
| Foreword .....                                                          | v    |
| 1 Scope .....                                                           | 1    |
| 2 Normative references .....                                            | 1    |
| 3 Terms and definitions .....                                           | 1    |
| 4 Eddy current instrument characteristics .....                         | 1    |
| 4.1 General characteristics .....                                       | 1    |
| 4.1.1 Type of instrument .....                                          | 1    |
| 4.1.2 Power supply .....                                                | 2    |
| 4.1.3 Safety .....                                                      | 2    |
| 4.1.4 Technology .....                                                  | 2    |
| 4.1.5 Physical presentation .....                                       | 2    |
| 4.1.6 Environmental effects .....                                       | 2    |
| 4.2 Electrical characteristics .....                                    | 2    |
| 4.2.1 General .....                                                     | 2    |
| 4.2.2 Functional block diagram .....                                    | 3    |
| 4.2.3 Generator unit .....                                              | 3    |
| 4.2.4 Input stage characteristics .....                                 | 4    |
| 4.2.5 Balance .....                                                     | 4    |
| 4.2.6 High-frequency signal processing .....                            | 4    |
| 4.2.7 Demodulated signal processing .....                               | 5    |
| 4.2.8 Output and signal display .....                                   | 6    |
| 4.2.9 Digitization .....                                                | 7    |
| 5 Verification .....                                                    | 7    |
| 5.1 General .....                                                       | 7    |
| 5.2 Levels of verification .....                                        | 8    |
| 5.3 Verification procedure .....                                        | 9    |
| 5.4 Corrective actions .....                                            | 9    |
| 6 Measurement of the electrical characteristics of the instrument ..... | 9    |
| 6.1 Measuring requirements .....                                        | 9    |
| 6.2 Generator unit .....                                                | 9    |
| 6.2.1 Excitation frequency .....                                        | 9    |
| 6.2.2 Harmonic distortion .....                                         | 10   |
| 6.2.3 Source impedance .....                                            | 11   |
| 6.2.4 Maximum output voltage, $V_{Omax}$ .....                          | 12   |
| 6.2.5 Maximum output current, $I_{Omax}$ .....                          | 12   |
| 6.3 Input stage characteristics .....                                   | 13   |
| 6.3.1 Maximum allowable input voltage .....                             | 13   |
| 6.3.2 Input impedance .....                                             | 14   |
| 6.4 Signal processing .....                                             | 14   |
| 6.4.1 General .....                                                     | 14   |
| 6.4.2 Measurement conditions .....                                      | 15   |
| 6.4.3 Balance .....                                                     | 15   |
| 6.4.4 Harmonic attenuation .....                                        | 16   |
| 6.4.5 Frequency response of the signal processing stage .....           | 16   |
| 6.4.6 Bandwidth .....                                                   | 18   |

|                                                                                                                |                                   |    |
|----------------------------------------------------------------------------------------------------------------|-----------------------------------|----|
| 6.4.7                                                                                                          | Phase linearity .....             | 18 |
| 6.4.8                                                                                                          | Orthogonality of components ..... | 19 |
| 6.4.9                                                                                                          | Gain-setting accuracy .....       | 20 |
| 6.4.10                                                                                                         | Phase-setting accuracy .....      | 20 |
| 6.4.11                                                                                                         | Cross-talk .....                  | 21 |
| 6.4.12                                                                                                         | Common-mode rejection .....       | 22 |
| 6.4.13                                                                                                         | Maximum instrument noise .....    | 23 |
| 6.5                                                                                                            | Output .....                      | 24 |
| 6.6                                                                                                            | Digitization .....                | 24 |
| Annex A (informative) Principle of frequency beat method .....                                                 |                                   | 25 |
| Annex B (informative) Method of measurement of the linearity range between an output O and an<br>input I ..... |                                   | 27 |
| Annex C (normative) Alternative measurement of the input impedance .....                                       |                                   | 28 |