

DIN EN 12668-1:2010-05 (E)

Non-destructive testing - Characterization and verification of ultrasonic examination equipment - Part 1: Instruments

| Contents | | Page |
|---------------------|---|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Symbols | 7 |
| 5 | General requirements for compliance | 8 |
| 6 | Manufacturer's technical specification for ultrasonic instruments | 9 |
| 6.1 | General | 9 |
| 6.2 | General attributes | 9 |
| 6.3 | Display | 9 |
| 6.4 | Transmitter | 10 |
| 6.5 | Receiver and attenuator | 10 |
| 6.6 | Monitor output | 11 |
| 6.7 | Additional information | 11 |
| 7 | Performance requirements for ultrasonic instruments | 11 |
| 8 | Group 1 tests | 13 |
| 8.1 | Equipment required for group 1 tests | 13 |
| 8.2 | Stability against temperature | 14 |
| 8.3 | Stability against voltage variation | 16 |
| 8.4 | Transmitter pulse parameters | 16 |
| 8.5 | Receiver | 18 |
| 8.6 | Monitor gate | 21 |
| 8.7 | Monitor gates with proportional output | 22 |
| 8.8 | Digital ultrasonic instruments | 26 |
| 9 | Group 2 tests | 27 |
| 9.1 | Equipment required for group 2 tests | 27 |
| 9.2 | Physical state and external aspects | 28 |
| 9.3 | Stability | 28 |
| 9.4 | Transmitter pulse parameters | 29 |
| 9.5 | Receiver | 30 |
| 9.6 | Linearity of time-base | 32 |
| Annex A (normative) | Special conditions for ultrasonic instruments with logarithmic amplifiers | 44 |
| A.1 | Introduction | 44 |
| A.2 | Basic requirements | 44 |
| A.2.1 | Measuring accuracy | 44 |
| A.2.2 | Vertical display "linearity" | 44 |
| A.3 | Tests | 44 |
| Bibliography | | 45 |