DIN EN 1071-12:2010-07 (E)

Advanced technical ceramics - Methods of test for ceramic coatings - Part 12: Reciprocating wear test

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Significance and use 7

5 Principle 7

6 Apparatus and materials 7
6.1 Apparatus construction 7
6.1.1 General 7
6.1.2 Friction measurement 9
6.2 Operating environment 9

7 Preparation of test pieces 9
7.1 Substrate material and preparation 9
7.2 Coating deposition 10
7.3 Post-coating preparation 10
7.4 Cleaning 11

8 Test procedure 11
8.1 Selection of test conditions 11
8.2 Preliminary set-up 11
8.3 Wear test 12
8.4 Evaluation of wear 13
8.4.1 Preliminary inspection 13
8.4.2 Measurement of wear scars 14
8.5 Calculation of wear results 16

9 Repeatability and limits 16

10 Test report 17

Annex A (informative) Issues related to dynamic measurements in reciprocating wear testing 18

A.1 Resonant frequencies 18
A.2 Frequency response 18
A.3 Phase angle errors 19
A.4 Further guidance 21

Annex B (informative) Methods for the determination of coating properties likely to be relevant to coating performance in a reciprocating wear test 22

B.1 Relevant properties 22
B.2 Phase composition and preferred orientation 22

B.3 Residual stress 22
B.4 Hardness 22

Annex C (informative) Examples of common wear mechanisms 23

Annex D (informative) Determination of volume loss from the pin using profilometry 24

Annex E (informative) Determination of wear of coated plate by ball crater technique 25

Bibliography 28