

# DIN EN ISO 2440:2010-06 (E)

## Flexible and rigid cellular polymeric materials - Accelerated ageing tests (ISO 2440:1997 + Amd 1:2010) (includes Amendment A1:2010)

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Apparatus .....</b>	<b>4</b>
<b>3.1</b>	<b>For heat ageing .....</b>	<b>4</b>
<b>3.2</b>	<b>For humidity ageing .....</b>	<b>4</b>
<b>3.3</b>	<b>For physical-property measurements .....</b>	<b>5</b>
<b>4</b>	<b>Test pieces .....</b>	<b>5</b>
<b>4.1</b>	<b>Number, size and shape .....</b>	<b>5</b>
<b>4.2</b>	<b>Conditioning .....</b>	<b>5</b>
<b>5</b>	<b>Procedure .....</b>	<b>5</b>
<b>5.1</b>	<b>General .....</b>	<b>5</b>
<b>5.2</b>	<b>Dry heat ageing .....</b>	<b>5</b>
<b>5.2.1</b>	<b>Temperatures .....</b>	<b>5</b>
<b>5.2.2</b>	<b>Duration of ageing .....</b>	<b>6</b>
<b>5.3</b>	<b>Humidity ageing .....</b>	<b>6</b>
<b>5.3.1</b>	<b>Humidity .....</b>	<b>6</b>
<b>5.3.2</b>	<b>Temperatures and duration of ageing .....</b>	<b>6</b>
<b>5.4</b>	<b>Reconditioning .....</b>	<b>6</b>
<b>6</b>	<b>Expression of results .....</b>	<b>6</b>
<b>6.1</b>	<b>Calculation .....</b>	<b>6</b>
<b>6.2</b>	<b>Format .....</b>	<b>7</b>
<b>7</b>	<b>Test report .....</b>	<b>7</b>