

# ISO 15653:2010-04 (E)

## Metallic materials - Method of test for the determination of quasistatic fracture toughness of welds

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Symbols and units .....	3
5	Principle .....	3
6	Choice of specimen design, specimen orientation and notch location .....	4
6.1	Classification of target area for notching .....	4
6.2	Specimen design .....	4
6.3	Specimen and crack plane orientation .....	4
7	Pre-machining metallography .....	8
7.1	Microstructural assessment of macrosections .....	8
7.2	Additional requirements for heat-affected zone tests .....	9
8	Machining .....	9
8.1	Tolerances on specimen dimensions .....	9
8.2	Notch placement for through-thickness notched specimens .....	10
8.3	Notch placement for surface-notched specimens .....	10
8.4	Notch machining .....	10
9	Specimen preparation .....	15
9.1	Fatigue precracking .....	15
9.2	Side grooving .....	15
10	Test apparatus, requirements and test procedure .....	15
11	Post-test metallography .....	15
11.1	General .....	15
11.2	Through-thickness notched specimens .....	16
11.3	Surface-notched specimens .....	16
11.4	Assessment of pop-in .....	16
12	Post-test analysis .....	19
12.1	Choice of tensile properties .....	19
12.2	K <sub>Ic</sub> .....	20
12.3	and J .....	20
12.4	Qualification requirements .....	20
13	Test report .....	24
Annex A (informative) Examples of notch locations .....		25
Annex B (informative) Examples of pre-test and post-test metallography .....		27

<b>Annex C (normative) Residual-stress modification and precracking technique .....</b>	<b>29</b>
<b>Annex D (normative) Assessment of pop-in .....</b>	<b>31</b>
<b>Annex E (informative) Shallow-notched specimen testing .....</b>	<b>37</b>
<b>Bibliography .....</b>	<b>41</b>