ISO 15653:2010-04 (E)

Metallic materials - Method of test for the determination of quasistatic fracture toughness of welds

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols and units 3

5 Principle 3

6 Choice of specimen design, specimen orientation and notch location 4
6.1 Classification of target area for notching 4
6.2 Specimen design 4
6.3 Specimen and crack plane orientation 4

7 Pre-machining metallography 8
7.1 Microstructural assessment of macrosections 8
7.2 Additional requirements for heat-affected zone tests 9

8 Machining 9
8.1 Tolerances on specimen dimensions 9
8.2 Notch placement for through-thickness notched specimens 10
8.3 Notch placement for surface-notched specimens 10
8.4 Notch machining 10

9 Specimen preparation 15
9.1 Fatigue precracking 15
9.2 Side grooving 15

10 Test apparatus, requirements and test procedure 15

11 Post-test metallography 15
11.1 General 15
11.2 Through-thickness notched specimens 16
11.3 Surface-notched specimens 16
11.4 Assessment of pop-in 16

12 Post-test analysis 19
12.1 Choice of tensile properties 19
12.2 KIc 20
12.3 and J 20
12.4 Qualification requirements 20

13 Test report 24

Annex A (informative) Examples of notch locations 25

Annex B (informative) Examples of pre-test and post-test metallography 27

Annex C (normative) Residual-stress modification and precracking technique 29

Annex D (normative) Assessment of pop-in 31

Annex E (informative) Shallow-notched specimen testing 37

Bibliography 41