

# ISO 28641:2010-06 (E)

## Rubber compounding ingredients - Organic chemicals - General test methods

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Abbreviations .....</b>	<b>2</b>
<b>4</b>	<b>General requirements .....</b>	<b>2</b>
<b>4.1</b>	<b>Thermometer .....</b>	<b>2</b>
<b>4.2</b>	<b>Dessicator .....</b>	<b>2</b>
<b>5</b>	<b>Sampling .....</b>	<b>2</b>
<b>5.1</b>	<b>Apparatus .....</b>	<b>2</b>
<b>5.2</b>	<b>Sampling method .....</b>	<b>2</b>
<b>6</b>	<b>Drying the sample .....</b>	<b>2</b>
<b>6.1</b>	<b>General .....</b>	<b>2</b>
<b>6.2</b>	<b>Drying methods for liquid compounding ingredients .....</b>	<b>2</b>
<b>6.3</b>	<b>Drying methods for solid compounding ingredients .....</b>	<b>3</b>
<b>7</b>	<b>Test methods .....</b>	<b>4</b>
<b>7.1</b>	<b>Relative density .....</b>	<b>4</b>
<b>7.2</b>	<b>Loss on heating .....</b>	<b>8</b>
<b>7.3</b>	<b>Sieve residue .....</b>	<b>10</b>
<b>7.4</b>	<b>pH of water extract .....</b>	<b>12</b>
<b>7.5</b>	<b>Melting point .....</b>	<b>14</b>
<b>7.6</b>	<b>Temperature of solidification .....</b>	<b>17</b>
<b>7.7</b>	<b>Softening point .....</b>	<b>20</b>
<b>7.8</b>	<b>Density of the bulk material .....</b>	<b>22</b>
<b>7.9</b>	<b>Ash .....</b>	<b>24</b>
<b>7.10</b>	<b>Refractive index .....</b>	<b>25</b>
<b>Annex A (informative) Examples of sampling apparatus .....</b>		<b>29</b>
<b>Annex B (informative) Examples of suitable drying apparatus .....</b>		<b>31</b>
<b>Annex C (normative) Verification of accuracy of pH-meter .....</b>		<b>34</b>
<b>Annex D (normative) Calibration of the pH-meter .....</b>		<b>38</b>
<b>Annex E (informative) Precision .....</b>		<b>40</b>
<b>Bibliography .....</b>		<b>47</b>