

# DIN EN 1007-7:2010-12 (E)

Advanced technical ceramics - Ceramic composites - Methods of test for reinforcements - Part 7: Determination of the distribution of tensile strength and of tensile strain to failure of filaments within a multifilament tow at high temperature

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>7</b>
<b>5</b>	<b>Principle .....</b>	<b>7</b>
<b>6</b>	<b>Significance and use .....</b>	<b>8</b>
<b>7</b>	<b>Apparatus .....</b>	<b>8</b>
7.1	Test machine .....	8
7.2	Load train .....	8
7.3	Adhesive .....	8
7.4	Test chamber .....	9
7.5	Set-up for heating .....	9
7.6	Temperature measurement .....	9
7.7	Data recording system .....	9
<b>8</b>	<b>Test procedure .....</b>	<b>9</b>
8.1	Test specimens .....	9
8.2	Test specimen preparation .....	10
8.3	Number of test specimens .....	12
8.4	Test Procedure .....	13
8.5	Calculation of results .....	17
<b>Annex A (informative) Derivation of the Young's modulus of the hot part of the tow .....</b>		<b>25</b>
<b>Bibliography .....</b>		<b>26</b>