

# ISO 48:2010-09 (E)

## Rubber, vulcanized or thermoplastic - Determination of hardness (hardness between 10 IRHD and 100 IRHD)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>2</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Principle .....</b>	<b>3</b>
<b>5</b>	<b>Apparatus .....</b>	<b>3</b>
<b>5.1</b>	<b>General .....</b>	<b>3</b>
<b>5.2</b>	<b>Methods N, H, L and M .....</b>	<b>3</b>
<b>5.3</b>	<b>Methods CN, CH, CL and CM .....</b>	<b>5</b>
<b>6</b>	<b>Test pieces .....</b>	<b>5</b>
<b>6.1</b>	<b>General .....</b>	<b>5</b>
<b>6.2</b>	<b>Methods N, H, L and M .....</b>	<b>6</b>
<b>6.3</b>	<b>Methods CN, CH, CL and CM .....</b>	<b>7</b>
<b>7</b>	<b>Time interval between vulcanization and testing .....</b>	<b>7</b>
<b>8</b>	<b>Conditioning of test pieces .....</b>	<b>7</b>
<b>9</b>	<b>Temperature of test .....</b>	<b>7</b>
<b>10</b>	<b>Procedure .....</b>	<b>7</b>
<b>11</b>	<b>Number of readings .....</b>	<b>8</b>
<b>12</b>	<b>Expression of results .....</b>	<b>8</b>
<b>13</b>	<b>Precision .....</b>	<b>8</b>
<b>14</b>	<b>Test report .....</b>	<b>11</b>
<b>Annex A (informative) Empirical relationship between indentation and hardness .....</b>		<b>12</b>
<b>Annex B (informative) Precision results from interlaboratory test programmes .....</b>		<b>14</b>
<b>Annex C (informative) Guidance for using precision results .....</b>		<b>22</b>
<b>Bibliography .....</b>		<b>23</b>