ISO/TS 11366:2011-03 (E)

Petroleum and related products - Guidance for in-servicing of lubricating oils for steam, gas and combined-cycle turbines

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Description of turbine oils 1

4 Factors affecting the service life 2
4.1 General 2
4.2 Oil system design 3
4.3 Conditions of the oil system at start-up 3
4.4 Original oil quality 3
4.5 System operating temperature 3
4.6 Contamination rates and provisions for purification 4
4.7 Oil make-up rates 4

5 Deterioration of turbine oils in service 4
5.1 General 4
5.2 Viscosity 4
5.3 Oxidation stability 4
5.4 Solid particles 5
5.5 Sludge 5
5.6 Antirust properties 5
5.7 Water separability 6
5.8 Foaming and air-release characteristics 6
5.9 Total acid number 7

6 Recommended tests and interpretation 7
6.1 Appearance and odour 7
6.2 Colour 7
6.3 Total acid number 7
6.4 Sludge and deposits 7
6.5 Particle counting 8
6.6 Kinematic viscosity 8
6.7 Remaining oxidation stability 8
6.8 Water content 9
6.9 Rust prevention characteristics 9
6.10 Water separability 9
6.11 Foaming characteristics 9
6.12 Air-release value 10
6.13 Flash point 10

7 Sampling 10
7.1 General 10
7.2 Sampling point 10
7.3 Sampling line 11
7.4 Containers 11
7.5 Samples marking 11

8 Examination of new oil 12
8.1 General 12
8.2 Sampling of new oil deliveries 12
8.3 Examination of new oil deliveries 13
8.4 Testing schedules 13

9 Examination of oils in service 15
9.1 Testing procedures 15
9.2 Frequency of the testing 18

Bibliography 20