

ISO 1817:2011-09 (E)

Rubber, vulcanized or thermoplastic - Determination of the effect of liquids

| Contents | | Page |
|--|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Apparatus | 1 |
| 4 | Calibration | 3 |
| 5 | Test liquids | 3 |
| 6 | Test pieces | 3 |
| 6.1 | Preparation | 3 |
| 6.2 | Dimensions | 4 |
| 6.3 | Time interval between vulcanization and testing | 4 |
| 6.4 | Conditioning | 4 |
| 7 | Immersion in the test liquid | 5 |
| 7.1 | Temperature | 5 |
| 7.2 | Duration | 5 |
| 8 | Procedure | 5 |
| 8.1 | General | 5 |
| 8.2 | Change in mass | 6 |
| 8.3 | Change in volume | 6 |
| 8.4 | Change in dimensions | 7 |
| 8.5 | Change in surface area | 8 |
| 8.6 | Change in hardness | 8 |
| 8.7 | Change in tensile stress-strain properties | 9 |
| 8.8 | Testing with liquid on one surface only | 9 |
| 8.9 | Determination of extractable matter | 10 |
| 9 | Test report | 11 |
| Annex A (normative) Reference liquids | | 12 |
| Annex B (normative) Calibration schedule | | 15 |