ISO 16827:2012-04 (E)

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Principles of characterization of discontinuities 1
3.1 General 1
3.2 Requirements for surface condition 2

4 Pulse echo techniques 2
4.1 General 2
4.2 Location of discontinuity 2
4.3 Orientation of discontinuity 2
4.4 Assessment of multiple indications 3
4.5 Shape of discontinuity 3
4.5.1 Simple classification 3
4.5.2 Detailed classification of shape 4
4.6 Maximum echo height of indication 4
4.7 Size of discontinuity 4
4.7.1 General 4
4.7.2 Maximum echo height techniques 4
4.7.3 Probe movement sizing techniques 5
4.7.4 Selection of sizing techniques 5
4.7.5 Sizing techniques with focussing ultrasonic probes 6
4.7.6 Use of mathematical algorithms for sizing 6
4.7.7 Special sizing techniques 6

5 Transmission technique 7
5.1 General 7
5.2 Location of discontinuity 7
5.3 Evaluation of multiple discontinuities 7
5.4 Reduction of signal amplitude 8
5.5 Sizing of discontinuity 8

Annex A (normative) Analysis of multiple indications 12

A.1 Lateral characterisation 12
A.2 Transverse (Through-thickness) characterisation 12
A.3 Shadow technique 12

Annex B (normative) Techniques for the classification of discontinuity shape 14

B.1 Simple classification 14
B.1.1 General 14
B.1.2 Reconstruction technique 14
B.1.3 Echo envelope technique 14
B.2 Detailed classification 14
B.2.1 General 14
B.2.2 Echodynamic pattern technique 15
B.2.3 Directional reflectivity 17

B.3 Combination of data 17

Annex C (informative) Maximum echo height sizing technique 25

C.1 Distance-gain-size (DGS) technique 25
C.1.1 Principle 25
C.1.2 Applications and limitations 25
C.2 Distance-amplitude-correction (DAC) curve technique 25
C.2.1 Principle 25

Introduction vi
C.2.2 Applications and limitations 26

Annex D (normative) Probe movement sizing techniques 27

D.1 Fixed amplitude level techniques 27
D.1.1 Principle 27
D.1.2 Application and limitations 27
D.2 6 dB drop from maximum technique 27
D.2.1 Principle 27
D.2.2 Application and limitations 27
D.3 12 dB or 20 dB drop from maximum technique 28
D.3.1 Principle 28
D.3.2 Application and limitations 28
D.4 Drop to noise level technique 28
D.4.1 Principle 28
D.4.2 Application and limitations 28
D.5 6 dB drop tip location technique 29
D.5.1 Principle 29
D.5.2 Application and limitations 29
D.6 Beam axis tip location technique 29
D.6.1 Principle 29
D.6.2 Application and limitations 29
D.7 20 dB drop tip location technique 30
D.7.1 Principle 30
D.7.2 Application and limitations 30

Annex E (normative) Iterative sizing technique 39

E.1 Scope 39
E.2 Normal incidence testing 39
E.2.1 Principle 39
E.2.2 Adjustment of gain 39
E.2.3 Procedure 39
E.3 Oblique incidence testing 40

Annex F (normative) Mathematical algorithms for the estimation of the actual size of a discontinuity 45

F.1 Large planar discontinuities 45
F.2 Small planar discontinuities 46
F.3 Planar discontinuities in a cylindrical test object 48

Annex G (informative) Examples of special sizing techniques 50

G.1 Tip diffraction techniques 50
G.2 Synthetic aperture focussing technique (SAFT) 51