

# ISO 4965-2:2012-07 (E)

## Metallic materials - Dynamic force calibration for uniaxial fatigue testing - Part 2: Dynamic calibration device (DCD) instrumentation

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Terms, definitions, and symbols .....</b>	<b>1</b>
<b>3</b>	<b>Principle .....</b>	<b>2</b>
<b>4</b>	<b>General requirements .....</b>	<b>2</b>
4.1	Temperature .....	2
4.2	DCD instrumentation .....	2
4.3	Dynamic voltage reference standard .....	2
<b>5</b>	<b>Calibration procedure .....</b>	<b>3</b>
5.1	DC calibration .....	3
5.2	Sinusoidal calibration .....	3
<b>6</b>	<b>Calculation of results .....</b>	<b>4</b>
6.1	DC calibration results .....	4
6.2	Sinusoidal calibration results .....	4
<b>7</b>	<b>Calibration report .....</b>	<b>5</b>
7.1	General information .....	5
7.2	Results of calibration .....	5
7.3	Re-calibration .....	5
<b>Annex A (informative) Calibration frequency content .....</b>		<b>6</b>
<b>Bibliography .....</b>		<b>9</b>