

# ISO 15632:2012-08 (E)

Microbeam analysis - Selected instrumental performance parameters for the specification and checking of energy-dispersive X-ray spectrometers for use in electron probe microanalysis

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Requirements .....</b>	<b>3</b>
4.1	General description .....	3
4.2	Energy resolution .....	3
4.3	Dead time .....	3
4.4	Peak-to-background ratio .....	4
4.5	Energy dependence of instrumental detection efficiency .....	4
<b>5</b>	<b>Check of further performance parameters .....</b>	<b>4</b>
5.1	General .....	4
5.2	Stability of the energy scale and resolution .....	4
5.3	Pile-up effects .....	4
5.4	Periodical check of spectrometer performance .....	5
<b>Annex A (normative) Measurement of line widths (FWHMs) to determine the energy resolution of the spectrometer .....</b>		<b>6</b>
<b>Annex B (normative) Determination of the L/K ratio as a measure for the energy dependence of the instrumental detection efficiency .....</b>		<b>9</b>
<b>Bibliography .....</b>		<b>11</b>