ISO 12108:2012-08 (E)

Metallic materials - Fatigue testing - Fatigue crack growth method

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols and abbreviated terms 3
4.1 Symbols 3
4.2 Abbreviatedtermsforspecimenidentification 4

5 Apparatus 5
5.1 Testing machine 5
5.2 Cycle-counter 5
5.3 GripsandfixturesforCTspecimens 5
5.4 GripsandfixturesforCCT/SENTspecimens 7
5.5 GripsandfixturesfortheSENBspecimens 11
5.6 Crack length measurement apparatus 11

6 Specimens 12
6.1 General 12
6.2 Crack plane orientation 16
6.3 Starter notch precracking details 18
6.4 Stress-intensity factor 20
6.5 Specimen size 21
6.6 Specimen thickness 22
6.7 Residual stresses 23

7 Procedure 23
7.1 Fatigue precracking 23
7.2 Crack length measurement 23
7.3 Constant-force-amplitude, -increasing, test procedure for da/dN > 10-5mm/cycle 24
7.4 K-decreasing procedure for da/dN < 10-5mm/cycle 25

8 Crack length measurement 27
8.1 Resolution 27
8.2 Interruption 27
8.3 Static force 27
8.4 Measurement interval 27
8.5 Symmetry 28
8.6 Out-of-plane cracking 28
8.7 Crack tip bifurcation 28

9 Calculations 28
9.1 Crack-front curvature 28
9.2 Determining the fatigue crack growth rate 28
9.3 Determination of the fatigue crack growth threshold 29

10 Test report 29

10.1 General 29
10.2 Material 29
10.3 Test specimen 30
10.4 Precracking terminal values 30
10.5 Test conditions 30
10.6 Test analysis 31
10.7 Presentation of results 31

AnnexA(informative) Non-visual crack length measurement methodology -- Electric potential difference [18] [24] [33] 38

Bibliography 41