ISO 1431-1:2012-08 (E)

Rubber, vulcanized or thermoplastic - Resistance to ozone cracking - Part 1: Static and dynamic strain testing

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Principle 2

5 Apparatus (see Figure 1) 2
5.1 Test chamber 2
5.2 Source of ozonized air 3
5.3 Means of adjusting the ozone concentration 4
5.4 Means of determining the ozone concentration 4
5.5 Meansofadjustingthegasflow 4
5.6 Mounting test pieces for static strain testing 4
5.7 Mounting test pieces for dynamic strain testing 5

6 Calibration 5

7 Test pieces 5
7.1 General 5
7.2 Wide test piece 6
7.3 Narrow test piece 6

8 Conditioning 6
8.1 Conditioning in the unstrained state 6
8.2 Conditioning in the strained state (for static strain testing only) 7

9 Test conditions 7
9.1 Ozone concentration 7
9.2 Temperature 7
9.3 Relative humidity 8
9.4 Maximum elongation 8

10 Static strain testing 8
10.1 General 8
10.2 Procedure A 8
10.3 Procedure B 8
10.4 Procedure C 8

11 Dynamic strain testing 9
11.1 General 9
11.2 Continuous dynamic exposure 9
11.3 Intermittent dynamic exposure 9

12 Expression of results 10
12.1 Procedure A 10
12.2 Procedure B 10
12.3 Procedure C (for static tests only) 10

13 Test report **11**

Annex A (informative) Ozone cracking -- Explanatory notes **13**

Annex B (normative) Calibration schedule **14**

Annex C (informative) Ozone cracking -- Rating scales **16**

Bibliography **17**