

# ISO 14603:2012-11 (E)

## Fine ceramics (advanced ceramics, advanced technical ceramics) - Test method for open-hole tension of continuous fibre-reinforced ceramic matrix composites at room temperature

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>2</b>
<b>5</b>	<b>Apparatus .....</b>	<b>2</b>
<b>5.1</b>	<b>Test machine .....</b>	<b>2</b>
<b>5.2</b>	<b>Load train and grip .....</b>	<b>2</b>
<b>5.3</b>	<b>Strain measurement .....</b>	<b>2</b>
<b>5.4</b>	<b>Data recording system .....</b>	<b>3</b>
<b>5.5</b>	<b>Dimension-measuring devices .....</b>	<b>3</b>
<b>6</b>	<b>Test specimens .....</b>	<b>3</b>
<b>7</b>	<b>Test specimen preparation .....</b>	<b>5</b>
<b>7.1</b>	<b>Machining and preparation .....</b>	<b>5</b>
<b>7.2</b>	<b>Number of test specimens .....</b>	<b>5</b>
<b>8</b>	<b>Test condition .....</b>	<b>5</b>
<b>9</b>	<b>Test procedure .....</b>	<b>5</b>
<b>9.1</b>	<b>Displacement or loading rate .....</b>	<b>5</b>
<b>9.2</b>	<b>Measurement of test specimen dimensions .....</b>	<b>5</b>
<b>9.3</b>	<b>Strain gauges .....</b>	<b>6</b>
<b>9.4</b>	<b>Bending load .....</b>	<b>6</b>
<b>9.5</b>	<b>Test specimen mounting .....</b>	<b>6</b>
<b>9.6</b>	<b>Measurement .....</b>	<b>6</b>
<b>9.7</b>	<b>Test validity .....</b>	<b>6</b>
<b>10</b>	<b>Calculation of results .....</b>	<b>7</b>
<b>10.1</b>	<b>Open-hole tensile strength .....</b>	<b>7</b>
<b>10.2</b>	<b>Average value, standard deviation and coefficient of variation .....</b>	<b>7</b>
<b>11</b>	<b>Test report .....</b>	<b>7</b>
<b>Bibliography .....</b>		<b>9</b>