ISO/TS 15029-2:2012-12 (E)

Petroleum and related products - Determination of spray ignition characteristics of fire-resistant fluids - Part 2: Spray test - Stabilized flame heat release method

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Principle 2

5 Reagents and materials 2

6 Apparatus 2
6.1 Test installation 2
6.2 Instrumentation 7

7 Sampling and sample preparation 9

8 Apparatus preparation 10

9 Procedure 10
9.1 Measurements at a propane flow rate of 0,13 Nm3/h 10
9.2 Measurements at a propane flow rate of 0,4 Nm3/h 11
9.3 Rejection of test data 11
9.4 Tabulation of measurements 12
9.5 Number of tests 12

10 Calculations 13
10.1 Ignitability factor 13
10.2 Flame length index 14
10.3 Smoke density 14

11 Expression of results 14
11.1 Individual results 14
11.2 Ranking system 14

12 Precision 15

13 Test report 15

Annex A (normative) Verification of propane pressure and flow rate 16

Annex B (normative) Verification of propane flame characteristics 17

Annex C (normative) Test apparatus calibration 22

Annex D (informative) Suggested fire-resistant classification scheme 24

Annex E (informative) Example pro-forma for test results 25

Bibliography 28